

18720 Crenshaw Boulevard,Torrance,CA90504 U.S.A http://www.quakysense.us E-Mail:info@quakysense.us



MODULAR FLOATING DOCK & PWC SYSTEMS

ARE YOU READY TO MAKE SOME WAVES?

The Wave Dock™ is a modular floating dock platform that revolutionizes the way lake and ocean home owners and marinas customize their floating dock systems; Available in an amazing new Pebble Beach textured finish, bringing a rich new look to the industry. With the proprietary patent pending H-Beam Channel Lock System™, these dock sections are infinitely modular, assemble quickly, and offer a solid connection platform with just the right mix of rigidity and flexibility. Each floating dock section is 60 inches wide x 120 inches long x 16 inches tall, allowing the system to be easily assembled into the exact configuration needed. With a full line of accessories and custom attachments the Wave Dock™ has set the new standard for modular floating dock systems. Visit us online at <u>www.wavearmor.net</u>



OFFICIAL SPONSOR OF TH



TIONAL JET SPORTS BOATING ASSO



TOYOTA NATIONAL TOUR

May 15-16: Super-Cup of watercross, Panama City Beach, FL

May 29-30: Toyota US Open of Watercross, Syracuse, NY

June 19-20: US Grand Prix of Watercross, Racine, WI

July 10-11: Toyota Water Jam, Rochester, NY

August 14-15: Triple Crown of watercross, Lake Hartwell, GA

August 20-22: Toyota Governor's Cup – UWP-IJSBA Nationals/ Charleston, WV& SportFEST 2010

Contact: AJ Handler

Phone: **214-498-3592** Email: <u>r5wxflyinbrian@hotmail.com</u> Web site: www.uwpinc.com



R5 Water X Racing

Round 1&2: May 22-23rd 2010 Genes Powersports, Baytown TX Round 3&4: June 19-20th 2010 Lake Madison, Madisonville TX (Music Festival) Round 5&6: July 3-4th 2010 The Liberty by the Lake Challenge The Colony TX Lake Lewisville Round 7&8 TBA July 3&4: 2010

IJSBA Endurance Nationals

Contact: Brian Smith



Phone: **214-498-3592** Email: **r<u>5wxflyinbrian@hotmail.com</u> Web site: www.r5waterxracing.com**

Nauti Water Racing

May 8-9 June 5-6 June 26-27 July 17-18 August 7-8



Contact: Terry Hiebert

Phone: 316-312-4049 Email: <u>nautiwater@live.com</u> Web site: <u>www.nautiwaterracing.com</u>



Race Dates Are:

April 24-25 June 26-27 July 31/Aug 1 Aug 28-29 Sep 18-19

Contact: David Pulley Phone: **951-609-3623** Web site: www.dmpmotorsport.com



We're in favor of closed courses...





And we oppose closed waters.

From the racers in Havasu to recreational riders from coast to coast, the AWA fights the good fight for the Good People.

We defeat two-stroke bans in Montana, keep waters open to PWC use in Texas, and fight against anti-PWC legislation from Florida to Washington state. The locations change, but the attacks on our personal freedoms will continue. The American Watercraft Association is committed to equal access for all on our

PWC organization, we need your commitment too. Become an AWA member, and add your voice to ours.

nation's waterways. As the only consumer based

Sign up for your membership now and we'll include a complimentary subscription to Ride PWC Magazine and its expanded Speed Zone section, featuring pages of extensive race and event coverage!!

Log on to awahq.org for membership details, and ...













FOREWORD

2010 Official Competition Rulebook The International Jet Sports Boating Association (IJSBA)

The International Jet Sports Boating Association (IJSBA) was formed to promote the safe use of personal watercraft, to provide regulated competition events, to formulate rules, to govern racing between these watercraft, to further the interest of its membership, and to act as an international governing and sanctioning body for the sport.

The objectives of the IJSBA are to encourage the promotion of safety in competition and in all events and activities, to foster strong and fair competition, and to provide an impartial events and competition program.

These rules for competition and special events are intended as a guide for the conduct of the sport pursuant to a uniform set of regulations. Changes made this year are based on previous season observations and experiences along with recommendations from competition members.

These rules govern the sanction, organization and conduct of IJSBA events as well as the eligibility of competitors and vehicles. Competitors can expect strict but fair enforcement of these rules.

Rules directed or related to safety are promulgated to ensure that everyone involved has a primary concern for safety. But each participant in IJSBA competition is responsible for assessing the safety aspects of the facilities and conditions, and personally assumes the risk of competition.

Please note that in addition to IJSBA rules and recommendations, all riders must obey local, state and federal boating regulations.

Advice from technical personnel, competitors and other experts has been of great assistance in the formulation of these rules. Additional help has been provided by the industry and others involved with the sport.

Have a safe and enjoyable year of IJSBA competition!

All material contained herein is copyright 2010, International Jet Sports Boating Association, Inc., 330 Purissima Street., Suite C Half Moon Bay, CA 94019, U.S.A. Phone: (714) 751 8695 - www.ijsba.com All rights reserved.



THAI JET SPORTS BOATING ASSOCIATION

Table of Contents

SECTION/ITEM

PAGE NO.

1.	IJSBA	.1
1.1	Mission Statement	. 1
1.2	International Headquarters	. 1
1.3	International Affiliates	. 1
1.4	Membership	. 2
1.5	How to Join	. 2
1.6	Membership Card	. 2
2.	COMPETITION PROGRAM	.3
2.1	IJSBA Control	. 3
2.2	Spirit of the Rules	. 3
2.3	Rules Compliance.	. 3
2.4	Safety	. 3
2.5	Application of the Rules	. 4
3.	EVENT SANCTIONS	.5
3.1	Race Sanctions	. 5
3.2	Special Event Sanctions	. 5
3.3	Application for Sanction	. 5
3.4	Sanction Procedures	. 5
3.5	General Sanction Regulations	. 5
4.	HOMOLOGATION	8
4.1	Homologation	. 8
5.	PERSONAL WATERCRAFT	12
5.1	Personal Watercraft	12
5.2	Ski Division	12
5.3	Sport Division	12
5.4	Runabout Division	13
5.5	Four-Stroke Runabout	13
6.	STOCK CLASS	15
6.1	Stock Class Competition	15
6.2	Stock Class – Hull	16
6.3	Stock Class – Engine – Two-Stroke	17
6.4	Stock Class – Engine – Four-Stroke	19
6.5	Stock Class – Air/Fuel Delivery – Two-Stroke	20
6.6	Stock Class – Air/Fuel Delivery – Four-Stroke	21
6.7		~ ~
~ ~	Stock Class – Ignition and Electronics – Two-Stroke	21
6.8	Stock Class – Ignition and Electronics – Two-Stroke Stock Class – Ignition and Electronics – Four-Stroke	21 21
6.8 6.9	Stock Class – Ignition and Electronics – Two-Stroke Stock Class – Ignition and Electronics – Four-Stroke Stock Class – Turbocharger/Supercharger	21 21 22

7.	LIMITED CLASS	23
7.1	Limited Class Competition	23
7.2	Limited Class – Hull	23
7.3	Limited Class – Engine – Two-Stroke	25
7.4	Limited Class – Air/Fuel Delivery – Two-Stroke	27
7.5	Limited Class – Air/Fuel Delivery – Four-Stroke	28
7.6	Limited Class – Ignition and Electronics – Two-Stroke	28
7.7	Limited Class – Driveline	28
7.8	Four Stroke Limited Specific	28
8.	OPEN CLASS	31
8.1	Open Class Competition	31
8.2	Open Class – Hull	32
8.3	Open Class – Engine – Two-Stroke	34
8.4	Open Class – Engine – Four-Stroke	35
8.5	Open Class – Air/Fuel Delivery – Two-Stroke	36
8.6	Open Class – Air/Fuel Delivery – Four-Stroke	37
8.7	Open Class - Ignition and Electronics - Two-Stroke/Four-Stroke	38
8.8	Open Class – Turbocharger/Supercharger	38
8.9	Open Class – Driveline	38
9		30
91	Modified Class Competition	39
92	Modified Class – Hull	
9.3	Modified Class – Engine – Two-Stroke	42
9.4	Modified Class – Air/Fuel Delivery – Two-Stroke	43
9.5	Modified Class - Ignition and Electronics - Two-Stroke	44
9.6	Modified Class – Driveline	44
10		45
10.1	Rider Classifications	45
10.1	Reginner	45
10.2	Novice	45
10.4	Expert	. 45
10.5	Amateur.	46
10.6	Pro	46
10.7	Pro-Am	46
10.8	Veterans	46
10.9	Masters	46
10.10	Women	46
10.11	Classification Changes	47
11.	FVENTS	48
11.1	Safety	48
11.2	Closed-Course Event	. 48
11.3	Slalom Event	48
11.4	Freestyle Event	48
11.5	Endurance Event	48
11.6	Drag-Racing Event	49
11.7	Special Event	49

12.	CLOSED COURSE EVENTS	50
12.1	General Pre-Start Procedures	50
12.2	General Starting Procedures	51
12.3	General Restart Procedures	51
12.4	General Regulations	. 52
13.	SLALOM EVENTS	54
13.1	General Regulations	. 54
14.	FREESTYLE EVENTS	55
14.1	General Freestyle Regulations	55
15.	ENDURANCE EVENTS	56
15.1	General Pre-Start Procedures	56
15.2	General Starting Procedures	56
15.3	General Restart Procedures	57
15.4	General Regulations	. 57
15.5	Fuel System, Fueling and Pit Stops	58
15.6	Special Equipment	. 59
15.7	Penalties	59
16.	SPECIAL EVENTS	60
16.1	Special Event Basics	60
17.	GENERAL COMPETITION RULES	61
17.1		
	General Competition Rules	61
17.2	General Competition Rules Rule Book Addenda	61 61
17.2 17.3	General Competition Rules Rule Book Addenda Technical Rules	61 61 61
17.2 17.3 17.4	General Competition Rules Rule Book Addenda Technical Rules Flag Rules	61 61 61 62
17.2 17.3 17.4 17.5	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations	61 61 61 62 63
17.2 17.3 17.4 17.5 17.6	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations	61 61 62 63 63
17.2 17.3 17.4 17.5 17.6 17.7	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules	61 61 62 63 63 64
17.2 17.3 17.4 17.5 17.6 17.7 17.8	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring	61 61 62 63 63 64 64 65
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards	61 61 62 63 63 64 64 65 65
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System	61 61 62 63 63 64 64 65 65 65
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System	61 61 62 63 64 64 65 65 65 65
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority	61 61 62 63 63 64 64 65 65 65 65 65 65
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12 18.	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority RULE INFRACTIONS	61 61 62 63 64 64 65 65 65 65 65 65
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12 18. 18.1	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority RULE INFRACTIONS Rules Infractions	61 61 62 63 64 64 65 65 65 65 65 65 65 65 65
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12 18. 18.1 18.2	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority RULE INFRACTIONS Rules Infractions Ejection from Race Site	61 61 62 63 64 64 65 65 65 65 65 65 65 65 65 65 65 65 69 69
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12 18. 18.1 18.2 18.3	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority RULE INFRACTIONS Rules Infractions Ejection from Race Site Discipline/Rider Conduct	61 61 62 63 64 65 65 65 65 67 68 69 69 69 69
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12 18. 18.1 18.2 18.3 18.4	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority RULE INFRACTIONS Rules Infractions Ejection from Race Site Discipline/Rider Conduct Rider/Pit Crew Liability	61 61 62 63 64 65 65 65 65 65 67 68 69 69 69 69 69
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12 18. 18.1 18.2 18.3 18.4 18.5	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority RULE INFRACTIONS Rules Infractions Ejection from Race Site Discipline/Rider Conduct Rider/Pit Crew Liability Rider Responsibility	61 61 62 63 64 65 65 65 65 65 67 69 69 69 69 69 69
17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 17.10 17.11 17.12 18. 18.1 18.2 18.3 18.4 18.5 18.6	General Competition Rules Rule Book Addenda Technical Rules Flag Rules General Regulations Pit Regulations Registration/Entry Rules Scoring Prizes and Awards Rider Point System Boat Numbering System Race Director Authority RULE INFRACTIONS Rules Infractions Ejection from Race Site Discipline/Rider Conduct Rider/Pit Crew Liability Rider Responsibility Penalties/Technical Infractions	61 61 62 63 64 65 65 65 65 65 67 68 69 69 69 69 69 70 70

19. 19.1 19.2 19.3 19.4	TECHNICAL PROCEDURES Pre-race Technical Inspection Post-race Technical Inspection Seals/Inspection Decals Fuel Tests	71 72 72 73
19.5	Sound Testing Procedure	73
20.	PROTESTS & APPEALS	74
20.1	Protests	74
20.2	Protest Procedure/Equipment Violations	74
20.3	Appeals	75
21.	GLOSSARY OF TERMS	76
22		70
22.	Port Chamfaring	70
	Pump Cover Plate	80
	Bond Flange	81
	Sponsons	82
	Rudder, Fin or Skeg	83
	Racing Number Location	84
	Starting Line Layout	85
	Slalom Course Layout	86
	Alternative Homologation	87
	Spec Classes Addendum	88
23	INTERNATIONAL AFFILIATES	94
23. 23.1	INTERNATIONAL AFFILIATES	94 95
23. 23.1 23.2	INTERNATIONAL AFFILIATES	94 95
23. 23.1 23.2 23.3	INTERNATIONAL AFFILIATES	94 95 95 95
23. 23.1 23.2 23.3 23.4	INTERNATIONAL AFFILIATES	94 95 95 95 95
23. 23.1 23.2 23.3 23.4 23.5	INTERNATIONAL AFFILIATES	94 95 95 95 95
 23.1 23.2 23.3 23.4 23.5 23.6 	INTERNATIONAL AFFILIATES	94 95 95 95 95 95
 23.1 23.2 23.3 23.4 23.5 23.6 23.7 	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95
 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 95 95
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 95 96 96
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 96 96
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 96 96 96
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 95 96 96 96 96
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 95 95 96 96 96 96
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 95 96 96 96 96 96 96 96
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15	INTERNATIONAL AFFILIATES	94 95 95 95 95 95 95 95 96 96 96 96 96 97 97
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Austria Bahamas Belgium Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark	94 95 95 95 95 95 95 95 96 96 96 96 96 97 97 97
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16 23.17 23.16	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Austria Bahamas Belgium Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark El Salvador	94 95 95 95 95 95 95 95 96 96 96 96 97 97 97 97
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16 23.17 23.18 23.17	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Australia Austria Bahamas Belgium Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark El Salvador England	94 95 95 95 95 95 95 95 96 96 96 96 96 97 97 97 97
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16 23.17 23.18 23.17 23.18 23.19	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Australia Austria Bahamas Belgium Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark El Salvador England Estonia	94 95 95 95 95 95 95 95 96 96 96 96 96 96 97 97 97 97 97
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16 23.17 23.18 23.19 23.20	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Australia Austria Bahamas Belgium Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark El Salvador England Estonia Finland Eranco	94 95 95 95 95 95 95 95 95 95 96 96 96 97 97 97 97 97 97 97
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16 23.17 23.18 23.19 23.20 23.20 23.21	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Australia Austria Bahamas Belgium Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark El Salvador England Estonia Finland France Carmany	94 9559595959595959595959596969696979797979
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16 23.17 23.18 23.19 23.20 23.21 23.20 23.22 23.23	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Australia Austria Bahamas Belgium Bermuda Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark El Salvador England Estonia Finland France Germany Greece	94 95 95 95 95 95 95 96 96 96 96 96 96 97 97 97 97 97 97 98 898
23. 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 23.13 23.14 23.15 23.16 23.17 23.18 23.19 23.20 23.21 23.20 23.21 23.22 23.23 23.24	INTERNATIONAL AFFILIATES Affiliate Directory Argentina Australia Australia Austria Bahamas Belgium Bermuda Bermuda Brazil Bulgaria Canada Canada Cayman Islands China Costa Rica Croatia Czech Republic Denmark El Salvador England Estonia Finland France Germany Greece Guam	94 95 95 95 95 95 95 96 96 96 96 97 97 97 97 97 98 88 98 98

23.25	Holland	98
23.26	Hong Kong	98
23.27	Hungary	99
23.28	Indonesia	99
23.29	Iran	99
23.30	Ireland	99
23.31	Israel	99
23.32	Italv	99
23.33	Japan	00
23.34	Korea 1	00
23.35	Kuwait 1	00
23.36	Malavsia 1	00
23.37	Mexico 1	00
23.38	Morocco 1	00
23.39	New Zealand	00
23.40	Nigeria 1	01
23 41	Norway	01
23.42	Oman 1	01
23.42	Paraguay 1	01
23.40	Peru 1	01
20.44		01
20.40	Polond 1	01
23.40	Polallu	02
23.47		02
23.40	Valar	02
23.49		02
23.50		02
23.51	South Africa	02
23.52	Spain	03
23.53		03
23.54		03
23.55	UAE	03
23.56	Uruguay 1	03
24.	UNITED STATES	J4
24.1	United States	04
25		דו
25.1	Compatition Classes	07
20.1	4 Stroko Eligibility Chart	01
20.1		00
26.	RELEASE AND WAIVER OF LIABILITY)9
26.1	Belease and Waiver of Liability	09
_0	. course and manor of Elaberty	

IJSBA

1.1 MISSION STATEMENT

The International Jet Sports Boating Association's mission is:

- to further the interest of IJSBA membership by providing a wide range of quality personal watercraft activities, services and benefits;
- to act as an international governing and sanctioning body for personal watercraft racing and to foster fair competition by formulating and promoting uniform rules and safety standards;
- to promote, organize and supervise personal watercraft events in a professional manner;
- to supervise and grant affiliation to international organizations with similar purposes and to cooperate with such organizations;
- to promote the positive image of personal watercraft by communicating with and educating IJSBA members and other users on the fun, safe and responsible usage of personal watercraft;
- to collect and disseminate information relating to the sport;
- to undertake activities aimed at advancing the sport; and
- to be an effective, unified voice for the sport.

1.2 INTERNATIONAL HEADQUARTERS

330 Purissima St. Ste. C Half Moon Bay, CA 94019 USA Please visit our website: www.ijsba.com

1.3 INTERNATIONAL AFFILIATES

- 1.3.1 The IJSBA, acting as the governing body for the personal watercraft sport worldwide, offers exclusive International Affiliate Memberships to qualified associations in specific countries or markets. The purpose of affiliation is to encourage the growth of personal watercraft activities; provide uniform regulations for competition events; promote the safe and responsible usage of personal watercraft; and further the interests of the IJSBA and its affiliates.
- 1.3.2 International IJSBA-affiliate associations may organize and promote National Championships in a manner most appropriate to local interest. International IJSBA-affiliate associations may create rules and racing classes that are not included in this rule book. All supplemental rules and racing classes must be approved by the IJSBA. It is the responsibility of the competitor to obtain this information. Contact the specific affiliate for supplemental rules and classes. A directory of international affiliates can be found in Section 23 (see pgs. 95-106).
- 1.3.3 Countries without IJSBA affiliates may request a list of requirements from IJSBA headquarters.

1.4 MEMBERSHIP

Eligibility for participation in an IJSBA- and IJSBA affiliate-sanctioned event requires the appropriate membership. The IJSBA and its international affiliates reserve the right to refuse membership to any group or individual.

1.5 HOW TO JOIN

- 1.5.1 Memberships may be purchased at sanctioned race events and activities, or from one of the IJSBA international affiliate offices.
- 1.5.2 If there is no IJSBA affiliate organization in your country, you may obtain membership information and application from any other affiliate organization. To receive a membership application form by mail, contact IJSBA international headquarters (see Section 1.2, pg. 1) or one of the international affiliates (see Section 23, pgs. 95-103).

1.6 MEMBERSHIP CARD

- 1.6.1 IJSBA or IJSBA affiliate membership cards must be available for officials' inspection when requested (e.g., at on-site event registration).
- 1.6.2 It is highly recommended that a competitor's medical history be carried with his/her membership card.



COMPETITION PROGRAM

2.1 IJSBA CONTROL

- 2.1.1 The IJSBA has established rules which govern the sanction, organization and conduct of sanctioned events; the standard for eligibility and conduct of competition and officials; the regulations for eligibility and preparation of watercraft; and the rules for annual series of events.
- 2.1.2 For rules specific to IJSBA international affiliate countries, contact the specific affiliate (see Sections 23, pgs. 95-103).

2.2 SPIRIT OF THE RULES

- 2.2.1 The official rules of the IJSBA included in this book are intended to provide fair and uniform regulations governing competition. These rules create competitive opportunities for riders in all classes.
- 2.2.2 It is not possible to write individual rules governing every possible circumstance. Therefore, the spirit of the rule shall grant the authority and responsibility for interpretation of the written rules to the Race Director whose duty it is to supervise and judge fair competition. It shall be the responsibility of the Race Director to interpret the unwritten rule in the interest of fair competition, and the Race Director's interpretation of the rule shall be binding on the individual and competition under the Race Director's jurisdiction.
- 2.2.3 From time to time, the IJSBA may, at its discretion, publish rule interpretations of written or unwritten rules which shall be binding upon all members of the association. Great care has been taken to publish rules addressing all possible issues of legal adjustment, changes, alteration, modifications and/ or replacement for racing.
- 2.2.4 Additional adjustments, changes, alterations, modifications and/or replacements not covered by written rules should not be assumed to be legal under the spirit of the rule.
- 2.2.5 Any member who is unable to locate a rule or has questions about a rule pertaining to a specific area of competition is advised to contact the IJSBA or local IJSBA international affiliate office for consultation and/or interpretation.

2.3 RULES COMPLIANCE

2.3.1 The rules and regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all IJSBA- and IJSBA affiliate-sanctioned events and activities. By participating in these events, all IJSBA or IJSBA affiliate members are deemed to have complied with the rules.

2.4 SAFETY

2.4.1 The rules for competition are intended only as a guide for the conduct of the sport pursuant to uniform rules. Rules directed or related to safety are promulgated to make all persons concerned with safety, but the IJSBA neither warrants safety if the rules are followed nor compliance with and enforcement

Competition Program

of rules. Moreover, each participant in competition has the responsibility to assess the safety aspects of facilities and conditions and must assume the risk of competition.

2.4.2 Participants are solely responsible for the condition of their vehicles and their competence to operate them.

2.5 APPLICATION OF THE RULES

These general rules will apply to all classes and competitors in all countries unless otherwise noted. All members and racing personnel—including owners, mechanics, pit crew, sponsors and promoters—are deemed to be fully aware of all rules and will be expected to adhere to and abide by them.





P.O. Box 518 · 654 Avenue K, Calimesa, CA 92320 Tech 909/795-2505 · Fax 909/795-6351 · Orders 800/969-7528 e-mail: sales@skat-trak.com · WWW.Skat-trak.com

EVENT SANCTIONS

3.1 RACE SANCTIONS

The International Jet Sports Boating Association (IJSBA) name, service mark and emblem may be associated only with activities and events which have been sanctioned or approved by the IJSBA or one of its international affiliates.

3.2 SPECIAL EVENT SANCTIONS

"Special events" are events which do not conform to those described in this rule book (see Sections 11-16, pgs. 48-60), but which otherwise meet established IJSBA standards. Prior approval from the IJSBA or an IJSBA international affiliate is required.

3.3 APPLICATION FOR SANCTION

- 3.3.1 An official race sanction can only be issued by the IJSBA or IJSBA affiliate office after proper applications are filed.
- 3.3.2 Application forms for sanction may be obtained from the local IJSBA affiliate office. (See Section 23, pgs. 95-103.)
- 3.3.3 Sanctions are non-transferable and non-assignable without permission of the IJSBA or IJSBA affiliate and must be used on the specified date or preapproved rescheduled date.
- 3.3.4 All sanctions must meet the proper legal requirements for compliance with any national, state, local, or province laws. This includes all necessary permits.
- 3.3.5 A sanction may be refused or withdrawn for any reason which the IJSBA and/or IJSBA affiliate deems to be in the best interests of the sport or for the safety of the racers, including the violation of any of the rules and regulations listed herein.
- 3.3.6 Written approval from the IJSBA must be obtained for any race to be cosanctioned.

3.4 SANCTION PROCEDURES

3.4.1 If you are planning an event or are requesting an IJSBA event date, you must advise the IJSBA or IJSBA affiliate office *in writing* at least 45 days in advance of the event.

3.5 GENERAL SANCTION REGULATIONS

- 3.5.1 All promoters applying for IJSBA sanction must comply with all IJSBA rules and regulations. The IJSBA may grant certain waivers to these general regulations, in the case of Continental and National Championships, Trophies or Cups.
- 3.5.2 The IJSBA shall be the sole international sporting authority entitled to make and enforce regulations for the encouragement and control of personal watercraft competitions and records, to organize and/or sanction IJSBA events and will be the final international court of appeal for the settlement of disputes.

Event Sanctions

- 3.5.3 In the event of doubt or ambiguity as to the meaning of rules and regulations for IJSBA-sanctioned events, the decisions of the IJSBA will prevail and be binding.
- 3.5.4 Each promoter, national club, association or affiliate belonging to the IJSBA will be presumed to understand and be bound by these rules and regulations.
- 3.5.5 Generally, only one single affiliate per country will be recognized by the IJSBA as the sole international sporting power for the enforcement of the rules and control of personal watercraft sport (exceptions may be granted where warranted by circumstances). Every person, or group of persons, organizing a competition or taking part in a competition will:
 - 1) Be acquainted with the rules and regulations of the IJSBA, official competition rulebook and the national regulations.
 - 2) Submit themselves without reserve to the above and to decisions of the sporting authority and to the consequences resulting therefrom. In case of non-compliance with these requirements and/ or rules, any person or group which organizes a competition or takes part therein, may have the license/sanction which has been issued to them withdrawn and/or fined, and any manufacturer/rider/ person may be excluded from the events on a temporary or permanent basis.
- 3.5.6 Any proposed event/competition (e.g., demonstrations, wakeboard events, skateboard event, Go-Ped event, etc.) not organized in conformity with the regulations or rules of the IJSBA will not obtain sanction. If such a competition is included in an event, without approval from the IJSBA, for which a sanction has been granted, the sanction will be null and void. The provisions of section 3.3.5 are applicable to any license-holder taking part in such competition.
- 3.5.7 The sanction of an event will be granted by the IJSBA based on the information supplied by the promoter and the quality of events previously promoted. The IJSBA must ensure that the promoter has the skill and experience to conduct events in a safe and professional manner. To be considered for sanctioning, a promoter must:
 - 1) Meet IJSBA equipment requirements such as buoys, starting gate, etc.
 - 2) Adhere to the IJSBA Competition Rulebook.
 - Meet IJSBA race operation practices as defined in the IJSBA Event Guide.
 - 4) Meet all the requirements for promoting an IJSBA sanctioned event.
 - 5) Be in good standing with the IJSBA.
- 3.5.8 Championship and invitational events will be assigned by the IJSBA. Championship classes will be decided by the IJSBA.
- 3.5.9 A promoter may not hold or advertise any event as a Championship or with any other title which may be deemed by the IJSBA to either World, National, International, or Invitational in character without written permission of the IJSBA. Titled "Charity Race" events must be approved by the IJSBA.

- 3.5.10 The "IJSBA-Sanctioned" logo must appear in all printed matter, including advertising of the event or series. Radio and television advertising must include the words "IJSBA-Sanctioned" or "Sanctioned by the IJSBA".
- 3.5.11 All event schedules must reach the IJSBA office before a specific date, which the IJSBA will state to the international affiliates and promoters each year, in order to be entered on the official IJSBA event calendar. The IJSBA may have additional requirements that must be met by a specified date. This does not imply that sanction is granted, but will give the promoter in good standing priority in case of a conflict in dates. Published event dates do not necessarily reflect the status of event sanction.

Sanction from the IJSBA provides the promoter in good standing exclusivity of location within a radius of 480 Kilometers (300 miles). The IJSBA may, for reasons of geographical and/or travel time nature, sanction an event within a shorter radius. The IJSBA may chose to substitute the radius with an exclusivity by state or by region (i.e. "Midwest").

Should a conflict arise between two events, the event with the longer history would have priority. However, the IJSBA reserves the right to reserve dates for national and world championship events.

The IJSBA may also refuse to grant sanction, and may withdraw or cancel a sanction that has already been granted for any reason which the IJSBA deems to be in the best interest of the sport, or the participating riders, including the violation of any of the IJSBA regulations or rules.



HOMOLOGATION

4.1 HOMOLOGATION

- 4.1.1 For a manufacturer to be eligible to submit a watercraft for IJSBA homologation, the manufacturer must be a current IJSBA Manufacturer Member in good standing. Manufacturers should contact the IJSBA international headquarters (see Section 1.2, pg. 1) for membership requirements.
- 4.1.2 For a watercraft to be eligible for current-year IJSBA- and IJSBA affiliatesanctioned competition events:
 - The manufacturer must produce a minimum of 500 identically manufactured units of a model and make those available for sale through the manufacturer's normal means of distribution.
 - 2) For a watercraft to be eligible for competition in Regional and National events in the United States, the manufacturer must produce a minimum of 500 identically manufactured units of a model and make those available for sale through the manufacturer's normal means of distribution in the United States of America.
 - To be eligible for the World Championships competition, new models must be homologated a minimum of 90 days prior to the first day of competition.
 - 4) Only upon formal approval from the IJSBA can a model be considered eligible for IJSBA-sanctioned competition.
 - 5) Each listing under "Eligible Watercraft" will be considered a separate model for purposes of this Rule Book.
 - 6) Only those models which have met the criteria for homologation at the date of publication are listed as "Eligible Watercraft." Watercraft that meet homologation after the Rule Book is published will be announced via official bulletins faxed or mailed to IJSBA affiliate offices; announced at an IJSBA- or IJSBA affiliate-sanctioned event; or any combination of the above. It is the responsibility of the competitor to obtain this information.
- 4.1.2.a For a Manufacturer to produce less than 500 identically manufactured units of a model and qualify for current-year IJSBA and- IJSBA affiliate sanctioned competition the manufacturer must adhere to the following criteria for all models produced in quantities below 500:
 - The manufacturer must produce a minimum of 100 identically manufactured units of a model. Should the manufacturer sell, or dispose of all 100 units before July 1st then the manufacturer must produce and additional 50 units, identical to the initial 100, and have those units available by September 2nd.
 - 2) The manufacturer shall declare, in the initial application for homologation, that the model will have production numbers less than 500.
 - 3) The manufacturer shall inform and update the IJSBA as to the status, location, and/or purchaser of each unit produced.
 - 4) The manufacturer must allow the IJSBA, upon request, to broker the sale of up to 25% of the total model units produced in order to ensure

distribution to IJSBA competition members.

- 5) The IJSBA may place restrictions on the model in stock class competitions.
- 6) In order to compete in Regional and National events in the United States, a total of 100 model units must be present and available in the United States, to customers, through the manufacturer's normal means of distribution.
- The manufacturer shall transport an IJSBA official to inspect the assembly line of the unit according to the terms listed in the homologation application.
- Failure to comply with all requirements in this section shall result in the immediate suspension of the unit in sanctioned competition.
- 4.1.3 The manufacturer must provide the IJSBA with a current service manual, parts catalog, owners manual and additional technical information for each model considered for homologation.
- 4.1.4 The manufacturer must provide the IJSBA, upon request, a production model watercraft and separate components for examination and testing for each model being considered for homologation. Items will be returned after completion of examination and testing.
- 4.1.5 Mid-year production changes to a homologated model must be approved by the IJSBA. Samples of new components, copies of related service bulletins and customer notification letters must be submitted before approval will be granted. Changes and updates on all affected units must be made available at no cost to the customer, parts and labor included.
- 4.1.6 IJSBA affiliates will generally accept IJSBA homologation of models. In cases where a specific model is not officially available through the manufacturer's normal means of distribution in a country or continent, exceptions may be granted.
- 4.1.7 The IJSBA reserves the right to refuse, withhold or withdraw the homologation of any component or watercraft for reasons deemed to be in the best interest of the sport.
- 4.1.8 The watercraft listed below have met U.S. homologation requirements and are eligible for competition. Each craft listed is eligible for competition within the specified division in classes of equal or greater engine displacement. No craft may be entered into a class of lesser designated engine displacement.

Example: A 580cc Sea-Doo may race in 800cc classes whereas a 701cc SuperJet may not race in 650cc classes.

Note: Updating and backdating parts may only be done within the same model (or IJSBA recognized replacement model).

Below, each model listed is considered as a separate model. Unless otherwise allowed, parts may not be updated or backdated to parts for other models. For example, a Superstock Kawasaki JS750SXi Pro may not back date to a 1995 JS750SXi cylinder, since the JS750SXi is listed as different model than a JS750SXi Pro.

4.1.2b For Homologation Methods not listed above, see Appendix.

Homologation

Ski Division

Kawasaki

JS300/300SX* JS440* JS550/550SX* JS650SX JS750SX JS750SXi JS750SXi Pro 800 SX-R

Polaris

Octane (776cc)

Yamaha

SuperJet (633cc) SuperJet (701cc) SuperJet (701cc) (1996 and newer) FX1 (701cc)

Hydrospace

S4 (749cc) S8 (1130cc- See Restrictions)

*Contact IJSBA for preparation rules.

Sport Division

Kawasaki X2 (633cc) X2 (800cc)

Polaris Hurricane (701cc)

Sea-Doo HX (720cc)

Yamaha WaveBlaster (701cc) WaveBlaster 800 (784cc) WaveJammer (500cc)

** All Sport Division PWC manufactured through 2009 are homologated for world wide use.

Runabout Division

Honda

Aquatrax F-12 (1235cc) Aquatrax F-12X (1235cc) Aquatrax R-12X (1235cc)

Kawasaki

Tandem Sport (633cc) 750 SS (743cc) 750 SS Xi (743cc) 750 SS Xi (743cc) 750 ST (743cc) 750 STS (743cc) 750 XiR (743cc) 750 ZXi (743cc) 900 STX (891cc) 900 STX (891cc, 1999 and newer) 900 ZXi (891cc) 1100 STX (1070cc) 1100 STX (1070cc) (2000 and newer) 1200 STX-R (1176cc) 1100 ZXi (1070cc) Ultra 130 DI (1070cc) Ultra 150 (1176cc)

STX-12F (1199cc) STX-15F (1498cc) Ultra 260 X (1498cc) Ultra LX (1498cc)

Polaris

Genesis (1164cc) Genesis I (1164cc) Pro 1200 (1164cc) SL 650/650 STD (647cc) SL 700 (701cc) SLT 700 (701cc) SL 750 (744cc) SLT 750 (744cc) SL 780 (779cc) SLT 780 (779cc) SLX 780 (779cc) SLX 785 Pro (779cc) SLXH (1050cc) SLX (1050cc/1165cc) SL 900 (900cc) SL 1050 (1051cc)

Homologation

Runabout Division (cont.)

SLTH (701cc) SLTX 1050/X-45 (1051cc/1165cc) Virage (701cc) Virage Freedom (701cc) Virage TX (1164cc) Virage TXi (1164cc) Polaris MSX 140**** (1192cc)

Sea-Doo

3-D (Only in "Vert" or "Moto" configuration) GS/GSi (720cc) GT/GTS (580cc) GTi (720cc) GTi (720cc) (1997 and newer) GTX (580cc) GTX (650cc) GTX (782cc) GTX RFI (782cc) GTX Limited (951cc) GTX DI (951cc) GSX (782cc) GSX (786cc) GSX RFI (782cc) GSX Limited (951cc) LRV (951cc)* LRV DI (951cc)* RX (951cc) RX DI (951cc) RXP RXP-X RXX (951cc) RXT RXT-X SP/SPi (580cc) SP (720cc) SPX (580cc) SPX (650cc) SPX (720cc) XP (580cc) XP (650cc) XP (720cc) XP800/XP/SPX (782cc) XP800/XP (786cc) XP/XP Limited (951cc) XP DI (951cc) GTX 4-TEC (1494cc) GTX 4-TEC Ltd Supercharged (1494cc)

Yamaha

VXR (633cc) Pro VXR (701cc) FX Cruiser High Output FX High Output WaveBlaster II (754cc) WaveRaider Deluxe (760cc) WaveRaider 700 (701cc) WaveRaider 760 (754cc) WaveRaider 1100 (1051cc) WaveRunner 500 (500cc) WaveRunner III (633cc) WaveRunner III GP (701cc) WaveRunner FZR (1812cc)*** WaveRunner FZS (1812cc)*** WaveRunner GP760 (754cc) WaveRunner GP800 (784cc) WaveRunner GP800R (784cc) WaveRunner GP1200 (1131cc) WaveRunner GP1200R (1176cc) WaveRunner GP1300R*** (1296cc) WaveRunner SUV (1131cc)* WaveRunner XL800 (784cc) WaveRunner XLT800 (784cc) WaveRunner XL1200 (1131cc) WaveRunner XL1200 Ltd. (1176cc) WaveRunner XLT1200 (1176cc) WaveRunner FX140 (998cc Four-Stroke) WaveVenture 700 (701cc) WaveVenture 1100 (1051cc)

*Eligible for Endurance competition only.

*** Engine displacement is limited to OEM displacement plus 1mm overbore.

****Sponsons must be modified or replaced with race-legal sponsons. Bow loop must be removed.

PERSONAL WATERCRAFT

5.1 PERSONAL WATERCRAFT

- 5.1.1 "Personal Watercraft (PWC) shall mean a vessel which uses an inboard engine powering a water-jet pump as its primary source of motive power. It is designed to be operated by a person sitting, standing or kneeling on the vessel rather than inside it. They are steered from the front directing a rear jet or fully enclosed prop drive system. They are defined as Class A inboard boats by the United States Coast Guard.
- 5.1.2 The four IJSBA racing divisions for PWC are Ski, Sport and Runabout
- 5.1.3 For two-stroke watercraft to be homologated for competition in the Ski divisions the watercraft must not exceed 785cc in stock configuration when furnished by the manufacturer. Unless stated by the class designation (ie Novice Ski 750 Limited), the maximum displacement of a two-stroke shall be 850cc in all Stock or Limited Classes. Normally aspirated four-stroke Ski PWC are limited to 1100cc as furnished by the manufacturer and the maximum displacement shall be the OEM displacement plus 1mm overbore on all cylinders. The maximum displacement that may be achieved by any two stroke Supercharged or Turbocharged Ski PWC is limited to 800cc maximum.
- 5.1.4 For two-stroke watercraft to be homologated for competition in the Runabout division, the watercraft must not exceed 1300cc in stock configuration when furnished by the manufacturer. Unless stated by the class designation (ie Novice Runabout 800 Limited), the maximum displacement of a two-stroke shall be 1200cc or OEM plus 1mm overbore on all cylinders (whichever is greater). Four-stroke Ski PWC are limited to 1600cc as furnished by the manufacturer. If a Runabout, as furnished by the manufacturer, exceeds 1600cc then the maximum displacement shall be the OEM displacement plus 1mm overbore on all cylinders. The maximum displacement that may be achieved by any Runabout PWC is 2000cc.

5.2 SKI DIVISION

- 5.2.1 The Ski Division includes PWC which are designed for one person to stand on and are controlled from a pivoting handlepole.
- 5.2.2 Watercraft competing in the Ski Division must conform to the following criteria:
 - 1) Dry weight must be greater than 102kg (225 lb.) for 550cc classes;
 - 2) Dry weight must be greater than 114kg (260 lb.) in all other classes;
 - 3) Hull length cannot exceed 304.8cm (120 in.);
 - 4) Hull width must be between 50.8cm (20 in.) and 76.2cm (30 in.).

5.3 SPORT DIVISION

- 5.3.1 The Sport Division includes PWC which are designed for one or more people and have a seat.
- 5.3.2 Watercraft competing in the Sport Division must conform to the following criteria:

- 1) Dry weight must be greater than 113kg (250 lb.) for 650cc classes;
- 2) Dry weight must be greater than 136kg (300 lb.) for 800cc classes;
- 3) Hull length cannot exceed 304.8cm (120 in.);
- 4) Hull width must be between 66.0cm (26 in.) and 96.5cm (38 in.).

5.4 RUNABOUT DIVISION

- 5.4.1 The Runabout Division includes PWC which are designed for one or more people and have a seat.
- 5.4.2 Watercraft competing in the Runabout Division must conform to the following criteria:
 - 1) Dry weight must be greater than 155kg (340 lb.) for 660cc classes;
 - 2) Dry weight must be greater than 182kg (400 lb.) for 800cc classes;
 - 3) Dry weight must be greater than 216kg (475 lb.) for 1300cc classes;
 - 4) Hull length cannot exceed 354cm (139 in.);
 - 5) Hull width must be between 96.5cm (38 in.) and 127.0cm (50 in.).

For Endurance and Offshore-type events only:

- 6) Hull length cannot exceed 394.0cm (156 in.);
- 7) Hull width must be greater than 96.5cm (38 in.

Note: The following minimum weight criteria applies to 800 & 1200cc watercraft homologated prior to September 1, 1998:

- 1) Dry weight must be greater than 168kg (370 lb.) for 800 cc classes;
- 2) Dry weight must be greater than 191kg (420 lb.) for 1300cc classes.

5.5 FOUR-STROKE RUNABOUT

- 5.5.1 The Four-Stroke Runabout includes PWC, which are designed for one or more people and have a seat. Four-stroke Runabout modification levels are broken down into three levels: Stock, Limited and Open.
- 5.5.2 For the purposes of this rule book, normally aspirated four-stroke watercraft only utilize atmospheric pressure for induction. Turbocharged and supercharged four-stroke engines utilize boosted induction systems that increase pressure in the intake tract for combustion.
- 5.5.3 In addition to four-stroke-specific class, four-stroke watercraft may be classified as compatible in two-stroke classes, provided the following:
 - Normally aspirated and turbocharged/supercharged Stock-class fourstroke watercraft may compete in Stock, Limited, Open and Modified two-stroke classes.
 - Normally aspirated Open-class four-stroke watercraft may compete in Limited, Open and Modified two-stroke classes.
 - 3) Four-strokes up to 1100cc may compete in 850cc two-stroke classes;
 - 4) Four-strokes up to 2000cc may compete in 1300cc two-stroke classes.

Personal Watercraft

 Ski division four-stroke watercraft up to 1100cc, which are normally aspirated, may compete in 800cc two- stroke classes. Ski division fourstoke watercraft which are supercharged or turbocharged may not exceed 800cc.

Note: See 25.1.4 on page 108 for Runabout Four-Stroke Eligibility Chart

- 5.5.4 Watercraft competing in Four-Stroke Runabout must conform to the following criteria:
 - 1) Dry weight must be greater than 250kg (550 lb.) for 1100cc classes;
 - Dry weight must be greater than 272kg (600 lb.) for classes exceeding 1100cc;
 - 3) Hull length cannot exceed 354cm (139 in.);
 - 4) Hull width must be between 96.5cm (38 in.) and 127.0cm (50 in.).

For Endurance/Offshore-type events only:

- 5) Hull length cannot exceed 394.0cm (156 in.);
- 6) Hull width must be greater than 96.5cm (38 in.).



or e-mail us at customerservice@jettribe.com

STOCK CLASS

6.1 STOCK CLASS COMPETITION

Intended to promote interest in stock personal watercraft competition and to enable individuals to become active competitors with relatively modest investment and maintenance costs. Watercraft competing in these classes must conform to the specifications which follow. Note: classes may be offered that have greater restrictions than these Stock Class Provisions. Such class offerings must be named to differentiate the applicable rules (ie Novice Ski Showroom Stock, etc.)

LITES ADDENDUM: LITES is a special designation applied to Stock Classes to implement a horsepower limit. Ski Lites are Stock Class Ski PWC with a maximum of 85 Horsepower as furnished by the manufacturer. Runabout Lites are Stock Class Runabout PWC with a maximum of 220 Horsepower as furnished by the manufacturer. The IJSBA will publish an official list of OEM Horsepower for all homologated models.

CLASS NAMING ADDENDUM: Different competition markets make have drastically different demographics of Personal Watercraft. Based on the needs of the market, the promoter may choose to rename classes to best describe the bulk of participation. For example, where Lites type Ski are more prevalent, a promoter may name the Lites Class as "Stock" while giving the non-Lites Stock class a name such as "Performance Stock," or "Four Stroke Stock."

6.1.1 All watercraft must remain strictly stock, except where rules allow or require substitutions or modifications. Changes or modifications not listed here are not permitted. The IJSBA may allow additional modifications to Stock Classified PWC which provide for replacement/ reinforcements to parts and components (i.e. intercooler end caps, brackets, fittings, etc.) that have known failure risks in race conditions. Such changes will only be allowed if the allow for no volume or performance gains. Such allowances are only legal if published by the IJSBA. Some original equipment components may not comply with IJSBA rules. Hull Identification Numbers must be displayed as furnished by the manufacturer.

NOTE: When rules permit or require equipment to be installed, replaced, altered or fabricated, it is the sole responsibility of the rider to select components, materials and/or fabricate the same so that the watercraft operates safely in competition.

- 6.1.2 Original equipment parts may be updated to newer original equipment parts of the same model. The part must be a bolt-on requiring no modifications to that part or any other parts except where rules allow substitutions or modifications. (Refer to Model Homologation listing on page 10.)
- 6.1.3 Sound level shall not exceed 86 dB(a) at 22.86m (75 ft.). See Section 19.5 (pg. 73).

Stock Class

6.1.4 Engine fuel must consist of gasoline meeting the criteria defined in Section 19.4.3 (pg. 73).

6.2 HULL

- 6.2.1 All watercraft must have a flexible tow loop attached to the bow. The tow loop should be made of a flexible material (e.g., nylon strap, rope, etc.) so as not to create a hazard. Tow hooks which protrude beyond the plane of the hull must be removed.
- 6.2.2 Hull and deck repairs may be made. However, these repairs must not alter the original configuration by more than 2.00mm (0.08 in.). Handles, drop-in type storage buckets, bolt-on type mirrors and gauges may be modified, aftermarket or removed provided a hazard is not created.
- 6.2.3 All watercraft may be equipped with a maximum of two sponsons. Original equipment sponsons may be modified, aftermarket, repositioned or removed. Overall length of each sponson shall not exceed 91.45cm (36.00 in.). Sponsons shall not protrude from the side of the hull by more than 100.00mm (3.94 in.) when measured in a level horizontal plane. The vertical channel created by the underside of the sponson shall not exceed 63.5mm (2.50in). No part of the sponson shall extend downward below the point at which the side of the hull intersects the bottom surface of the hull by more than 38.00mm (1.50 in.). Aftermarket or modified sponsons must exceed 6mm (0.24 in.) in thickness. All leading edges must be radiused so as not to create a hazard. Sponsons may not be attached to the planing surfaces of the hull. Fins, rudders, skegs and other appendages that may create a hazard will not be allowed. (See diagrams in Appendix.)

Ski Division Only: Sponsons may be attached to the inside of the bond flange, but no part of the sponson may extend more than 38mm (1.50 in.) below the lower part of the bond flange (bumper removed). Sponsons attached to the inside of the bond flange shall not protrude outside the bond flange (bumper removed) when measured in a level horizontal plane. *Ski PWC Homologated under 4.1.2 Only (500 Units):* If a model has not had the hull updated for greater than five years then all updated year models shall be allowed an additional set of sponsons for a total of four sponsons. All other provisions of 7.2.3 remain in tact.

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition.

- 6.2.4 Intake grate may be modified or aftermarket. Intake grate is required and must be the full-length type with at least one bar running parallel to the drive shaft. Grates may not extend more than 12.00mm (0.47 in.) below the flat plane of the pump intake area. All leading edges must be radiused so as not to create a hazard.
- 6.2.5 Pump cover plate may be modified or aftermarket. An extension may be added to the rear of the pump cover plate but shall not exceed the width of the original equipment plate. Modified and aftermarket plates must not extend more than 100.00mm (3.94 in.) beyond the end of the original equipment plate for *Ski* and *Sport Division* or 177.80mm (7.00 in.) for *Runabout Divisions. The* sides of the extension must be connected to the radiused portion of the pump plate so as not to create a hazard. Fins, rudders, skegs

and other appendages that may create a hazard will not be allowed. (See diagram in Appendix.)

- 6.2.6 Replacement trim plates may be used. Only replica parts that offer handling characteristics the same as stock are allowed. Material shall not be restricted to original equipment provided a hazard is not created (i.e., aluminum in place of plastic). See Glossary of Terms for definition of Replacement and Replica.
- 6.2.7 Replacement bumpers may be used provided a hazard is not created.
- 6.2.8 A soft, flexible water-spray deflector may be attached to the hull sides or to the bond flange provided a hazard is not created. No part of the deflector may extend beyond the perimeter of the original equipment bumper or side moldings as measured by a plumb line.
- 6.2.9 Handlebar, throttle, throttle cable, and grips may be modified or aftermarket. Handlebar cover may be modified or removed. Aftermarket switches and switch housings may be used. Steering shaft, steering shaft holder and handlebar holder may be aftermarket. The handlebar must be padded at the mounting bracket or, if it has a crossbar, the crossbar must be padded. Quick-turn steering modifications to alter steering ratio are allowed. Aftermarket steering cables will be allowed.
- 6.2.10 **Ski Division Only:** Handlepole (and mounting bracket) may be modified or aftermarket provided it functions as originally designed. Handlepole attaching point may be reinforced.
- 6.2.11 Sport and Runabout Division Only: Original equipment seat base must be used. Seat cover may be changed. Seat foam may be modified or aftermarket. The OEM seat height cannot be changed by more than +/-12.7mm (0.5 in).
- 6.2.12 Padding and/or mat kits may be added and custom painting is allowed. The surface finish of any metal component outside the hull area above the bond flange may be polished, shot peened or painted.
- 6.2.13 Original bilge pump may be modified or disconnected. Aftermarket bilge draining systems that do not create a hazard are allowed.
- 6.2.14 Engine compartment ventilation tubes may be modified, aftermarket, or removed. Inlet and outlet openings may not be enlarged (i.e., when the tube is removed, the opening may not be larger than stock). Vents may be shielded or plugged. No other modifications to the hood will be allowed.
- 6.2.15 Ballast weight may be added within the normally exposed areas of the hull to alter the handling of the watercraft provided a hazard is not created. Only weight consisting of constant mass (i.e., water or other fluid is not allowed) that does not require the modification or relocation of any parts will be allowed unless such modification or relocation is specified by other rules.

6.3 ENGINE — TWO-STROKE

6.3.1 Engines may be bored. Replacement piston assemblies may be used provided the original port timing, compression ratio, dome profile, skirt length and shape and type of material are not changed. Non-conforming pistons (ie skirt shape that is not an exact replica of the OEM piston) may be approved by the IJSBA but such approval must be obtained in writing. Replacement

Stock Class

piston assemblies must weigh within $\pm 25.00\%$ of original equipment. Engine displacement must not exceed class designation (e.g., 550cc in 550 Stock, 850cc in 850 Stock, etc.) unless otherwise noted. Chamfering of cylinder ports must not exceed 1.00mm (0.04 in.) at a 30 degree maximum angle. (See diagram in Appendix.).

- 6.3.2 Crankshaft may be rebuilt using replacement counterweights, crank pins, bearings and connecting rods. Counterweights, crank pins and connecting rods made of non-ferrous metals are not allowed. Stroke and rod length may not be changed. Counterweights on non-rebuildable style crankshafts may be machined to accept a press-through crank pin. Replacement bearings must maintain their original type and dimensions. Replacement counterweights must resemble the original part (i.e., holes and/or pockets not existing on the original part may not be on the replacement part). Total weight of the crankshaft assembly must be within ±5.00% of original equipment. Crankpins may be welded and/or keyed to the counterweights.
- 6.3.3 Repairs to cracked or punctured crankcases may be made provided only one damaged area affecting one cylinder bank has been repaired. No other modifications or repairs are allowed.
- 6.3.4 External modifications to the engine finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only.
- 6.3.5 No internal modifications of any kind, including grinding, surfacing, polishing, machining, shot peening, etc., will be allowed on any engine components.
- 6.3.6 Exhaust system must remain stock as supplied by the manufacturer. An insert may be added to reduce the inside diameter of the stinger portion of the exhaust system.
- 6.3.7 Cooling system may be modified or aftermarket subject to the limitations in this section: Aftermarket cooling lines and water bypass systems may be used. Additional cooling supply lines and fittings may be added to the pump. Fittings may not be added to the cylinder head, cylinder, or crankcase. Existing fittings to the cylinder head, cylinder, and crankcase may be aftermarket so long as they do not provide additional volume. Bypass fittings may be modified, aftermarket and/or relocated but must be directed downward and/ or rearward so as not to create a hazard for other riders. Any valves used within the entire cooling system must be of the fixed type or automatic (e.g., thermostats, pressure regulators, etc.). Electronically controlled water injections systems are not allowed unless originally equipped. Manually controlled devices (by any means of actuation) that alter the flow of cooling water during operation are not allowed. Cooling system flush kits are allowed.
- 6.3.8 Replacement starter motor and bendix may be used.
- 6.3.9 Replacement engine mounts may be used.
- 6.3.10 Oil-injection system may be disconnected or removed.
- 6.3.11 Replacement of general maintenance parts (e.g., gaskets, seals, spark plugs, spark plug wires, spark plug caps, wiring, water hoses, fuel lines, clamps and fasteners) shall not be restricted to original equipment providing the following:
 - 1) Replacement gaskets may be used but must be of the same type (e.g., sheet, o-ring, etc.) as their OEM counterparts. With the exception of

head gaskets and base gaskets, all replacement gaskets must maintain a thickness of plus or minus 20% of the OEM gasket thickness as furnished by the manufacturer. Base gasket cannot be thicker than 0.8mm (0.032in). Head gaskets must be no thinner than .005mm (0.002in) than the OEM thickness as supplied by the manufacturer. Head gaskets must be no thicker than 1.55mm (0.06in) than the OEM thickness as supplied by the manufacturer.

- **Ski Division Only:** Two Stroke engines that have a displacement of less 780cc shall be allowed a minimum head gasket thickness of .75mm (0.03 in) with a tolerance of -10% and a base gasket thickness of .5mm (0.02 in) with a tolerance of +/-10%.
- 2) Stripped threads must be repaired to the original size.
- Fasteners (e.g., bolts, nuts and washers) may not be substituted with titanium pieces unless originally equipped. Fasteners may integrate locking mechanisms.
- 6.3.12 Cylinders may be interchanged between homologated watercraft of the same manufacturer subject to restrictions announced by the IJSBA. Any modifications to the cylinder or crankcase must be approved, in writing, by the IJSBA. This provision is only applicable to Two Stroke Ski PWC Homologated provision 4.1.2.
- 6.3.13 (Two Stroke Ski PWC Homologated under 4.1.2 only) If the OEM cylinders or the cylinders allowed under 6.3.12 do not provide for a displacement within 10% of the maximum allowable displacement then an aftermarket cylinder sleeve may be utilized. The aftermarket sleeve must maintain the same port sizes and specifications as the original OEM cylinder sleeve.

6.4 ENGINE — FOUR-STROKE

- 6.4.1 Cylinder head combustion chambers may be cleaned by bead blasting with valves seated in place. Intake and exhaust ports may not be bead blasted or cleaned with abrasive material such as steel wool or Scotch-Brite®. Repairs to the cylinder head affecting one cylinder bank are allowed.
- 6.4.2 Crankshaft must remain stock. Replacement bearings or bearing shells are allowed, providing they maintain their original type and dimensions.
- 6.4.3 Camshaft(s) must remain stock. Replacement bearings or bearing shells are allowed, providing they maintain their original type and dimensions.
- 6.4.4 Intake and exhaust valves may be shimmed with OEM or aftermarket shims.
- 6.4.5 Cooling system may be modified or aftermarket. Aftermarket cooling lines and water bypass systems may be used. Additional cooling supply lines and fittings may be added to the pump. Fittings may not be added to the cylinder head, cylinder, or crankcase. Existing fittings to the cylinder head, cylinder, and crankcase may be aftermarket so long as they do not provide additional volume. Bypass fittings may be modified, aftermarket and/or relocated but must be directed downward and/or rearward so as not to create a hazard for other riders. Any valves used within the entire cooling system must be of the fixed type or automatic (e.g., thermostats, pressure regulators, etc.). Electronically controlled water injections systems are not allowed unless

Stock Class

originally equipped. Manually controlled devices (by any means of actuation) that alter the flow of cooling water during operation are not allowed. Additional fittings/enlarged fittings may be added to the intercooler so long as the intercooler volume is not changed. Cooling system flush kits are allowed.

- 6.4.6 Valve cover may be modified or replaced for cosmetic purposes and/or weight reduction only.
- 6.4.7 Replacement of general maintenance parts (e.g., gaskets, seals, spark plugs, spark plug wires, spark plug caps, wiring, water hoses, fuel lines, clamps and fasteners) shall not be restricted to original equipment providing the following:
 - Replacement gaskets may be used but must be of the same type (e.g., sheet, o-ring, etc.) as their OEM counterparts. With the exception of head gaskets and base gaskets, all replacement gaskets must maintain a thickness of plus or minus 20% of the OEM gasket thickness as furnished by the manufacturer. Base gasket cannot be thicker than 0.8mm (0.032in). Head gaskets must be no thinner than .005mm (0.002in) than the OEM thickness as supplied by the manufacturer. Head gaskets must be no thicker than 1.55mm (0.06in) than the OEM thickness as supplied by the manufacturer.
 - 2) Stripped threads must be repaired to the original size.
 - Fasteners (e.g., bolts, nuts and washers) may not be substituted with titanium pieces unless originally equipped. Fasteners may integrate locking mechanisms.
- 6.4.8 When Four-Stroke and Two-Stroke Ski PWC are combined in the same Stock Class then the IJSBA may require that those Four-Stroke Ski PWC which are not normally aspirated (Turbocharged or Supercharged) shall be affixed with an IJSBA approved boost regulator. The boost regulator shall be set to release any boost pressure above 110% of the stock specifications. The IJSBA shall publish the official interpretation of the stock specifications. The HSR-Benelli S4 boost pressure is limited to 7.7psi in Stock Class Competition.
- 6.4.9 (Runabout Only) A stop valve may be affixed to the intercooler supply line in order to prevent surges which might cause damage to the intercooler.

6.5 AIR/FUEL DELIVERY — TWO-STROKE

- 6.5.1 Aftermarket flame arresters that meet USCG, UL-1111 or SAE J-1928 Marine standards may be used. Carburetor jets (replaceable type), needle valves and needle valve springs may be changed. Choke may be removed provided additional air intake for the engine is not created. Aftermarket primer system may be installed. No other carburetor modifications will be allowed.
- 6.5.2 The entire fuel system is a closed system. The watercraft must not vent or spill fuel at any attitude with or without the engine running. Original equipment fuel tank, fuel pickup, fuel filler, fuel filter, fuel tap assembly and relief valve must be used and cannot be modified. Fuel petcock may be bypassed. Additional fuel filters may be used. Fuel tank filler cap may be modified or aftermarket provided a hazard is not created.

6.6 AIR/FUEL DELIVERY — FOUR-STROKE

- 6.6.1 Electronic fuel-injection systems: Flame arresters that meet USCG, UL-1111 or SAE J-1928 Marine backfire flame arrester test standards must be installed. If not equipped with an airflow sensor, the ducting between the flame arrestor and throttle body may be modified or aftermarket. If originally equipped with an airflow sensor, the ducting may be modified or aftermarket between the flame arrestor and airflow sensor. Modifications to the airflow downstream of the airflow sensor are not allowed. No modifications to the turbocharger and supercharger system, if applicable, are allowed.
- 6.6.2 Carbureted induction systems: Flame arrestors that meet USCG, UL-1111 or SAE J-1928 Marine backfire flame arrester test standards must be installed. Carburetor jets (replaceable type), needle valves and needle valve springs may be changed. Choke may be removed provided additional air intake for the engine is not created. Aftermarket primer system may be installed. No other carburetor modifications will be allowed.
- 6.6.3 Fuel injectors and fuel pump must remain stock. Fuel pressure regulator may be modified to change fuel pressure.
- 6.6.4 Aftermarket Valve Spring Retainers may be used so long as OEM valve springs are used.

6.7 IGNITION AND ELECTRONICS — TWO-STROKE

- 6.7.1 Replacement batteries are allowed but must fit into the original equipment battery box and be securely fastened.
- 6.7.2 The original electronic control unit may be modified or aftermarket so long as it does not offer any additional inputs or outputs than the original unit, and it must connect with the original connections. No additional sensors may be added (e.g., exhaust gas temperature, detonation sensors, etc.). Engine temperature sensors may be disabled.
- 6.7.3 Ignition timing may be altered by slotting ignition trigger mounting plate. An adapter plate may be used for the sole purpose of relocating the ignition trigger.
- 6.7.4 Aftermarket spark plugs with a different heat rating may be used.

6.8 IGNITION AND ELECTRONICS — FOUR-STROKE

- 6.8.1 Replacement batteries are allowed but must fit into the original equipment battery box and be securely fastened.
- 6.8.2 The original electronic control unit may be modified or aftermarket so long as it does not offer any additional inputs or outputs than the original unit, and it must connect with the original connections. No additional sensors may be added (e.g., exhaust gas temperature, detonation sensors, etc.). Engine temperature sensors may be disabled.
- 6.8.3 Ignition timing may be altered by slotting ignition trigger mounting plate. An adapter plate may be used for the sole purpose of relocating the ignition trigger.
- 6.8.4 Aftermarket spark plugs with a different heat rating may be used.

Stock Class

6.9 TURBOCHARGER/SUPERCHARGER

6.9.1 Modifications to any part of the turbocharger or supercharger system (i.e., housing, turbines, rotors, sensors, ducting, etc.) are not allowed.

6.10 DRIVELINE

- 6.10.1 Impeller may be modified or aftermarket, providing that the original diameter is maintained. Replacement wear rings that are within OEM internal diameter specifications may be used. Silicone adhesive sealant may be used in addition to original equipment seal to seal pump inlet. Visibility spout must be removed or plugged.
- 6.10.2 No internal modifications of any kind, including grinding, surfacing, polishing, machining, shot peening, etc., will be allowed on any driveline components (e.g., pump stator, reduction nozzle, etc.).


LIMITED CLASS

7.1 LIMITED CLASS COMPETITION

Intended to promote interest in personal watercraft competition with a limited number of modifications, and to enable individuals to become active competitors with a relatively modest investment. Watercraft competing in this class must conform to the specifications which follow.

7.1.1 All watercraft must remain strictly stock (all Stock Class provisions are allowed in Limited Class unless otherwise noted), except where rules allow or require substitutions or modifications. Changes or modifications not listed here are not permitted. The IJSBA may allow additional modifications to Stock Classified PWC which provide for replacement/reinforcements to parts and components (i.e. intercooler end caps, brackets, fittings, etc.) that have known failure risks in race conditions. Such changes will only be allowed if the allow for no volume or performance gains. Such allowances are only legal if published by the IJSBA. Some original equipment components may not comply with IJSBA rules. Hull Identification Numbers must be displayed as furnished by the manufacturer.

NOTE: When rules permit or require equipment to be installed, replaced, altered or fabricated, it is the sole responsibility of the rider to select components, materials and/or fabricate the same so that the watercraft operates safely in competition.

7.1.2 Original equipment parts may be updated or backdated with original equipment parts of the same model. The part must be a bolt-on requiring no modifications to that part or any other parts except where rules allow substitutions or modifications. (Refer to Model Homologation listing on page 10-11.)

Note: Pre-1996 Yamaha SuperJet may update to 1996 and newer engine components and waterbox. Kawasaki JS750SX and SXi may update to SXi Pro engine components and waterbox.

- 7.1.3 Sound level shall not exceed 86 dB(a) at 22.86m (75 ft.). See Section 19.5 (pg. 73).
- 7.1.4 Engine fuel must consist of gasoline meeting the criteria defined in Section 19.4.3 (pg. 73).

7.2 HULL

- 7.2.1 All watercraft must have a flexible tow loop attached to the bow. The tow loop should be made of a flexible material (e.g., nylon strap, rope, etc.) so as not to create a hazard. Tow hooks which protrude beyond the plane of the hull must be removed.
- 7.2.2 Hull and deck repairs may be made. However, these repairs must not alter the standard configuration by more than 2.00mm (0.08 in.). Hull, bulkhead and deck may be internally reinforced. Fasteners may be installed through the hull, bulkhead and deck for the purposes of securing components to interior surfaces, provided a hazard is not created. Other than for the use of fasteners, the bulkhead may not be modified.

Limited Class

7.2.3 All watercraft may be equipped with a maximum of two sponsons. Original equipment sponsons may be modified, aftermarket, repositioned or removed. Overall length of each sponson shall not exceed 91.45cm (36.00 in.). Sponsons shall not protrude from the side of the hull by more than 100.00mm (3.94 in.) when measured in a level horizontal plane. The vertical channel created by the underside of the sponson shall not exceed 63.5mm (2.50 in.). No part of the sponson shall extend downward below the point at which the side of the hull intersects the bottom surface of the hull by more than 63.5mm (2.50 in.). Aftermarket or modified sponsons must exceed 6mm (0.24 in.) in thickness. All leading edges must be radiused so as not to create a hazard. Sponsons may not be attached to the planing surfaces of the hull. Fins, rudders, skegs and other appendages that may create a hazard will not be allowed. (See diagrams in Appendix.)

Ski Division Only: Sponsons may be attached to the inside of the bond flange, but no part of the sponson may extend more than 38.00\80mm (1.50 in.) below the lower part of the bond flange (bumper removed). Sponsons attached to the inside of the bond flange shall not protrude outside the bond flange (bumper removed) when measured in a level horizontal plane.

Ski PWC Homologated under 4.1.2 Only (500 Units): If a model has not had the hull updated for greater than five years then all updated year models shall be allowed an additional set of sponsons for a total of four sponsons. All other provisions of 7.2.3 remain in tact.

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition.

- 7.2.4 Intake grate may be modified or aftermarket. Intake grate is required and must be the full-length type with at least one bar running parallel to the drive shaft. Grates may not extend more than 12.00mm (0.47 in.) below the flat plane of the pump intake area of the hull. All leading edges must be radiused so as not to create a hazard.
- 7.2.5 Pump cover plate may be modified or aftermarket. An extension may be added to the rear of the plate but shall not exceed the width of the original equipment plate. Modified and aftermarket plates must not extend more than 100.0mm (3.94 in.) beyond the end of the original equipment plate for *Ski* and *Sport Division* or 177.80mm (7.00 in.) for *Runabout Divisions*. The extension must be connected to the radiused portion of the pump plate so as not to create a hazard. (See diagram in Appendix.) Fins, rudders, skegs and other appendages that may create a hazard will not be allowed.
- 7.2.6 Aftermarket fixed-position trim tabs may be used. Original equipment trim plates that are detachable from the hull may be removed or replaced when installing aftermarket trim tabs. Trim tabs cannot exceed the width of the planing surface or extend rearward more than 100.00mm (3.94 in.) beyond the end of the original planing surface. Manual or automatic trim tabs attached to the hull or ride plate are not allowed. All hull extensions mounted on the hull's transom will be considered as a trim tab. All edges must be radiused so as not to create a hazard. Fins, skegs, rudders and other appendages that may create a hazard are not allowed.
- 7.2.7 Replacement bumpers may be used provided a hazard is not created.

- 7.2.8 A soft, flexible water-spray deflector may be attached to the hull sides or to the bond flange provided a hazard is not created. No part of the deflector may extend beyond the perimeter of the original equipment bumper or side moldings as measured by a plumb line.
- 7.2.9 Handlebar, throttle, throttle cable, and grips may be modified or aftermarket. Handlebar cover may be modified or removed. Aftermarket switches and switch housings may be used. Steering shaft, steering shaft holder and handlebar holder may be aftermarket. The handlebar must be padded at the mounting bracket or, if it has a crossbar, the crossbar must be padded. Aftermarket steering cables will be allowed.
- 7.2.10 **Ski Division Only:** Handlepole (and mounting bracket) may be modified or aftermarket provided it functions as originally designed. Handlepole attaching point may be reinforced.
- 7.2.11 **Sport and Runabout Division Only:** Seat assembly may be aftermarket. Seat height may be changed.
- 7.2.12 Padding and/or mat kits may be added and custom painting is allowed. The surface finish of any metal component outside the area above the hull bond flange may be polished, shot peened or painted.
- 7.2.13 Original bilge pump may be modified or disconnected. Aftermarket bilge draining systems that do not create a hazard are allowed.
- 7.2.14 Engine compartment foam may be removed, modified or aftermarket. Only floatation foam within the engine compartment may be removed. Only foam that can be removed without modification to any other part or parts, except where rules allow the parts to be modified, is allowed. Parts may not be relocated based on the removal of the foam. The hull's inner liner or deck may not be cut or modified to remove foam. Removal of foam between layers of the hull and/or deck is not allowed.
- 7.2.15 Engine compartment ventilation tubes may be modified, aftermarket, relocated on the original equipment ducting, or removed. Inlet and outlet openings may not be enlarged (i.e., when the tube is removed, the opening may not be larger than stock). Vents may be shielded or plugged. No other modifications to the hood will be allowed.

Ski Division Only: Minor internal modifications to the hood, in order to fit an aftermarket exhaust pipe, will be allowed. No other modification will be allowed (i.e., no additional ventilation, etc.). Modifications will be subject to Race/Tech Directors' approval.

- 7.2.16 Handles, drop-in type storage buckets, bolt-on type mirrors and gauges may be modified, aftermarket or removed provided a hazard is not created.
- 7.2.17 Ballast weight may be added within the normally exposed areas of the hull to alter the handling of the watercraft provided a hazard is not created. Only weight consisting of constant mass (i.e., water or other fluid is not allowed) that does not require the modification or relocation of any parts will be allowed unless such modification or relocation is specified by other rules.

7.3 ENGINE – TWO-STROKE

7.3.1 Engines may be bored. Replacement piston assemblies may be used provided the original port timing, compression ratio, dome profile, skirt length

Limited Class

and shape and type of material are not changed. Replacement piston assemblies must weigh within $\pm 25.00\%$ of original equipment. Engine displacement must not exceed class designation (e.g., 550cc in 550 Limited, 800cc in 800 Limited, etc.). Chamfering of cylinder ports must not exceed 1.00mm (0.04 in.) at a 30 degree maximum angle. (See diagram in Appendix.) Cylinders may be machined to accept girdle system cylinder heads.

- 7.3.2 Crankshaft may be rebuilt using replacement counterweights, crank pins, bearings and connecting rods. Counterweights, crank pins and connecting rods made of non-ferrous metals are not allowed. Stroke and rod length may not be changed. Counterweights on non-rebuildable style crankshafts may be machined to accept a press-through crank pin. Replacement bearings must maintain their original type and dimensions. Replacement counterweights must resemble the original part (i.e., holes and/or pockets not existing on the original part may not be on the replacement part). Total weight of the crank-shaft assembly must be within ±5.00% of original equipment. Crankpins may be welded and/or keyed to the counterweights.
- 7.3.3 Repairs to cracked or punctured crankcases may be made provided only one damaged area affecting one cylinder bank has been repaired. Crankcase drain and cable may be removed and plugged. No other modifications or repairs are allowed.
- 7.3.4 External modifications to the engine finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only.
- 7.3.5 No internal modifications of any kind, including grinding, surfacing, polishing, machining, shot peening, etc., will be allowed on any engine components.
- 7.3.6 Cylinder head and gasket may be modified or aftermarket.
- 7.3.7 Exhaust manifold, head pipe, expansion chamber, gaskets and hose between expansion chamber and OEM waterbox may be modified/altered or aftermarket. Exhaust location of the exhaust gases may not be relocated. Original size opening must be maintained for exhaust exit. Original equipment waterbox must be used and may not be modified. No tuned portion of the exhaust shall protrude outside the hull. Through-hull exhaust outlet flap may be removed.

Runabout Limited classes: Removal of the plastic resonator is allowed.

- 7.3.8 Cooling system may be modified or aftermarket. Aftermarket cooling lines and water bypass systems may be used. Additional cooling supply lines and fittings may be added to the pump. Bypass fittings may be modified, aftermarket and/or relocated but must be directed downward and/or rearward so as not to create a hazard for other riders. Any valves used within the entire cooling system must be of the fixed type or automatic (e.g., thermostats, pressure regulators, solenoids, etc.). Manually controlled devices (by any means of actuation) that alter the flow of cooling water during operation are not allowed. Cooling system flush kits are allowed.
- 7.3.9 Replacement starter motor and bendix may be used.
- 7.3.10 Replacement engine mounts may be used.
- 7.3.11 Oil-injection system may be disconnected or removed.
- 7.3.12 Replacement of general maintenance parts (e.g., gaskets, seals, spark plugs,

spark plug wires, spark plug caps, wiring, water hoses, fuel lines, clamps and fasteners) shall not be restricted to original equipment providing the following:

- Replacement gaskets may be used but must be of the same type (e.g., sheet, o-ring, etc.) as their OEM counterparts. Base gasket cannot be thicker than 1.52mm (0.060in).
- 2) Stripped threads must be repaired to the original size.
- Fasteners (e.g., bolts, nuts and washers) may not be substituted with titanium pieces unless originally equipped. Fasteners may integrate locking mechanisms.
- 7.3.13 Cylinders may be interchanged between homologated watercraft of the same manufacturer subject to restrictions announced by the IJSBA. Any modifications to the cylinder or crankcase must be approved, in writing, by the IJSBA.
- 7.3.14 (Two Stroke Ski PWC Homologated under 4.1.2 only) If the OEM cylinders or the cylinders allowed under 6.3.12 do not provide for a displacement within 10% of the maximum allowable displacement then an aftermarket cylinder sleeve may be utilized. The aftermarket sleeve must maintain the same port sizes and specifications as the original OEM cylinder sleeve.

7.4 AIR/FUEL DELIVERY — TWO-STROKE

- 7.4.1 Carburetor(s) may be modified or aftermarket provided they do not vent or spill fuel at any attitude with or without the engine running. The number of venturis cannot exceed the number of cylinders. No slide-type carburetors. Aftermarket primer may be used. Intake manifold assembly may be modified or aftermarket. Aftermarket crankcase-pressure-operated fuel pumps may be used. Additional carburetor pulse line fittings may be installed on the crankcase.
- 7.4.2 Modified or aftermarket vapor/air separators must not exceed 2 in. x 6 in., and must have a return line to the fuel tank open at all times. Additional fuel reservoirs may not be used. Aftermarket or modified electric fuel pumps, not exceeding 4 psi, may be used. When the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off-type fuel pumps are allowed.
- 7.4.3 Aftermarket fuel-injection systems and components are allowed provided the following regulations are adhered to: High-pressure fuel hose meeting SAE J30R9 must be used; A.N. threaded-type fittings or equivalent and non-removable, crimped- type clamps must be used on the high-pressure portion of the system (i.e., hose clamps, tie wraps, etc. are not allowed); only metal-type fuel filters may be used on the high-pressure portion of the system; all other in-line filters must be installed on the low-pressure portion of the system. When the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off-type fuel pumps are allowed.
- 7.4.4 The entire fuel system is a closed system. The watercraft must not vent or spill fuel at any attitude with or without the engine running. Original equipment fuel tank, fuel filler and relief valve must be used and cannot be modified. The fuel pickup, fuel filter and fuel petcock assembly may be removed and/ or after-market parts may be used. Additional fuel filters may be used and

Limited Class

fuel cell foam may be added to the original equipment fuel tank. Fuel tank filler cap may be modified or aftermarket provided a hazard is not created.

- 7.4.5 Flame arrester(s) which satisfy United States Coast Guard, SAE-J1928 Marine or UL-1111 Marine backfire flame arrester test standards must be installed. Aftermarket flame arresters satisfying one of these test standards will be allowed. Intake silencer may be removed.
- 7.4.6 Reed valve assemblies may be modified or aftermarket. Rotary valve may be modified or aftermarket.

7.5 AIR/FUEL DELIVERY — FOUR-STROKE

7.5.1 A fuel pressure regulator may me added or modified for safety purposes.

7.6 IGNITION AND ELECTRONICS — TWO-STROKE

- 7.6.1 RPM limiter function may be bypassed or eliminated. CDI unit may be modified or aftermarket. Ignition timing may be changed. Modifications to the original equipment ignition pickup mount will be allowed. Original equipment charging system must be used. No other ignition system modifications will be allowed.
- 7.6.2 Flywheel cover may be modified to accept a crankshaft-end bearing support.
- 7.6.3 Replacement batteries are allowed but must fit into the original equipment battery box and be securely fastened.
- 7.6.4 Engine temperature sensor may be disconnected and/or removed.
- 7.6.5 Relocation of electrical components (e.g., battery, box or housing) is allowed in order to fit an aftermarket exhaust system (only the strict minimum needed). Modification will be subject to Race/Tech Directors' approval.

7.7 DRIVELINE

7.7.1 Impeller housing, stator vane assembly, pump mounting plate and/or pump shoe may be modified or aftermarket. No titanium driveshaft, impeller housing or stator vane assemblies. Impeller may be modified or aftermarket. Pump nozzle and directional nozzle may be modified or aftermarket. Overall length of the complete pump and nozzle assembly may be no more than 50.00mm (1.97 in.) longer than original equipment. Aftermarket nozzle-trim systems may be used. Additional cooling fittings may be installed. Visibility spout must be removed or plugged. Silicone adhesive sealant may be used in addition to original equipment seal to seal pump inlet. Couplers, bearing housing and driveshaft may be modified or aftermarket provided they maintain a 1:1 drive ratio between the engine and the pump.

7.8 FOUR-STROKE LIMITED SPECIFIC

7.8.1 Supercharged and Turbocharged Ski Division PWC must adhere to Stock Class Rules in all Limited Classes where Two Stroke and Four Stroke PWC are combined (except for the single provision of 7.8.4.1). The regulated boost pressure (see Rule 6.4.8) shall be set to release any boost pressure above 200% of the stock specifications. The IJSBA shall publish the official interpretation of the stock specifications. The HSR-Benelli S4 boost pressure is limited to a scale of 10-14 psi in Limited Class Competition. Unless specifically posted, the default boost pressure for HSR-Benelli S4 units shall be 14 psi.

7.8.2 ENGINE — FOUR-STROKE (RUNABOUTS ONLY)

- 7.8.2.1 Engines may be bored. Replacement piston assemblies may be used provided the original port timing, compression ratio, dome profile, skirt length and shape and type of material are not changed. Replacement piston assemblies must weigh within ±25.00% of original equipment. Engine displacement must not exceed class.
- 7.8.2.2 Crankshaft may be rebuilt/replaced provided by the following: Counterweights and material type must maintain the shape and dimensions as provided by the manufacturer. Stroke and rod lengths may not be changed. Counterweights may be deburred to remove only casting flaws, no other machining or knife edging of counterweights are allowed. Rod journals must maintain their OEM diameters/dimensions, Main journals must maintain there OEM diameters/dimensions. Cross drilling of crankshaft to improve oil flow or redirection is allowed. Replacement bearing shells are allowed provided the following: (max. allowable undersized bearing is .060 or 1.5mm). Total weight of the crankshaft assembly must be within +/- 5.00% of original equipment. Damaged rod or main journals may be welded and machined to their OEM dimensions or within the allowable bearing sizes.
- 7.8.2.3 Repairs to cracked or punctured crankcases may be made provided only one damaged area affecting one cylinder bank has been repaired. Crankcase drain and cable may be removed and plugged. No other modifications or repairs are allowed.
- 7.8.2.4 External modifications to the engine finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only.
- 7.8.2.5 No internal modifications of any kind, including grinding, surfacing, polishing, machining, shot peening, etc., will be allowed on any engine components.
- 7.8.2.6 Aftermarket cooling lines and water bypass systems may be used. Additional cooling supply lines and fittings may be added to the pump. Bypass fittings may be modified, aftermarket and/or relocated but must be directed downward and/or rearward so as not to create a hazard for other riders. Any valves used within the entire cooling system must be of the fixed type or automatic (e.g., thermostats, pressure regulators, solenoids, etc.). Manually controlled devices (by any means of actuation) that alter the flow of cooling water during operation are not allowed. Cooling system flush kits are allowed.
- 7.8.2.7 Replacement starter motor and bendix may be used.
- 7.8.2.8 Replacement engine mounts may be used.
- 7.8.2.9 Replacement of general maintenance parts (e.g., gaskets, seals, spark plugs, spark plug wires, spark plug caps, wiring, water hoses, fuel lines, clamps and fasteners) shall not be restricted to original equipment providing the following:
 - 1) Replacement gaskets may be used but must be of the same type (e.g., sheet, o-ring, etc.) and thickness as their OEM counterparts
 - Fasteners (e.g., bolts, nuts and washers) may not be substituted with titanium pieces unless originally equipped. Fasteners may integrate locking mechanisms.
- 7.8.2.10 Camshafts may be modified or aftermarket.

Limited Class

- 7.8.2.11 Valves may be modified or aftermarket. Valve seats may be modified. Springs may be modified or aftermarket. Pushrods may be modified or aftermarket. Replacement valves, pushrods, and seats may not be titanium unless originally equipped.
- 7.8.2.12 Aftermarket valve spring retainers may be used.

7.8.3 AIR/FUEL DELIVERY — FOUR-STROKE (RUNABOUTS ONLY)

- 7.8.3.1 Turbocharger impeller or supercharger impeller may be modified or aftermarket. The impeller housing must remain stock as supplied by the manufacturer. Intercoolers may be modified or aftermarket.
- 7.8.3.2 The entire fuel system is a closed system. The watercraft must not vent or spill fuel at any attitude with or without the engine running. Original equipment fuel tank, fuel filler and relief valve must be used and cannot be modified. The fuel pickup, fuel filter and fuel petcock assembly may be removed and/ or aftermarket parts may be used. Additional fuel filters may be used and fuel cell foam may be added to the original equipment fuel tank. Fuel tank filler cap may be modified or aftermarket provided a hazard is not created.
- 7.8.3.4 A fuel pressure regulator may be added and/or modified for safety purposes.
- 7.8.3.5 Throttle bodies must remain stock as supplied by the manufacturer. No changing of throttle plate angles and/or modifications to the throttle body housing. No phenolic or aluminum spacers are allowed behind the throttle body.

7.8.4 AIR/FUEL DELIVERY — FOUR-STROKE (SKI ONLY)

7.8.4.1 Intercoolers may be modified or aftermarket. Intercooler heat exchange surface area may not be increased by more than 25%. However, if any Limited Class Ski is equipped with a modified or aftermarket intercooler then that PWC shall have the boost regulator set to release any boost pressure above 110% of the stock specifications. The IJSBA shall publish the official interpretation of the stock specifications. The HSR-Benelli S4 boost pressure is limited to a scale of 10-14 psi in Limited Class Competition. Unless specifically posted, the default boost pressure for HSR-Benelli S4 units shall be 14 psi.

7.8.5 DRIVELINE — FOUR-STROKE (RUNABOUT ONLY)

7.8.5.1 Impeller housing, stator vane assembly, pump mounting plate and/or pump shoe may be modified or aftermarket. No titanium driveshaft, impeller housing or stator vane assemblies. Impeller may be modified or aftermarket. Pump nozzle and directional nozzle may be modified or aftermarket. Overall length of the complete pump and nozzle assembly may be no more than 50.00mm (1.97 in.) longer than original equipment. Aftermarket nozzle-trim systems may be used. Additional cooling fittings may be installed. Visibility spout must be removed or plugged. Silicone adhesive sealant may be used in addition to original equipment seal to seal pump inlet. Couplers, bearing housing and driveshaft may be modified or aftermarket provided they maintain a 1:1 drive ratio between the engine and the pump.

OPEN CLASS

8.1 OPEN CLASS COMPETITION

Intended to promote interest in personal watercraft competition with a higher degree of modification. Watercraft competing in this class must conform to the specifications which follow.

SUPERSTOCK ADDENDUM: If a class is designated as Superstock then Open Class rules shall apply with the exception of 8.2.2 (aftermarket hulls) and 8.3.5.a (aftermarket cylinders).

DISPLACEMENT ADDENDUM: All Normally Aspirated Four Stroke Ski PWC shall be allowed a maximum displacement of 1100cc or OEM displacement plus 1mm overbore on all cylinders (whichever is greater). All Normally Aspirated Two Stroke Ski PWC shall be allowed a maximum displacement of 1200cc. Any Ski PWC which is supercharged or turbocharged shall be limited to a maximum displacement of 800cc or OEM displacement plus 1mm overbore on all cylinders (whichever is greater).

8.1.1 All watercraft must remain strictly stock, except where rules allow or require substitutions or modifications. Changes or modifications not listed here are not permitted. Some original equipment components may not comply with IJSBA rules. Hull Identification Numbers must be displayed as furnished by the manufacturer.

NOTE: When rules permit or require equipment to be installed, replaced, altered or fabricated, it is the sole responsibility of the rider to select components, materials and/or fabricate the same so that the watercraft operates safely in competition.

8.1.2 Original equipment parts may be updated or backdated to original equipment parts of the same model. The part must be a bolt-on requiring no modifications to that part or any other parts except where rules allow substitutions or modifications. (Refer to Model Homologation listing on page 10-11.)

Note: Pre-1996 Yamaha SuperJet may update to 1996 and newer engine components. Kawasaki JS750SX and SXi may update to SXi Pro engine components.

- 8.1.3 Sound level shall not exceed 100 dB (a) at 22.86m (75 ft.). See Section 19.5 (pg. 73). A sound level of 86 dB may be enforced so long as the promoter notifies participants at least 14 days prior to the event.
- 8.1.4 Engine fuel must consist of gasoline meeting the criteria defined in Section 19.4.3 (pg. 73).
- 8.1.5 At all times, the watercraft must weigh no less than 10 percent under the watercraft's original dry weight as determined by the IJSBA, providing the following:
 - Includes fuel and oil.
 - Includes the water in the waterbox, so long as the waterbox is not deemed to be out of ordinary in volume.
 - Includes the battery.
 - All reasonable amount of water must be removed from all compartments.

Open Class

Ballast weight may be added prior to competition to meet the required weight limit (see 8.2.16).

8.2 HULL

- 8.2.1 All watercraft must have a flexible tow loop attached to the bow. The tow loop should be made of a flexible material (e.g., nylon strap, rope, etc.) so as not to create a hazard. Tow hooks, which protrude beyond the plane of the hull, must be removed.
- 8.2.2 Aftermarket hulls may be used, on watercraft homologated in numbers of 500 or higher, in classes which carry Expert and Pro designations. Top decks must be the original OEM top deck as supplied by the manufacturer. Hull and deck repairs may be made. However, these repairs must not alter the standard configuration of the top deck by more than 2.00mm (0.08 in.). Hull, bulkhead and deck may be internally reinforced. Fasteners may be installed through the hull, bulkhead and deck for the purposes of securing components to interior surfaces, provided a hazard is not created. Other than for the use of fasteners, the bulkhead may not be modified. Glue squeeze-out may be removed from the hull.
- 8.2.3 All watercraft may be equipped with a maximum of two sponsons. Original equipment sponsons may be modified, aftermarket, repositioned or removed. Overall length of each sponson shall not exceed 91.45cm (36.00 in.). Sponsons shall not protrude from the side of the hull by more than 100.00mm (3.94 in.) when measured in a level horizontal plane. The vertical channel created by the underside of the sponson shall not exceed 63.5mm (2.50 in.). No part of the sponson shall extend downward below the point at which the side of the hull intersects the bottom surface of the hull by more than 63.5mm (2.50 in.). Aftermarket or modified sponsons must exceed 6mm (0.24 in.) in thickness. All leading edges must be radiused so as not to create a hazard. Sponsons may not be attached to the planing surfaces of the hull. Fins, rudders, skegs and other appendages that may create a hazard will not be allowed. (See diagrams in Appendix.)

Ski Division Only: Sponsons may be attached to the inside of the bond flange, but no part of the sponson may extend more than 38.00mm (1.50 in.) below the lower part of the bond flange (bumper removed). Sponsons attached to the inside of the bond flange shall not protrude outside the bond flange (bumper removed) when measured in a level horizontal plane.

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition.

- 8.2.4 Intake grate may be modified or aftermarket. Intake grate is required and must be the full-length type with at least one bar running parallel to the drive shaft. Grates may not extend more than 12.00mm (0.47 in.) below the flat plane of the pump intake area. All leading edges must be radiused so as not to create a hazard.
- 8.2.5 Pump cover plate may be modified or aftermarket. An extension may be added to the rear of the pump cover plate but shall not exceed the width of the original equipment plate. Modified and aftermarket plates must not extend more than 100.00mm (3.94 in.) beyond the end of the original equipment plate for *Ski* and *Sport Division* or 177.80mm (7.00 in.) for *Runabout*

Divisions. The sides of the extension must be connected to the radiused portion of the pump plate so as not to create a hazard. (See diagram in Appendix.) Fins, rudders, skegs and other appendages that may create a hazard will not be allowed.

- 8.2.6 Aftermarket trim tabs, either fixed, automatic and/or rider controlled, may be used. Original equipment trim plates that are detachable from the hull may be removed or replaced when installing aftermarket trim tabs. Trim tabs cannot exceed the width of the planing surface or extend rearward more than 100mm (3.94 in.) beyond the end of the original planing surface. All hull extensions mounted on the hull's transom will be considered as a trim tab. All edges must be radiused so as not to create a hazard. Fins, skegs, rudders and other appendages that may create a hazard are not allowed.
- 8.2.7 Replacement bumpers may be used provided a hazard is not created.
- 8.2.8 A soft, flexible water-spray deflector may be attached to the hull sides or to the bond flange provided a hazard is not created. No part of the deflector may extend beyond the perimeter of the original equipment bumper or side moldings as measured by a plumb line.
- 8.2.9 Handlebar, throttle, throttle cable, and grips may be modified or aftermarket. Handlebar cover may be modified or removed. Aftermarket switches and switch housings may be used. Steering shaft, steering shaft holder and handlebar holder may be aftermarket. The handlebar must be padded at the mounting bracket or, if it has a crossbar, the crossbar must be padded.

Aftermarket steering cables are allowed.

- 8.2.10 **Ski Division Only:** Handlepole (and mounting bracket) may be modified or aftermarket provided it functions as originally designed. Handlepole attaching point may be reinforced.
- 8.2.11 **Sport and Runabout Division Only:** Seat assembly may be modified or aftermarket. Seat height may be changed.
- 8.2.12 Padding and/or mat kits may be added and custom painting is allowed. The surface finish of any metal component outside the hull area above the bond flange may be polished, shot peened or painted.
- 8.2.13 Original bilge pump may be modified or disconnected. Aftermarket bilge draining systems that do not create a hazard are allowed.
- 8.2.14 Engine compartment foam may be removed, modified or aftermarket. Only floatation foam within the engine compartment may be removed. Only foam that can be removed without modification to any other part or parts, except where rules allow the parts to be modified, is allowed. Parts may not be relocated based on the removal of the foam. The hull's inner liner or deck may not be cut or modified to remove foam. Removal of foam between layers of the hull and/or deck is not allowed.
- 8.2.15 Storage covers, hatches, instrument cowlings and engine covers may be modified or aftermarket provided a hazard is not created and the OEM appearance is maintained. Additional engine compartment ventilation is allowed. Original equipment vents may be shielded or plugged. Handles, drop-in type storage buckets and bolt-on type mirrors may be modified, aftermarket or removed provided a hazard is not created.

Open Class

8.2.16 Ballast weight may be added within the normally exposed areas of the hull to alter the handling of the watercraft provided a hazard is not created. Only weight consisting of constant mass (i.e., water or other fluid is not allowed) that does not require the modification or relocation of any parts will be allowed unless such modification or relocation is specified by other rules.

8.3 ENGINE — TWO-STROKE

- 8.3.1 Engines may be bored. Aftermarket piston assemblies are allowed. Engine displacement must not exceed class designation (e.g., 800cc in 800 Superstock, 1600 Open, etc.). The number, type, and placement of rings on piston may be changed.
- 8.3.2 Original equipment crankcase must be used. Internal modifications to the fuel, oil and/or water-exposed surfaces are allowed. Filler material may be added to hollow pockets in the base gasket areas. Base gasket and intake surfaces may be machined. Additional carburetor pulse line fittings may be installed. Bearing and seal surfaces may not be modified. Crankcase drain system may be removed and plugged. Repairs to cracked or punctured crankcases may be made provided only one damaged area affecting one cylinder bank has been repaired. No other external modifications or external repairs are allowed.

Ski Division Only: Crankcases of Two-Stroke powered Ski may be interchanged between homologated watercraft of the same manufacturer. Crankcases must be of the same type (i.e., cylinder induction, crankcase induction or rotary valve induction) and number of cylinders as original equipment (cylinders may be increased/decreased to the corresponding number of the replacement OEM cylinder). Internal modifications to the fuel, oil and/or water exposed surfaces are allowed. Bearing and seal surfaces may not be modified. Filler material may be added to hollow pockets in the base gasket areas. Ignition/stator mounting area modifications are limited to spot facing, drilling and tapping threads for the purpose of mounting an aftermarket or modified ignition system. Additional carburetor pulse line fittings may be installed. Crankcase drain system may be removed or plugged. Additional mounting holes, not to exceed 10.00mm (0.40 in.) diameter, are allowed provided they do not penetrate the internal surface of the cases. Base gasket and intake surfaces may be machined. Repairs to cracked or punctured crankcases may be made provided only one damaged area affecting one cylinder bank has been repaired. External modifications to the crankcase finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only. No other external modifications or external repairs will be allowed.

- 8.3.3 Crankshaft assembly may be modified or aftermarket. Stroke and rod length may be changed.
- 8.3.4 Engine balancing assemblies may be modified, aftermarket, or removed.
- 8.3.5 Cylinders may be interchanged between homologated watercraft of the same manufacturer subject to restrictions announced by the IJSBA. Any modifications to the cylinder or crankcase must be approved, in writing, by the IJSBA. Base gasket, head gasket and exhaust manifold gasket surfaces may be machined. Port heights, widths and shapes may be changed. Ports may be added or deleted from cylinder. Cylinders may be machined to accept

aftermarket cylinder liners. Epoxy-type filler material may be added to hollow pockets in the base gasket areas and in the port area. Repairs to cracked or damaged cylinders may be made provided only one damaged area affecting one cylinder bank has been repaired. Cylinders may be machined to accept girdle-system cylinder heads. Water-cooling fittings may be added to cylinder. Exhaust power valve components and means of actuation may be modified or aftermarket.

8.3.5.a SKI DIVISION ONLY: Cylinder may be modified or aftermarket.

- 8.3.6 External modifications to the engine finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only.
- 8.3.7 Cylinder head may be modified or aftermarket.
- 8.3.8 Engine gaskets may be modified or aftermarket.
- 8.3.9 Exhaust system (i.e., manifold, head pipe, expansion chamber, waterbox, muffler(s), etc.) may be modified or aftermarket. Through-hull exhaust may be modified or aftermarket, providing a hazard is not created. Exit location of the exhaust gases may be relocated to the transom below the bond flange. No tuned portion of the exhaust system shall protrude outside the hull.
- 8.3.10 Cooling system may be modified or aftermarket. Aftermarket cooling lines and water bypass systems may be used. Bypass fittings may be modified, aftermarket and/or relocated but must be directed downward and/or rearward so as not to create a hazard for other riders. Any valves used within the entire cooling system must be of the fixed type or automatic (e.g., thermostats, pressure regulators, solenoids, etc.). Manually controlled devices (by any means of actuation) that alter the flow of cooling water during operation are not allowed. Cooling system flush kits are allowed.
- 8.3.11 Replacement starter motor and bendix may be used.
- 8.3.12 Replacement engine mounts may be used.
- 8.3.13 Oil-injection system may be disconnected or removed.
- 8.3.14 Replacement of general maintenance parts (e.g., spark plugs, spark plug wires, spark plug caps, wiring, water hoses, fuel lines, clamps and fasteners) shall not be restricted to original equipment. Stripped threads can be repaired.

8.4 ENGINE — FOUR-STROKE

- 8.4.1 Original engine block must be used. Internal modifications to the oil and/or water-exposed surfaces will be allowed. The head gasket surface of the cylinder block may be machined.
- 8.4.2 The original cylinder head casting must be used. Intake and exhaust runners may be modified. Material may be added to the runners. Intake and exhaust ports may be modified. Port diameters and shapes may be changed. Combustion chambers may be modified. Material may be added to the combustion chamber. The original number of intake and exhaust valves must be the same as original. Repairs to the cylinder head affecting one cylinder bank are allowed. The head gasket surface may be machined.
- 8.4.3 Aftermarket valvestrain components are allowed, providing the original method of activation is maintained (e.g., if originally activated by a camshaft, they may not converted to solenoid activation). Valves may be shimmed with OEM or aftermarket shims. Valve springs may be modified or aftermarket.

Open Class

Camshaft(s) may be aftermarket. The number of camshafts must be the same as original. Original bearing type and dimensions must be used. Cam timing may be changed. Cam gears, tensioners, chain or belt may be modified or aftermarket.

- 8.4.4 Engines may be bored. Aftermarket piston assemblies are allowed. Engine displacement must not exceed class designation (e.g., 1100cc in Runabout 1100 Superstock, 1600cc in Runabout Superstock Turbo, etc.).
- 8.4.5 Crankshaft may be modified or aftermarket. Stroke must remain the same as original. Total weight of the crankshaft must be within +/-5.00% of original equipment. Replacement bearings or bearing shells are allowed, providing they maintain their original type and dimensions.
- 8.4.6 Engine balancing assemblies may be modified, aftermarket, or removed.
- 8.4.7 Aftermarket connecting rods made of ferrous materials are allowed. Rod length may be changed.
- 8.4.8 Exhaust system (i.e., manifold, connecting pipes, hoses, muffler(s), etc.) may be modified or aftermarket. Through-hull exhaust may be modified or aftermarket, providing a hazard is not created. No tuned portion of the exhaust system may protrude outside of the hull. Exit location of the exhaust gases may be relocated to the transom below the bond flange
- 8.4.9 Cooling system may be modified or aftermarket. Additional cooling lines may be added. Aftermarket water bypass systems may be used. Cooling system bypass fittings may be modified or aftermarket and/or relocated but must be directed downward and/or rearward so as not to create a hazard for other riders. Any valves used within the entire cooling system must be of the fixed type or automatic (e.g., thermostats, pressure regulators, solenoids, etc.). Manually controlled devices (by means of actuation) that alter the flow of cooling water during operation are not allowed. Original cooling system flush kits are allowed.
- 8.4.10 Baffles in oil reservoir may be modified. The addition of baffles in oil reservoir is allowed. Oil pump may be modified or aftermarket.
- 8.4.11 Valve cover may be replaced for cosmetic purposes and/or weight reduction only.
- 8.4.12 Replacement starter motor and bendix may be used.
- 8.4.13 Replacement engine mounts may be used.
- 8.4.14 External modifications to the engine finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only.
- 8.4.15 Replacement of general maintenance parts (e.g., gaskets, seals, spark plug wires, spark plug caps, wiring, water hoses, fuel lines, fuel filters, oil filters, clamps and fasteners) shall not be restricted to original equipment. Stripped threads may be repaired. Fasteners may integrate locking mechanisms.

8.5 AIR/FUEL DELIVERY — TWO-STROKE

8.5.1 Carburetor(s) may be modified or aftermarket provided they do not vent or spill fuel at any attitude with or without the engine running. The number of venturis cannot exceed the number of cylinders. No slide-type carburetors.

Aftermarket primer may be used. Intake manifold assembly may be modified or aftermarket. Aftermarket crankcase pressure operated fuel pumps may be used.

- 8.5.2 Modified or aftermarket vapor/air separators must not exceed 2 in. x 6 in., and must have a return line to the fuel tank open at all times. Additional fuel reservoirs may not be used. Aftermarket or modified electric fuel pumps, not exceeding 4 psi, may be used. When the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off-type fuel pumps are allowed.
- 8.5.3 Aftermarket fuel-injection systems and components are allowed provided the following regulations are adhered to: High-pressure fuel hose meeting SAE J30R9 must be used; A.N. threaded-type fittings or equivalent and non-removable, crimped- type clamps must be used on the high-pressure portion of the system (i.e., hose clamps, tie wraps, etc. are not allowed); only metal-type fuel filters may be used on the high-pressure portion of the system; all other in-line filters must be installed on the low-pressure portion of the system. When the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off-type fuel pumps are allowed.
- 8.5.4 The entire fuel system is a closed system. The watercraft must not vent or spill fuel at any attitude with or without the engine running. Original equipment fuel tank, fuel filler and relief valve must be used and cannot be modified. The fuel pickup, fuel filter and fuel petcock may be removed and/or aftermarket parts may be used. Additional fuel filters may be used and fuel cell foam may be added to the original equipment fuel tank. Fuel tank filler cap may be modified or aftermarket provided a hazard is not created.
- 8.5.5 Flame arrester(s) which satisfy United States Coast Guard, SAE-J1928 Marine or UL-1111 Marine backfire flame arrester test standards must be installed. Aftermarket flame arresters satisfying one of these test standards are allowed. Intake silencer may be removed.
- 8.5.6 Reed valve assemblies may be modified or aftermarket. Rotary valve may be modified or aftermarket.

8.6 AIR/FUEL DELIVERY — FOUR-STROKE

- 8.6.1 The original fuel injectors may be modified to increase fuel-flow rate. Aftermarket fuel injectors that increase fuel flow are allowed provided they must not increase airflow into the combustion chamber. Fuel rail and fuel regulator may be modified or aftermarket. Additional fuel injectors may be added. Aftermarket fuel pumps are allowed provided that when the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off fuel pumps are allowed. High-pressure fuel hose meeting SAE J30R9 must be used; only metal-type fuel filters may be used on the high-pressure portion of the system; all other in-line filters must be installed on the low-pressure portion of the system
- 8.6.2 Flame arresters that meet USCG, UL-1111 or SAE J-1928 Marine standards must be used. Airflow sensor may be modified, aftermarket or removed. Ducting between the flame arrestor and throttle body may be modified or aftermarket.

Open Class

- 8.6.3 Throttle body may be modified or aftermarket. The number of butterflies may be increased but may not exceed the number of cylinders. Intake manifold assembly may be modified or aftermarket.
- 8.6.4 Carburetor(s) may be modified or aftermarket provided they do not vent or spill fuel at any attitude with or without the engine running. Carburetors may be used in addition to or in place of the fuel-injection system. The number of venturis cannot exceed the number of cylinders. No slide-type carburetors. Aftermarket primer may be used. Intake manifold assembly may be modified or aftermarket. Aftermarket air-pulse-pressure operated fuel pumps may be used.

8.7 IGNITION AND ELECTRONICS — TWO-STROKE/FOUR-STROKE

- 8.7.1 Ignition system, electrical box, flywheel and flywheel cover may be modified or aftermarket. Battery charging circuit may be disabled and/or removed.
- 8.7.2 An additional battery and battery box may be used. Batteries must fit into a proper battery box and be securely fastened. Batteries may be relocated.
- 8.7.3 Engine temperature sensor assembly may be disconnected and/or removed.

8.8 TURBOCHARGER/SUPERCHARGER

- 8.8.1 Turbocharger housing must be of the full circulating, water-jacket type at all times when the engine is running. Aftermarket turbochargers and superchargers may be used provided a hazard is not created. Original turbocharger or supercharger may be modified. Aftermarket turbochargers and superchargers may be added to originally normally aspirated watercraft. All hoses and pipes may be modified or aftermarket.
- 8.8.2 Intercooler may be modified or aftermarket.
- 8.8.3 Boost pressure-relief valve may be modified or aftermarket
- 8.8.4 Boost sensor may be modified or aftermarket.

8.9 DRIVELINE

- 8.9.1 Impeller, impeller housing, stator vane assembly, pump mounting plate and/ or pump shoe may be modified or aftermarket. Pump nozzle and directional nozzle may be modified or aftermarket. Overall length of the complete pump and nozzle assembly may be no more than 50.00mm (1.97 in.) longer than original equipment. Aftermarket nozzle trim systems may be used. Additional cooling fittings may be installed. Visibility spout must be removed or plugged. Silicone adhesive sealant may be used in addition to original equipment seal to seal pump inlet.
- 8.9.2 Couplers, bearing housing and driveshaft may be modified or aftermarket provided they maintain a 1:1 drive ratio between the engine and the pump.

MODIFIED CLASS

9.1 MODIFIED CLASS COMPETITION

Competitors in this class are allowed modifications to gain maximum machine and engine performance. Watercraft competing in this class must conform to the specifications which follow.

FREESTYLE ADDENDUM: Amateur and Pro Freestyle classes are allowed identical modifications with the exception that Amateur Freestyle Competitors may compete on PWC with a maximum displacement of 900cc while Pro Freestyle Competitors may compete on PWC with a maximum displacement of 1200cc.

GP ADDENDUM: When a class is designated a GP class then Modified Rules apply with the following additional providions: 1) OEM Crankcases from any homologated make/model PWC may be used; and, 2) Top deck may be modified or aftermarket so long as it resembles an OEM homologated top deck.

9.1.1 All watercraft must remain strictly stock, except where rules allow or require substitutions or modifications. Changes or modifications not listed here are not permitted. Some original equipment components may not comply with IJSBA rules.

NOTE: When rules permit or require equipment to be installed, replaced, altered or fabricated, it is the sole responsibility of the rider to select components, materials and/or fabricate the same so that the watercraft operates safely in competition.

- 9.1.2 Original equipment parts may be updated or backdated to original equipment parts of the same model. The part must be a bolt-on requiring no modifications to that part or any other parts except where rules allow substitutions or modifications. (Refer to Model Homologation listing on page 10-11.)
- 9.1.3 Sound level shall not exceed 86 dB(a) at 22.86m (75 ft.). See Section 19.5 (pg. 73).
- 9.1.4 Engine fuel must consist of gasoline meeting the criteria defined in Section 19.4.3 (pg. 73).

9.2 HULL

- 9.2.1 All watercraft must have a flexible tow loop attached to the bow. The tow loop should be made of a flexible material (e.g., nylon strap, rope, etc.) so as not to create a hazard. Tow hooks, which protrude beyond the plane of the hull, must be removed.
- 9.2.2 **Deck:** Original equipment deck must be used. Deck repairs may be made, provided they do not alter the standard configuration by more than 2.00mm (0.08 in.). The deck's bond flange may not be modified. Deck may be internally reinforced. Fasteners may be installed through the hull and deck for the purpose of securing components to interior surfaces, provided a hazard is not created.

Modified Class

If upper and lower components of the original equipment bond flange are separated and rejoined, they must be rejoined by the same method as original equipment (i.e., bonded together with a high-strength adhesive). (See bond flange diagram in Appendix.)

Freestyle ONLY: Footholds may be installed into the footwells. If the same watercraft is used for racing, the footwells must be blocked off, allowing no indentation into the footwell sides.

Freestyle ONLY: The top deck of freestyle craft may be modified or aftermarket, providing the following: The top deck must resemble the original top deck of the homologated watercraft; the length of the top deck must be no less than 165.1 mm (6.5 inches) shorter than the original OEM top deck and the width of top deck must be within 50.8 mm (2.0 in) of the original component; the craft must function as originally intended. The hull may be no smaller than the minimum measurements of the top deck. These restrictions also apply to the minimum length of the hull. The front bumper may add no more than 31.75 mm (1.25 in) to the overall length of the Top Deck for the purposes of meeting the minimum measurements. Fuel fillers may be relocated internally.

Freestyle, Ski Type, ONLY: The top deck of freestyle craft may be modified or aftermarket, providing the following: The top deck must resemble the generic look of existing homologated watercraft with the following dimensions: Minimum Length of 193 cm (76 in), Minimum Width of 68.5 cm (27 in), Minimum Height of 53.3 cm (21 in).

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition.

9.2.3 *Hull:* Hull may be modified or aftermarket but cannot exceed the length or width of the original equipment upper deck component of the bond flange as measured by a plumb bob (bumpers removed). Fins, rudders, skegs and other appendages that may create a hazard will not be allowed.

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition.

9.2.4 All watercraft may be equipped with a maximum of two sponsons. Original equipment sponsons may be modified, aftermarket, repositioned or removed. Overall length of each sponson shall not exceed 91.45cm (36.00 in.). Sponsons shall not protrude from the side of the hull by more than 100.00mm (3.94 in.) when measured in a level horizontal plane. The vertical channel created by the underside of the sponson shall not exceed 63.00mm (2.50 in.). No part of the sponson shall extend downward below the point at which the side of the hull intersects the bottom surface of the hull by more than 63.5mm (2.50 in.). Aftermarket or modified sponsons must exceed 6mm (0.24 in.) in thickness. All leading edges must be radiused so as not to create a hazard. Sponsons may not be attached to the planing surfaces of the hull. Fins, rudders, skegs and other appendages that may create a hazard will not be allowed. (See diagrams in Appendix.)

Ski Division Only: Sponsons may be attached to the inside of the bond flange, but no part of the sponson may extend more than 38.00mm (1.50

in.) below the lower part of the bond flange (bumper removed). Sponsons attached to the inside of the bond flange shall not protrude outside the bond flange (bumper removed) when measured in a level horizontal plane.

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition.

- 9.2.5 Intake grate may be modified or aftermarket. Intake grate is required and must be the full-length type with at least one bar running parallel to the drive shaft. Grates may not extend more than 12.00mm (0.47 in.) below the flat plane of the pump intake area. All leading edges must be radiused so as not to create a hazard.
- 9.2.6 Pump cover plate may be modified or aftermarket. An extension may be added to the rear of the pump cover plate but shall not exceed the width of the original equipment plate. Modified and aftermarket plates must not extend more than 100.00mm (3.94 in.) beyond the end of the original equipment plate for *Ski* and *Sport Division* or 177.80mm (7.00 in.) for *Runabout Divisions.* The sides of the extension must be connected to the radiused portion of the pump plate so as not to create a hazard. (See diagram in Appendix.) Fins, rudders, skegs and other appendages that may create a hazard will not be allowed.
- 9.2.7 Aftermarket trim tabs, either fixed, automatic and/or rider controlled, may be used. Original equipment trim plates that are detachable from the hull may be removed or replaced when installing aftermarket trim tabs. Trim tabs cannot exceed the width of the planing surface or extend rearward more than 100mm (3.94 in.) beyond the end of the original planing surface. All hull extensions mounted on the hull's transom will be considered as a trim tab. All edges must be radiused so as not to create a hazard. Fins, skegs, rudders and other appendages that may create a hazard are not allowed.
- 9.2.8 Replacement bumpers may be used provided a hazard is not created.
- 9.2.9 A soft, flexible water-spray deflector may be attached to the hull sides or to the bond flange provided a hazard is not created. No part of the deflector may extend beyond the perimeter of the original equipment bumper or side moldings as measured by a plumb line.
- 9.2.10 Handlebar, throttle, throttle cable, and grips may be modified or aftermarket. Handlebar cover may be modified or removed. Aftermarket switches and switch housings may be used. Steering shaft, steering shaft holder and handlebar holder may be aftermarket. The handlebar must be padded at the mounting bracket or, if it has a crossbar, the crossbar must be padded. Aftermarket steering cables are allowed.
- 9.2.11 **Ski Division Only:** Handlepole (and mounting bracket) may be modified or aftermarket provided it functions as originally designed. Handlepole attaching point may be reinforced.
- 9.2.12 **Sport and Runabout Division Only:** Seat assembly may be modified or aftermarket. Seat height may be changed.
- 9.2.13 Padding and/or mat kits may be added and custom painting is allowed. The surface finish of any metal component outside the hull area above the bond flange may be polished, shot peened or painted.

Modified Class

- 9.2.14 Original bilge pump may be modified or disconnected. Aftermarket bilge draining systems that do not create a hazard are allowed.
- 9.2.15 Engine compartment foam may be removed, modified or aftermarket.
- 9.2.16 Storage covers, hatches, instrument cowlings and engine covers may be modified or aftermarket provided a hazard is not created and the OEM appearance is maintained. Additional engine compartment ventilation is allowed. Original equipment vents may be shielded or plugged. Handles, drop-in type storage buckets and bolt-on type mirrors may be modified, aftermarket or removed provided a hazard is not created.
- 9.2.17 Ballast weight may be added within the normally exposed areas of the hull to alter the handling of the watercraft provided a hazard is not created. Only weight consisting of constant mass (i.e., water or other fluid is not allowed) that does not require the modification or relocation of any parts will be allowed unless such modification or relocation is specified by other rules.

9.3 ENGINE — TWO-STROKE

Engines may be bored. Aftermarket piston assemblies are allowed. Engine displacement must not exceed class designation (e.g., 800cc in 800 Modified, 1200cc in 1200 Modified, etc.). The number, type, and placement of rings on piston may be changed.

Freestyle ONLY: The maximum displacement for Ski type PWC in Pro freestyle competition is 1200cc. The maximum displacement for Ski Type PWC in the Amateur Freestyle classes is 900cc. The maximum displacement for a supercharged or turbocharged Ski type PWC is 800cc in any Freestyle class.

9.3.2 Crankcases may be interchanged between homologated watercraft of the same manufacturer. Crankcases must be of the same type (i.e., cylinder induction, crankcase induction or rotary valve induction) and number of cylinders as original equipment (no adding or deleting cylinders). Internal modifications to the fuel, oil and/or water exposed surfaces are allowed. Bearing and seal surfaces may not be modified. Filler material may be added to hollow pockets in the base gasket areas. Ignition/stator mounting area modifications are limited to spot facing, drilling and tapping threads for the purpose of mounting an aftermarket or modified ignition system. Additional carburetor pulse line fittings may be installed. Crankcase drain system may be removed or plugged. Additional mounting holes, not to exceed 10.00mm (0.40 in.) diameter, are allowed provided they do not penetrate the internal surface of the cases. Base gasket and intake surfaces may be machined. Repairs to cracked or punctured crankcases may be made provided only one damaged area affecting one cylinder bank has been repaired. External modifications to the crankcase finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only. No other external modifications or external repairs will be allowed.

Freestyle ONLY: OEM crankcases may be substituted with eligible replicas of homologated Two Stroke crankcases. For a crankcase to be an eligible replica, it must reasonably resemble the look of the OEM crankcases and provide for some amount of OEM components (ie cylinders, starters, crankshaft, etc.) to still be utilized. IJSBA will publish a list of approved replica crankcases.

- 9.3.3 Cylinder and cylinder head may be modified or aftermarket.
- 9.3.4 Crankshaft assembly may be modified or aftermarket. Stroke and rod length may be changed.
- 9.3.5 Engine bed and motor mounts may be modified or aftermarket. Engine may be repositioned in the hull.
- 9.3.6 Engine gaskets may be modified or aftermarket.
- 9.3.7 Exhaust system (i.e., manifold, head pipe, expansion chamber, waterbox, muffler(s), etc.) may be modified or aftermarket. Through-hull exhaust may be modified or aftermarket, providing a hazard is not created. Exit location of the exhaust gases may be relocated to the transom below the bond flange. No tuned portion of the exhaust system shall protrude outside the hull.
- 9.3.8 Cooling system may be modified or aftermarket. Aftermarket cooling lines and water bypass systems may be used. Bypass fittings may be modified, aftermarket and/or relocated but must be directed downward and/or rearward so as not to create a hazard for other riders. Any valves used within the entire cooling system must be of the fixed type or automatic (e.g., thermostats, pressure regulators, solenoids, etc.). Manually controlled devices (by any means of actuation) that alter the flow of cooling water during operation are not allowed. Cooling system flush kits are allowed.
- 9.3.9 Replacement starter motor and bendix may be used.
- 9.3.10 Oil-injection system may be disconnected or removed.
- 9.3.11 Replacement of general maintenance parts (e.g., spark plugs, spark plug wires, spark plug caps, wiring, water hoses, fuel lines, clamps and fasteners) shall not be restricted to original equipment. Stripped threads can be repaired.

9.4 AIR/FUEL DELIVERY — TWO-STROKE

- 9.4.1 Carburetor(s) may be modified or aftermarket provided they do not vent or spill fuel at any attitude with or without the engine running. The number of venturis cannot exceed the number of cylinders. No slide-type carburetors. Aftermarket primer may be used. Intake manifold assembly may be modified or aftermarket. Aftermarket crankcase pressure operated fuel pumps may be used.
- 9.4.2 Modified or aftermarket vapor/air separators must not exceed 2 in. x 6 in., and must have a return line to the fuel tank open at all times. Additional fuel reservoirs may not be used. Aftermarket or modified electric fuel pumps, not exceeding 4 psi, may be used. When the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off-type fuel pumps are allowed.
- 9.4.3 Aftermarket fuel-injection systems are allowed provided the following regulations are adhered to: High-pressure fuel hose meeting SAE J30R9 must be used; A.N. threaded-type fittings or equivalent and non-removable, crimped-type clamps must be used on the high-pressure portion of the system (i.e., hose clamps, tie wraps, etc. are not allowed); only metal-type fuel filters may be used on the high-pressure portion of the system; all other in-line filters must be installed on the low-pressure portion of the system. When the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off-type fuel pumps are allowed.

Modified Class

9.4.4 The entire fuel system is a closed system. The watercraft must not vent or spill fuel at any attitude with or without the engine running. Original equipment fuel tank, fuel filler and relief valve must be used and cannot be modified. The fuel pickup, fuel filter and fuel petcock may be removed and/or aftermarket parts may be used. Additional fuel filters may be used and fuel cell foam may be added to the original equipment fuel tank. Fuel tank filler cap may be modified or aftermarket provided a hazard is not created.

Freestyle ONLY: The fuel tank may be modified or aftermarket, providing the watercraft must not vent or spill fuel at any attitude with or without the engine running. The tank must be securely fastened to the hull. The fuel filler location may be relocated.

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition.

- 9.4.5 Flame arrester(s) which satisfy United States Coast Guard, SAE-J1928 Marine or UL-1111 Marine backfire flame arrester test standards must be installed. Aftermarket flame arresters satisfying one of these test standards are allowed. Intake silencer may be removed.
- 9.4.6 Reed valve assemblies may be modified or aftermarket. Rotary valve may be modified or aftermarket.

9.5 IGNITION AND ELECTRONICS — TWO-STROKE

- 9.5.1 Ignition system, electrical box, flywheel and flywheel cover may be modified or aftermarket. Battery charging circuit may be disabled and/or removed.
- 9.5.2 An additional battery and battery box may be used. Batteries must fit into a proper battery box and be securely fastened. Batteries may be relocated.
- 9.5.3 Engine temperature sensor assembly may be disconnected and/or removed.

9.6 DRIVELINE

- 9.6.1 Impeller, impeller housing, stator vane assembly, pump mounting plate and/ or pump shoe may be modified or aftermarket. Pump nozzle and directional nozzle may be modified or aftermarket. Overall length of the complete pump and nozzle assembly may be no more than 50.00mm (1.97 in.) longer than original equipment. Aftermarket nozzle trim systems may be used. Additional cooling fittings may be installed. Visibility spout must be removed or plugged. Silicone adhesive sealant may be used in addition to original equipment seal to seal pump inlet.
- 9.6.2 Couplers, bearing housing and driveshaft may be modified or aftermarket provided they maintain a 1:1 drive ratio between the engine and the pump.

RIDER CLASSIFICATIONS

10.1 RIDER CLASSIFICATIONS

- 10.1.1 The International Jet Sports Boating Association does not test the skill of individual participants in IJSBA-sanctioned events, nor does the Association judge each competitor's competence. Participants are solely responsible for their safety.
- 10.1.2 As a general policy, the IJSBA requires that riders be 16 years old or older for all competition classes except Junior 10-12 year old Ski Stock and Junior 13-15 year old Ski Stock and Limited. Boating laws in some countries require higher age minimums or allow lower age limits. Refer to Section 23 and/or contact the local IJSBA International Affiliate for information about specific age requirements in each country. A birth certificate and/or passport shall be presented to substantiate age.
- 10.1.3 The IJSBA and most IJSBA International Affiliates require that waiver of liability be signed by a parent or legal guardian if the competitor is under 18 years old. A birth certificate and/or drivers license may be required to substantiate age.

A Rider will represent his/her country of citizenship at the World Finals. In case of multiple citizenships, the country of residence will apply.

10.1.4 Riders may have different skill classifications for Runabout/Sport and Ski divisions (i.e., an Expert Runabout racer may also be a Novice Ski racer).

10.2 BEGINNER

10.2.1 The Beginner class is provided as an entry-level class for new riders who wish to experience the fun of racing. It is open to all Novice competitors (see Section 10.3) who have competed in three or fewer races. In the case of a series, riders may compete in the entire series prior to moving to the Novice class. Otherwise, in a rider's fourth race, he/she must compete in the Novice class.

Beginner-class competitors may race Stock or Limited watercraft.

10.3 NOVICE

10.3.1 Novice competitors are those with minimal racing experience. First-time competitors must participate in the Novice or Beginner class.

THE IJSBA STRONGLY ADVISES AGAINST NOVICES COMPETING IN OPEN/MODIFIED/GP CLASSES WHERE SUPERCHARGED OR TURBOCHARGED RUNABOUTS ARE ALLOWED.

10.3.2 Novice-class riders may reclassify themselves as Expert at their own discretion. Novice-class riders may also be reclassified as Expert-class riders at the discretion of the IJSBA or IJSBA International Affiliate.

10.4 EXPERT

10.4.1 Expert-class riders are those who demonstrate a skill level that has exceeded beyond that of a Novice-class rider.

Rider Classifications

- 10.4.2 An Expert competitor may request to be reclassified as a Pro by submitting a Change of Classification Form to the IJSBA or IJSBA International Affiliate. The IJSBA and IJSBA International Affiliates have the authority to move an Expert competitor to Pro if he/she displays skills that are superior to others in that class.
- 10.4.3 An Expert competitor may request to be reclassified as an Novice by submitting a Change of Classification to the IJSBA or IJSBA International Affiliate.
- 10.4.4 An Expert competitor may be moved back to Novice if it is determined by the IJSBA or IJSBA International Affiliate that his/her riding skill is not Expertclass level.

10.5 AMATEUR

10.5.1 The Amateur class is comprised of Novice- and Expert-level riders.

10.6 PRO

- 10.6.1 Pro riders are those who have substantial racing experience and have advanced competition skills.
- 10.6.2 A Pro competitor may request to be reclassified as an Expert by submitting a Change of Classification Form to the IJSBA or IJSBA International Affiliate.
- 10.6.3 A Pro rider may be moved back to Expert if it is determined by the IJSBA or IJSBA International Affiliate that his/her riding skill is not Pro-class level.

10.7 PRO-AM

10.7.1 The Pro-Am class is comprised of Expert- and Pro-level riders.

10.8 VETERANS

- 10.8.1 The Veterans Ski class is open to a riders who are 30 years of age or older. The Veterans Sport and Runabout classes are open to riders 35 years of age or older.
- 10.8.2 Closed-course Veterans-class competitors may race Stock, Limited or Open watercraft.

10.9 MASTERS

- 10.9.1 The Masters Ski class is open to riders who are 40 years of age or older. The Masters Sport and Runabout classes are open to riders 45 years of age or older.
- 10.9.2 Closed-course Masters-class competitors may race Stock, Limited or Superstock watercraft.

10.10 WOMEN

- 10.10.1 Women's classes in Novice, Expert and Pro categories are for female riders who elect to compete in them, generally for separate points, awards and/or purse.
- 10.10.2 Closed-course Women-class competitors may race Stock or Limited watercraft.

10.11 CLASSIFICATION CHANGES

- 10.11.1 Rider classification changes not described in Sections 10.2 through 10.10 must be submitted to the IJSBA or IJSBA International Affiliate on a Change of Classification Form for consideration.
- 10.11.2 The IJSBA and IJSBA International Affiliates reserve the right to reclassify any rider as deemed appropriate in the best interest of safety, competition and/or sportsmanship.
- 10.11.3 A Rider may not be reclassified during the World Finals, except where specifically noted by the IJSBA.
- 10.11.4 Any Novice classified rider that wins a title during the World Finals will automatically be classified as an Expert rider as of January 1st the following year. Reclassification may be appealed in writing within 30 days following the last day of World Finals competition.





P.O. Box 518 • 654 Avenue K, Calimesa, CA 92320 Tech 909/795-2505 • Fax 909/795-6351 • Orders 800/969-7528 e-mail: sales@skat-trak.com • WWW.Skat-trak.com

EVENTS

11.1 SAFETY

- 11.1.1 The International Jet Sports Boating Association does not inspect courses used in IJSBA-sanctioned events. Participants are solely responsible for their safety at IJSBA-sanctioned races and should assess their own ability to negotiate each individual course. Participants who doubt the competence of course officials, have concerns about the safety of the course, or their own ability to negotiate the course, or are uncertain about the condition of their watercraft, or doubt the competence of fellow competitors, should not participate and should request the return of their entry fee before competitive activity begins.
- 11.1.2 It is the sole responsibility of the promoter to ensure compliance with all rules relating or directed to safety and to otherwise act to promote the safety of the competition. The IJSBA does not attend or in any way supervise every competition and cannot undertake to determine safety aspects. It is the sole responsibility of the promoter to purchase the required liability insurance.
- 11.1.3 IJSBA-sanctioned events may use routes traversing public waterways, and the promoter is not responsible for their condition or for the actions of other individuals using the public waterway.

11.2 CLOSED-COURSE EVENT

11.2.1 A closed-course event is a contest of speed and riding ability featuring multiple competitors negotiating multiple laps of a course consisting of left and/or right-hand turns. Obstacles (e.g., log jumps and/or ramps) may be present. Competing watercraft must meet IJSBA class specifications. For specific closed-course event rules, refer to Section 12, pgs. 50-53.

11.3 SLALOM EVENT

11.3.1 A slalom event is a timed event requiring a competitor to negotiate zig-zag right and left-hand turns around stationary markers. Competing watercraft must meet IJSBA class specifications. For specific slalom event rules, refer to Section 13, pg. 54.

11.4 FREESTYLE EVENT

11.4.1 Freestyle events are intended to show a rider's skill and expertise in executing difficult, challenging and creative maneuvers within a set period of time and scored by a panel of judges. Competing watercraft must meet IJSBA class specifications. For specific freestyle event rules, refer to Section 14, pg. 55.

11.5 ENDURANCE EVENT

11.5.1 Endurance events are long-distance races which may or may not include required turns and be of more than one lap. Competing watercraft must meet IJSBA class specifications. For specific endurance event rules, refer to Section 15, pgs. 56-59.

11.6 DRAG-RACING EVENT

11.6.1 Drag-racing events can be either timed/single-elimination contests or bracket elimination-type events over a predetermined distance. Competing watercraft must meet IJSBA class specifications. Contact the IJSBA for specific rules.

11.7 SPECIAL EVENT

11.7.1 "Special events" are any type of watercraft event meeting IJSBA technical requirements that are not hazardous to participants. Examples: obstacle race, relay races, Australian Pursuit, or other fun-type event that encourages participation by riders and tests skills and performance of rider and machine. These events may be determined by the promoter, but prior approval from the IJSBA is required (see Section 3.2, page 5). Watercraft must meet IJSBA class specifications. For specific special event rules, refer to Section 16, pg. 60.



CLOSED-COURSE EVENTS

12.1 GENERAL PRE-START PROCEDURES

- 12.1.1 Due to varying shoreline and water conditions, the type of start will be explained at the riders meeting.
- 12.1.2 Watercraft must be pushed or ridden at idle to the starting line. All watercraft must enter the race course, in both practice and racing, through the starting area only. Entry from the pit area is not allowed.
- 12.1.3 The maximum number of watercraft per closed-course heat should not exceed the following:

CLASS	SKI DIVISION	SPORT DIVISION	RUNABOUT DIVISION
JUNIOR	12 (14*)	12 (14*)	8 (12*)
BEGINNER	12 (14*)	12 (14*)	10 (14*)
NOVICE	14 (16*)	12 (16*)	12 (16*)
EXPERT	16 (18*)	14 (18*)	14 (18*)
PRO	18 (20*)	16 (20*)	16 (20*)

* If a dual first-turn design is used.

IN RUNABOUT OPEN CLASSES, THE IJSBA RECOMMENDS REDUCING THE AMOUNT OF ALLOWED WATERCRAFT BY A TOTAL OF FOUR (Two on each side of a split start).

- 12.1.4 The method for determining starting lineup in heat or qualifying races is by drawing for position. The number drawn will be the starting position, from the pole to the outside. (The pole position is always closest to the first turn buoy.) Starting-line positions for main events are determined by finish positions in heat or qualifying races. At the Race Director's discretion, riders may be given their choice of starting-line position for main events based on their qualifying position.
- 12.1.5 No warm-up or practice starts will be allowed during staging or while getting positioned in the starting area.
- 12.1.6 The Race Director may penalize any rider whose method of start interferes with other participants.
- 12.1.7 A damaged watercraft may be prohibited from competition if, in the opinion of the Race Director, it presents a hazard to spectators, participants or the rider him/herself. The decision of the Race Director is final.
- 12.1.8 The watercraft used in a semi-final or final race must be the same watercraft used to qualify for that race. If the moto scoring system is used, the same watercraft must be used in all motos. The use of a second or backup

watercraft, due to damage or other conditions that make the craft nonoperational, may be allowed, providing that it meets all class and safety regulations. Any such replacements can be made only with the authorization of the Race Director.

12.2 GENERAL STARTING PROCEDURES

- 12.2.1 If a rubber band-type starting gate is used, riders should stay clear of the neutral zone to avoid any chances of the rubber band hindering their start. All riders must position the nose of their boats behind the rubber band. A maximum staging distance of 60cm (2 ft.) from the rubber band will be allowed. No running starts. (See diagram in Appendix.) Riders must be on the starting line at the start of the race to compete (i.e., riders may not enter the race course unless they are on the starting line at the start of the race).
- 12.2.2 The starter will signal riders to start their engines and hold up the "2" card.
- 12.2.3 After acknowledging the riders, the starter will hold up the "1" card. Within seconds, the "1" card will be turned sideways signifying the race will start at any moment. The race will start when the green flag is waved, or when the starting gate is tripped.
- 12.2.4 Other methods of starting may be used with prior approval from the IJSBA.
- 12.2.5 The start of the race may be delayed only when the "2" card is displayed. Once the starter has displayed the "1" card, the start of the race cannot be delayed. Only one two-minute hold will be granted per race unless the race is officially restarted. Both boat and rider must be on the starting line in order to receive a two-minute hold.
- 12.2.6 Only one holder and one mechanic will be allowed in the starting area. Runabout and Sport classes will be allowed two holders. (The Race Director may allow more holders depending on water conditions.) Holders will not be allowed to use ropes or other implements to hold their riders' watercraft. When the "2" card is held up, the mechanic must move to the back of starting area. All other persons except officials and/or designated media must be out of the starting area.
- 12.2.7 **Ski Division** riders will not be allowed to place feet or knees in or on the riding platform until the race has been officially started. Both feet must remain on the ground. Riders must be in a standing position on their watercraft immediately after the start and well before reaching the first turn buoy. Riders cannot sit on the rails or kneel in the tray. No rider will be allowed to use devices (e.g., milk crates) to aid his or her starting procedure unless all riders are given the same opportunity and it is announced by the Race Director. Riders not obeying these rules will be penalized.
- 12.2.8 **Sport and Runabout Division** riders may start in their riding positions and may sit while riding. No rider will be allowed to use devices (e.g., milk crates) to aid his or her starting procedure unless all riders are given the same opportunity and it is announced by the Race Director. Riders not obeying these rules will be penalized.

12.3 GENERAL RESTART PROCEDURES

12.3.1 The Race Director may have a restart at his/her discretion. Reasons for restart may include (but are not limited to) a jumped start, loose buoy, an

accident on the first lap involving several riders, or a downed rider whose presence potentially creates a hazard.

- 12.3.2 All machines will be stopped under the red flag. The starter will notify riders when to move their machines, and will have them proceed slowly to the point of restart. Any rider causing the stoppage of a race and subsequent restart, or any rider unable to immediately restart, may be penalized.
- 12.3.3 If the race is restarted, riders not having previously started in that race will not be allowed to enter with the restart. Exceptions to this rule must be clearly stated at the Rider's Meeting or be printed in writing and published in reasonable advance of the event.
- 12.3.4 A rider who jumps the start and causes a restart must restart in the same position with a dead engine. The rider must remove the lanyard from the engine stop switch and hold it with his/her arm extended overhead. The rider must be standing or sitting in an upright position. After the green flag is waved or the starting gate is tripped, the lanyard may be connected and the engine started.
- 12.3.5 If a race is stopped with fewer than three laps completed and a restart is required, a total restart (i.e., previously run laps will not count) may be used. Riders will be assembled on the starting line in the order of the original start. Any rider penalized on the original start will be required to restart under the same penalty.
- 12.3.6 If a race is stopped after three or more laps have been completed and a restart is required, a flying start may be used. The riders will be positioned in a single-file line in the order in which the last complete lap was scored. The riders will be led around the course in single file at slow speed, maintaining one boat length between them. When the starter waves the green flag, the riders may resume racing. No passing will be allowed until the green flag is waved by the starter.

12.4 GENERAL REGULATIONS

- 12.4.1 **Corner/Course Marker Buoys:** All riders must negotiate completely around any course marker buoy in either slalom or closed-course events. The nose of the watercraft must be clearly steered around any marker buoy. Any competitor riding over a course marker buoy will be judged to have missed the buoy no matter what side of the watercraft the buoy reappears. The rider will be required to renegotiate the turn buoy going in the proper direction, and will be required to do so in a safe manner so as not to create a hazard or danger to other riders on the course.
- 12.4.2 **Missed Buoys:** A rider failing to negotiate a buoy or missing a marker buoy in a closed-course event will be penalized one lap for each missed buoy unless he/she completes the announced procedure for picking up a buoy.
- 12.4.3 *Merge Lanes:* A rider crossing over the line created by merge-lane buoys will be penalized one lap. Going back to renegotiate the merge lane is not allowed.
- 12.4.4 **Buoy Identification:** Red buoys signify a left-hand turn. Yellow buoys signify a right-hand turn. Black Buoys are generally used to signify the path taken

by a rider who has missed a buoy. Blue and other specially colored buoys are for special use (e.g., merge lanes, perimeter boundaries, etc.). The Race Director will explain their purpose at the riders meeting.

- 12.4.5 *Finish Line Buoy:* Finish line buoys, two (2) each, should be clearly marked with contrasting colored checkerboard and/or the word "Finish" repeating around the central circumference of each buoy. A rider incorrectly negotiating a finish line buoy will be penalized two positions. Going back to renegotiate a finish line buoy is not allowed.
- 12.4.6 **At the Finish:** A rider and his/her watercraft shall be considered a unit to constitute a finish. The rider must be in reasonable control to be scored as finishing an event.



SLALOM EVENTS

13.1 GENERAL REGULATIONS

- 13.1.1 When applicable, Women-, Veterans- and Masters-class riders entering more than one slalom class per division must make their respective Women-, Veterans- or Masters-class runs first.
- 13.1.2 Each rider will be allowed two runs with a maximum of one minute between each run. The same watercraft must be used in all slalom runs per class.
- 13.1.3 Riders attempting to trip electronic timing systems with their hands or by any means other than the watercraft itself will be disqualified.
- 13.1.4 **Missed buoys:** A rider failing to properly negotiate a course buoy in slalom will be penalized 10 seconds for each buoy missed, unless he/she goes back to pick up the buoy in the proper direction.
- 13.1.5 *Tie breaker:* Finishing-position tie breaker for slalom events is a rider's second fastest run (i.e., assuming two or more riders have identical best runs), the rider with the best next-fastest run will receive the higher ranking. If still tied, the event will be scored as such and the position will be considered a tie.



FREESTYLE EVENTS

14.1 GENERAL FREESTYLE REGULATIONS

- 14.1.1 The rider will be judged by three to seven persons scoring on a scale of "1 to 10," with "10" being best. There is a two-minute time limit. Other times may be used, but must be approved by the IJSBA and will be announced to competitors during the riders meeting.
- 14.1.2 Maneuvers, tricks or stunts that may create a hazard to the rider, spectators, pit crew or officials must be approved in advance by the Race Director.
- 14.1.3 Only one person per watercraft during competition. Only one homologated watercraft may be used during competition. Freestyle competitors may compete on Stock, Limited, Superstock or Modified watercraft.
- 14.1.4 Riders competing in freestyle should draw for their starting order prior to the event.
- 14.1.5 Each freestyle rider must signify the start of his or her routine with a wave of the hand over his/her head.
- 14.1.6 A freestyle routine of greater difficulty with minimal mistakes will be scored higher than a routine of lesser difficulty with fewer or no mistakes.
- 14.1.7 Each freestyle rider should finish as close to the time limit as possible.
- 14.1.8 No score or points will be awarded to freestyle routines that are less than one minute in length.
- 14.1.9 The judges will award a score of at least "6" if the full two-minute freestyle routine has been completed.
- 14.1.10 In the case of a tie for first place, each competitor in the tie will perform a one-minute routine. Ties for all other positions will be broken by re-adding the high and low scores that may have been thrown out to calculate their original total score. If no high and low scores were thrown out to calculate the original total score, the highest single score will be used to break the tie. If still tied, the next highest individual score will be used and so on. If still tied, the riders will then perform a one-minute routine.

ENDURANCE EVENTS

15.1 GENERAL PRE-START PROCEDURES

- 15.1.1 Due to varying shoreline and water conditions, the type of start will be explained at the riders meeting.
- 15.1.2 Watercraft must be pushed or ridden at idle to the starting line. All watercraft must enter the race course, in both practice and racing, through the starting area only. Entry from the pit area is not allowed.
- 15.1.3 No warm-up or practice starts will be allowed during staging or while getting positioned in the starting area.
- 15.1.4 The Race Director may penalize any rider whose method of start interferes with other participants.

15.2 GENERAL STARTING PROCEDURES

- 15.2.1 The Race Director will explain the race starting procedure at the pre-race riders meeting (e.g., staggered starts, class, category, teams, etc.).
- 15.2.2 A *LeMans* start can be used to start an entire field of riders or individual classes. Each rider will line up his/her watercraft in the designated starting area facing offshore. Each rider will be allowed one holder to steady the watercraft. (The Race Director may allow more holders depending on water conditions.) Riders will line up on shore at equal distances away from their watercraft predetermined by the Race Director. At the signal from the Starter, riders will race on foot to their watercraft, start the engine and enter the course.
- 15.2.3 A **Driscoll** start can be used to start an entire field of riders or individual classes. Each rider will line up his/her watercraft in the designated starting area facing offshore. The rider will stand with both feet on the ground in front of the watercraft facing toward shore. The rider will place both hands together holding the nose of the watercraft. At the signal from the Starter, riders will maneuver into the proper riding position on their watercraft, start the engine and enter the course.
- 15.2.4 A *Timed* start is used to start individual riders one at a time. Each rider is assigned a starting time. The race will start at a time predetermined by the Race Director. The first rider will start at the posted start time with each subsequent rider typically to be started in 15- or 30-second intervals until all riders have started. Each rider's individual finish time will be corrected depending on his/her start time.
- 15.2.5 A *Running* start can be used to start the entire field of riders or individual classes. All riders to be started will line up his/her watercraft in an area predetermined by the Race Director. Engines will be running at idle speed. When the Starter has determined all riders are in their proper positions, a signal for the start of the race will be given.
- 15.2.6 In LeMans, Driscoll and Running starts, the watercraft must be lined up with no less than 1m (3 ft.) separating the sides of the watercraft.

15.2.7 Only one mechanic will be allowed in the starting area for each rider. Holders will not be allowed to use ropes or other implements to hold their riders' watercraft. All other persons, excluding officials and/or designated media must be out of the starting area.

15.3 GENERAL RESTART PROCEDURES

- 15.3.1 The Race Director may have a restart at his/her discretion. Reasons for a restart may include (but are not limited to) a jumped start, loose buoy, an accident on the first lap involving several riders, or a downed rider whose presence potentially creates a hazard.
- 15.3.2 All machines will be stopped under the red flag. Course officials will notify riders when to move their machines, and will have them proceed slowly to the point of restart. Any rider causing the stoppage of a race and subsequent restart, or any rider unable to immediately restart, may be penalized.

15.4 GENERAL REGULATIONS

- 15.4.1 **Rider/Pit Crew Identification:** All riders and pit crew members who are registered to compete or will be entering into controlled areas shall wear an event identification wristband permanently marked with the competitor's last name and race number. Team-class competitors shall wear an event identification wristband permanently marked with the race number and each of the competitor's last names. The last name of the Team competitor on which the individual wristband is worn shall be additionally marked to identify the particular competitor. (i.e., wearer's last name underlined or circled)
- 15.4.2 *Rider Responsibility:* In long-distance events it is a rider's responsibility to inform the nearest race official of any injured rider(s) or disabled boat(s) on the course.
- 15.4.3 **Course Abandonment:** If a rider abandons the race course, the rider or a team member must notify the Race Director immediately. A rider or team may be penalized for non-notification or for failure to notify within a reasonable amount of time.
- 15.4.4 **Corner/Course Marker Buoys:** A course marker is a mandatory negotiating point signified by a perfectly identifiable floating device whose position will be described during the pre-race riders meeting and a publicly posted course map (practice or reconnaissance lap(s) may also be used). Buoys or lines of buoys may be used to guide, slow down or mark areas where a change of pace is expected. Any such buoy(s) shall be clearly identifiable by different size or color from other course marker buoys. All riders must negotiate completely around any course marker buoy. The nose of the watercraft must be clearly steered around any marker buoy. Any competitor riding over a course marker buoy will be judged to have missed the buoy no matter what side of the watercraft the buoy reappears. The rider will be required to renegotiate the turn buoy going in the proper direction, and will be required to do so in a safe manner so as not to create a hazard or danger to other riders on the course.

Endurance Events

15.4.5 **Missed Buoys:** A rider failing to negotiate a buoy or missing a marker buoy will be penalized for each missed buoy unless he/she completes the proper method for correcting a missed buoy.

The preferred method for correcting a missed buoy is to have a strategically placed buoy on the course which serves as a "penalty buoy" (commonly called the "Black Buoy"). If a rider fails to properly negotiate, or misses, a buoy then that rider must properly negotiate the penalty buoy instead of reattempting the missed buoy. The buoy should be placed between the merge section of an option course and the finish line buoys. The penalty buoy should be placed in a position to cause the offending rider to markedly depart from the course. Riders who cut the course may not make up any missed buoy by negotiating the penalty buoy. If the race director determines that a rider is strategically missing a buoy to gain a position then that rider may be penalized even if the penalty buoy is properly negotiated. The penalty buoy should be placed in a location sufficient to cause lost time to the rider who has missed the originally intended buoy so that an advantage is not gained by having to take the penalty buoy. The location of the penalty buoy should allow for safe travel to and from the rest of the race course. The penalty buoy may not be renegotiated if missed or improperly negotiated. The race director may make some buoys/pathways ineligible for the penalty buoy if missed or improperly negotiated (i.e. log jump, merge buoy, first turn buoy, etc.).

A rider circling back against traffic to renegotiate a buoy is not the preferred method for correcting a missed buoy. The IJSBA recommends that this procedure not be used to correct a missed buoy.

- 15.4.6 **Buoy Identification:** Red buoys signify a left-hand turn. Yellow buoys signify a right-hand turn. Blue and other specially colored buoys are used for special use. The Race Director will explain their purpose at the riders meeting.
- 15.4.7 *Finish Line Buoy:* Finish line buoys, two (2) each, should be clearly marked with contrasting colored checkerboard and/or the word "Finish" repeating around the central circumference of each buoy. A rider incorrectly negotiating a finish line buoy will be penalized two positions. Going back to renegotiate a finish line buoy is not allowed.
- 15.4.8 **At the Finish:** A rider and his/her watercraft shall be considered a unit to constitute a finish. The rider must be in reasonable control to be scored as finishing an event.

15.5 FUEL SYSTEM, FUELING AND PIT STOPS

15.5.1 The entire fuel system is a closed system. The watercraft must not vent or spill fuel at any attitude with or without the engine running. Original equipment fuel tank must be used and may not be modified. Fuel filler assembly may be aftermarket or modified. The fuel filler assembly must be mounted thru the deck or through a plate that completely blocks off a storage opening (i.e., no internal refueling allowed and no spilt fuel may enter engine compartment). The fuel pickup and fuel filter(s) may be removed and/or aftermarket parts may be used. Fuel tap assembly may be modified, aftermarket or removed. Additional fuel filters may be used and fuel cell
foam may be added to the original equipment fuel tank. Modified or aftermarket vapor/air separators must not exceed 2 in. x 6 in., and must have a return line to the fuel tank open at all times. Additional fuel reservoirs may not be used.

- 15.5.2 Fueling and refueling must be performed in areas designated by the Race Director.
- 15.5.3 The Race Director may prohibit any method of refueling that creates a potential hazard to spectators, participants or the rider him/herself. The decision of the Race Director is final.
- 15.5.4 Riders may be penalized for spilling fuel.
- 15.5.5 All riders must operate his/her watercraft at 5 mph while entering and exiting the designated lane leading to the pit and refueling areas. Riders may be penalized for exceeding the 5 mph speed limit.

15.6 SPECIAL EQUIPMENT

- 15.6.1 Equipment required by the Race Director and/or local authorities may include but is not limited to the following:
 - Compass and/or other navigational equipment
 - · Flexible tow loop attached to front of watercraft
 - Tow rope
 - VHF radio or cellular phone
 - Drinking water and rations
 - Radar reflector
 - First Aid kit
 - · Flares or other signaling device
 - · Emergency repair kit

15.7 PENALTIES

- 15.7.1 The Race Director may assign stop-and-go and/or time penalties for course and other infractions. A rider signaled by the Race Director or an appointed official must bring their watercraft to a complete stop in a manner so as not to create a hazard to oncoming riders and stop the engine. When signaled, the rider may restart the engine and continue racing. Due to varying course design and starting methods, the length of stop-and-go and/or time penalties will be determined by the Race Director and explained at the riders meeting.
- 15.7.2 Any competitor entering an area prohibited to navigation may be penalized.

Special Events

SPECIAL EVENTS

16.1 SPECIAL EVENT BASICS

16.1.1 A special event is any type of watercraft event that meets IJSBA technical requirements and is not hazardous to participants. Examples: obstacle race, relay races, Australian pursuit, or other fun-type event that encourages participation by riders and tests skills and performance of rider and machine. These events may be determined by the promoter, but prior approval from the IJSBA is required (also see Section 3.2, pg. 5). Watercraft must meet IJSBA class specifications.





P.O. Box 518 · 654 Avenue K, Calimesa, CA 92320 Tech 909/795-2505 · Fax 909/795-6351 · Orders 800/969-7528 e-mail: sales@skat-trak.com · WWW.Skat-trak.com

GENERAL COMPETITION RULES

17.1 GENERAL COMPETITION RULES

- 17.1.1 The following General Competition Rules will apply to all IJSBA- and IJSBA affiliate-sanctioned events and classes.
- 17.1.2 All IJSBA and IJSBA affiliate members and racing personnel—including but not limited to owners, mechanics, pit crew, sponsors and promoters—are deemed to be fully aware of all rules and will be expected to abide by them. Any entry is subject to inspection upon request of the Technical Director or Race Director.
- 17.1.3 *Riders Meeting:* A meeting for all event competitors will be held at an announced time and place. Attendance is mandatory. The meeting will be conducted by the Race Director or an official appointed by the Race Director. Descriptions of the course and flags will be made. Roll call may be used to verify attendance of riders at the meeting. Riders not attending or arriving late are subject to penalty.

17.2 RULE BOOK ADDENDA

- 17.2.1 Rule book addenda shall be announced via official bulletins that are faxed or mailed to IJSBA promoters and affiliates; announced at an IJSBA- or IJSBA affiliate-sanctioned event; published on the IJSBA's Web site or any combination of the above. It is the responsibility of the competitor to obtain this information.
- 17.2.2 Rule book addenda become legal and enforceable upon announcement.

17.3 TECHNICAL RULES

- 17.3.1 It is the responsibility of the rider to select a helmet and apparel that will provide appropriate protection. The International Jet Sports Boating Association does not endorse or guarantee specific products or manufacturers. Riders must rely on their own judgment in the selection of helmets and apparel for safety and durability.
- 17.3.2 At all IJSBA- and IJSBA affiliate-sanctioned events, a Personal Flotation Device (PFD) meeting local buoyancy requirements (typically U.S. Coast Guard Type I or Type III) that is in sound condition must be worn by all competitors at all times when on the water. Inflatable-type PFDs are not allowed.
- 17.3.3 At all IJSBA- and IJSBA affiliate-sanctioned events, a properly fitting, fullcoverage helmet with chin and mouth protection (face shield removed) meeting local requirements often including internationally recognized DOT and Snell Foundation motorized vehicle standards will be worn by all competitors at all times when on the water. Helmets with bolt-on chin guards are not allowed. Exception: Helmets are not required for freestyle competitors when engaged in freestyle competition. All helmets must be in sound condition and must be approved during pre-race technical inspection. No plastic, bicycle-type, BMX, or similarly designed headgear will be allowed.
- 17.3.4 Back protection, protective footwear and eye protection are recommended for all riders in all competition events.

- 17.3.5 The Race Director of an event shall have the authority to prohibit the use of any helmet or PFD, and/or other equipment which he or she may consider to be unsafe, to offer insufficient protection or to be otherwise considered inadequate.
- 17.3.6 No rider shall be allowed to compete in any event if it is determined by an official that he/she is under the influence of alcohol or drugs. It is forbidden for anyone to consume any alcoholic beverages during an event in the pit area or any other portion of the premises under official control.
- 17.3.7 The Race Director shall have the authority to deny participation to any rider if, in his/her opinion, the rider may be a hazard to spectators, participants or themselves. Written approval of a doctor may be required.
- 17.3.8 Any competitor exhibiting dangerous or un-sportsmanlike conduct at any time during a sanctioned event may be penalized.
- 17.3.9 All watercraft, with the exception of those used during freestyle competition, must have a properly working, lanyard-type engine stop switch installed. Modifications made to the lanyard-type engine stop switch, using tape, wire or any other material whatsoever, that can be removed by the rider or pit crew during or immediately following a competition event are not allowed. Engines may idle at any time, provided that the lanyard is connected.
- 17.3.10 All watercraft must pass a pre-race technical inspection. The Race Director may remove any watercraft from competition that does not meet IJSBA technical requirements.
- 17.3.11 Equipment that is damaged, broken or lost during a race is not necessarily grounds for penalty unless an infraction is determined during that race.
- 17.3.12 All watercraft must run a permanently affixed nose bumper approved by the IJSBA. If plastic or metal hull supports are used, all edges must be smooth as not to create a hazard.
- 17.3.13 The Race Director shall have authority to stop or conclude any event(s) he/ she deems necessary to ensure the safety of participants, spectators and/ or officials, or because of technical problems.
- 17.3.14 The maximum number of riders per vehicle is one. No two-up or tandem racing allowed.

17.4 FLAG RULES

- 17.4.1 The following flag rules apply generally to all forms of IJSBA competition, including closed course, drag and endurance racing, slalom and freestyle competition and other special events.
- 17.4.2 *Green Flag:* Signifies the start of the race or the course is clear and the race is in progress.
- 17.4.3 **Yellow Flag:** Warns of hazard on the course. After the yellow flag is displayed, riders should continue with caution and be aware of hazards; however, they are allowed to continue racing in a responsible manner. Competitors may be penalized if they continue to race in an improper manner.

- 17.4.4 **Red Flag:** Signifies the event will stop immediately regardless of position of machines on the course. The red flag will be used if, in the opinion of the Race Director, the race course has become hazardous. Riders must return to the starting line using extreme caution.
- 17.4.5 **Black Flag:** Signifies the rider must leave the course immediately and report to the Race Director. This does not necessarily mean an additional penalty will be given; however, failure to obey the black flag may result in additional penalties.
- 17.4.6 **Blue Flag w/Diagonal Yellow Stripe:** Signals that one rider is being overtaken and lapped by another. Competitor(s) must make way for the overtaking rider(s) to pass safely. Riders not yielding may be penalized.
- 17.4.7 **Crossed Checkered and White Flags:** Signifies the halfway point of the race has been reached. For events with an odd number of scheduled laps, the halfway point will be rounded up (e.g., in a 15-lap race, the halfway point is decided when the lead rider passes the finish line after 8 laps have been completed).
- 17.4.8 *White Flag:* Signifies that riders have started the last lap.
- 17.4.9 **Checkered Flag:** Signifies the completion of the race or event. As a rider passes the checkered flag, he/she has completed the last lap of the race. Riders must return to the pit area in a cautious and responsible manner. Racers may first be required to report to post-race technical inspection.

17.5 GENERAL REGULATIONS

- 17.5.1 **Riding Tune-Up Area:** If location/space allows, an area will be designated as a "Riding Tune-Up Area." All riders must wear approved PFD and helmet while tuning/testing watercraft in this area, and must ride in a safe manner.
- 17.5.2 *Riding on the Course:* Riding will not be allowed on the race course at any time without permission from the Race Director.
- 17.5.3 **Reckless/Dangerous Riding:** Any reckless or dangerous riding, unnecessary bumping, crowding, chopping, blocking, deliberate striking or breaking of a course marker buoy, or unsportsmanlike conduct on the course or off, may result in the rider being penalized. In the case of a team effort, the complete team may be penalized at the discretion of the Race Director.
- 17.5.4 **Blocking:** The deliberate blocking of a faster machine is cause for penalty at the discretion of the Race Director.
- 17.5.5 **Spin Outs:** It is expressly forbidden to ride in a direction opposite of that in which the event is being run. A rider whose boat has spun out is permitted to turn around to continue the event provided such action is taken only when the course is clear. The rider must give right of way to other racers on the course. Riders going in the wrong direction may be penalized.
- 17.5.6 **Obstruction:** If for any reason a rider is forced to stop on or near the course during an event, it is the rider's first duty to remove his or her boat from the course in a safe manner so as not to endanger or obstruct other riders.

- 17.5.7 **Passing:** A rider must always be prepared for another rider to pass and must therefore be aware of other riders approaching from behind. The overtaking rider must consider the safest route to pass and must do so without forcing the overtaken rider to suddenly alter course.
- 17.5.8 *Lapping:* A rider being lapped must move over, but can continue racing.
- 17.5.9 *Hand Signals:* A rider who has spun out, fallen or stalled must raise one or both hands overhead to indicate that he or she is not injured. Re-entry into the course must be done in a safe and careful manner with the right-of-way given to oncoming riders.
- 17.5.10 **On-course assistance:** Racers may not receive any on-course assistance from anyone other than course officials. If mechanical or other assistance is needed, the rider must safely pull completely off of the course. A rider receiving on-course assistance may be penalized one lap. Riders entering the course in an unsafe manner may be penalized. The decision by the Race Director will be final.

17.6 PIT REGULATIONS

- 17.6.1 **Support Vehicles:** No motorized rider-support vehicles (e.g., minicycle, motorcycle or ATV) will be allowed in the pit area unless authorized as an official vehicle by the Race Director. Support vehicles must not be ridden in excess of 5 mph in the pit area. Helmets may be required.
- 17.6.2 *Misuse of Pit Passes:* Improper usage of pit passes will be grounds for discipline.
- 17.6.3 *Fuel Containers:* All fuel containers must be 1) red in color; 2) marked "Flammable" or "Gasoline" with 7.5cm (3 in.) tall letters; and 3) be placed in a safe area at least 4.6m (15 ft.) from any open flame.
- 17.6.4 **Inspection of Fuel Containers:** Fuel containers will be subject to inspection by and approval of the Race Director and local fire marshal. Local regulations in some countries and/or areas of countries allow only metal containers.
- 17.6.5 *Fire Extinguishers:* At least one dry chemical fire extinguisher must be carried by each participant/crew and readily accessible in his/her respective pit areas.
- 17.6.6 *Fuel Disposal:* Any entrant disposing of fuels or lubricants in the pit area or on the race course by pouring or spilling such fuels or lubricants is subject to penalty.

17.7 REGISTRATION/ENTRY RULES

- 17.7.1 Any class except freestyle can be eliminated when there are less than five entries at the close of registration (freestyle requires just one entry). In the event of minimum entries per class, classes may be combined to create an event. Riders will be scored separately and trophies/prize money may be paid at the option of the promoter agreement with the IJSBA or IJSBA affiliate.
- 17.7.2 No refunds of entry or other fees will be made at sanctioned events after competition has begun unless the event is officially canceled or rescheduled by a ruling of the Race Director or at the discretion of the Race Director, after which time, fees will be returned.

- 17.7.3 Entry fees will be regulated by the IJSBA and/or IJSBA affiliate.
- 17.7.4 A rider may enter as many classes as he/she wishes. However, only specified classes may count toward overall championships.
- 17.7.5 Veterans-, Masters- and Women-class competitors may additionally compete in Novice, Expert and Pro classes of their ranking (i.e., a Novice Woman Ski rider may compete in Novice Ski but not Expert Ski).
- 17.7.6 Novice-, Expert- or Pro-ranked riders may not compete in another ranking within the same division (i.e., Novice Ski riders may compete only in Novice Ski classes).
- 17.7.7 If a rider has questions regarding class determination, it is his/her responsibility to check with the proper official for clarification.
- 17.7.8 Gate admission fees for rider and crew members will be regulated by the promoter.
- 17.7.9 The schedule of events will be regulated by the promoter.
- 17.7.10 No rider, entrant or mechanic shall enter and/or sign the waiver and release with an assumed and/or fictitious name or give inaccurate information (e.g., age, date of birth, etc.).

17.8 SCORING

- 17.8.1 The portion of the course from the starting line to the scoring/flag tower shall be considered as the first lap.
- 17.8.2 The checkered flag will be shown to the lead rider, indicating the completion of the race. All penalties, other than those requiring a black flag, will be assessed after the completion of the race.

17.9 PRIZES AND AWARDS

- 17.9.1 All prizes, awards and paybacks shall be presented to the official winners or their appointed representatives at the close of the event day unless another time and place for awards is specifically advertised.
- 17.9.2 Riders will not be required to attend award banquets or ceremonies to receive prizes and awards, although they are encouraged to attend as a courtesy to the promoter and/or sponsors.
- 17.9.3 The promoter payback at IJSBA- and IJSBA affiliate-sanctioned cash purse events will be as advertised for that event, or as stated in bulletins, or as announced at an official riders meeting at the event.

17.10 RIDER POINT SYSTEM

- 17.10.1 The official rider point system will be in effect for all IJSBA- and IJSBA affiliate-sanctioned events.
- 17.10.2 Points are awarded for final event positions only. No points are awarded in heats, last chance qualifiers (LCQs), semi-finals or exhibition events. Points will not be awarded to riders who are disqualified or have not been scored on at least one lap in a final event. Exceptions may be granted for national and world championship events with IJSBA approval.
- 17.10.3 Freestyle points count towards a freestyle points championship only. Freestyle events require one entry to receive full points.

- 17.10.4 The points tiebreaker for individual class championships based on closed course, slalom or other points earned (e.g., Novice Ski Limited Slalom, Expert Sport Limited Closed Course, Pro Freestyle, etc.) is the greater number of first-place finishes in the class. If still tied, the rider with the greater number of second-place finishes will receive the higher ranking, and so on. If still tied, the rider with the better finish in the final event of the championship series will receive the higher ranking.
- 17.10.5 The points tiebreaker for a combined overall championship based on points earned in closed course added with points earned in slalom and/or other events (e.g., Expert Ski Open Closed Course points combined with Expert Ski Open Slalom points, etc.) is the rider with the greater number of closed-course points. If still tied, the rider with the greater number of first place closed-course finishes will receive the higher ranking. If still tied, the rider with the greater number of higher ranking, and so on. If still tied, the rider with the better finish in the final closed-course event of the championship series will receive the higher ranking.
- 17.10.6 When the number of entries is less than or equal to the maximum number of watercraft allowed on the starting line the moto scoring system may be used. The Moto Scoring system uses the combined results of two separate races to mathematically determine the overall finishing order.
- 17.10.7 **Moto Scoring:** Overall results are determined by adding the finishing positions from each of two motos together. The rider with the lowest sum will receive the higher ranking. In case of a tie, the rider with the better finish in the second moto will receive the higher ranking. A DNR (did not race) in one of the two motos will be scored as the number of riders entered in the class plus two.
- 17.10.10 The IJSBA official Closed Course point system is as follows:

Pos.	Points	Pos.	Points	Pos.	Points
1	60	8	30	15	14
2	53	9	27	16	12
3	48	10	24	17	10
4	43	11	22	18	8
5	39	12	20	19	6
6	36	13	18	20	4
7	33	14	16		

17.10.11 The IJSBA official Slalom/Freestyle point system is as follows:

Pos.	Points	Pos.	Points	Pos.	Points
1	20	8	9	15	2
2	17	9	8	16	1
3	15	10	7	17	1
4	13	11	6	18	1
5	12	12	5	19	1
6	11	13	4	20	1
7	10	14	3		

17.10.12 The IJSBA	official Endurance	Offshore point	system is as follows:
--------------------	--------------------	----------------	-----------------------

Pos. Points	Pos. Points	Pos. Points
1 400	8 340	15 312
2 380	9 336	16 308
3 368	10 332	17 304
4 360	11 328	18 300
5 352	12 324	19 296
6 348	13 320	20 292
7 344	14 316	21 290

Continue in increments of two until 40th position where points continue in increments of one.

17.11 BOAT NUMBERING SYSTEM

17.11.1 Racing numbers and backgrounds will be color-coordinated according to rider classification.

Class	Number	Background
Novice	Black	Orange (PMS 021)
Expert	Black	Yellow (PMS Process Yellow)
Pro	Black	White

- 17.11.2 Racing number backgrounds must be clearly located on the hull in the positions indicated (see the Appendix) for each model. Be careful not to place them in a location that will obscure them from the scorers (i.e., they should not be placed in the footwell or on horizontal surfaces). Only numbers can appear on the background.
- 17.11.3 Race number backgrounds size minimums are as follows:

Racing No. Background Size

- 17.11.4 Racing numbers must be a minimum of 18cm (7 in.) high and spaced at least 13mm (0.50 in.) apart. Standard block-type numbers without shading or outlining must be used. It is the rider's responsibility to ensure that the numbers are easy to read.
- 17.11.5 If two or more riders using the same number enter the same class at the same event, all but one will be required to add a temporary letter suffix (e.g., "101A," "101H," etc.).
- 17.11.6 All riders competing outside their home country must display the national code for their home country in front of their racing number (e.g., "F1" for France, no. 1). Letters must be a minimum of 15.25cm (6 in.) in height and must be the same color as the racing numbers. (Refer to Section 23.1, page 83, for listing of IJSBA Affiliate National Codes.)
- 17.11.7 At world championship events, Expert and Pro racers who earn an overall World Championship title may run the "1" plate for the following year in the class in which it was earned (e.g., an Expert Ski Limited Closed-Course World Champion may run a "1" in that closed-course class only). The World

Championship number "1" must be displayed on the boat with a white number on a black background with minimum sizes as noted in 17.9.3 and 17.9.4. No other world championship number may be used.

17.12 RACE DIRECTOR AUTHORITY

- 17.12.1 The Race Director shall be responsible for the conduct of the race. He or she will be responsible for the design of the racing courses and adjacent event facilities as they pertain to that event.
- 17.12.2 The Race Director shall have the authority to discipline riders, owners, sponsors and/or pit crew for violation of rules. Such discipline will be limited to disqualification, exclusion from an event, and/or ejection from the race site.
- 17.12.3 Disciplinary action by the Race Director other than a disqualification, exclusion or ejection will be under provisions established by the IJSBA. The Race Director will advise the IJSBA or local IJSBA affiliate of the infraction(s) and disciplinary actions taken. The member will then be officially advised by mail of action and/or discipline by the IJSBA.
- 17.12.4 Official results shall be approved by the assigned Race Director and a copy of those results will be submitted by the promoter to the IJSBA international headquarters or local IJSBA affiliate office within seven days following the event.
- 17.12.5 The Race Director may cancel any race or event for reasons of potential hazard to competitors and/or spectators at his/her own discretion. In such cases, the promoter shall determine awards, if any. The Race Director may shorten a race or event for any reason, but must give riders notice in advance.
- 17.12.6 The Race Director may cancel or stop any race or event in progress if a potential hazard to competitors and/or spectators exists, or the method of scoring has been faulted. In such case, the rules governing restarts will apply (refer to Section 12.3, pages 51-52). Events that are stopped with more than half of the scheduled laps completed will be considered as finished. For events with an odd number of scheduled laps, the halfway point will be rounded up (e.g., in a 15-lap race, the halfway point is decided when the lead rider passes the finish line after 8 laps have been completed).
- 17.12.7 Unresolved racing violations will be sent to the IJSBA or IJSBA affiliate office for resolution.
- 17.12.8 The Race Director may judge the method of lap counting and the mechanical integrity of all technical and timing equipment, and may ask the Technical Director to conduct technical inspections at any time.
- 17.12.9 Race officials (including but not limited to the Race Director and/or event Promoter) may not compete in sanctioned events at which they are officiating or promoting.

RULES INFRACTIONS

18.1 RULES INFRACTIONS

18.1.1 All infractions of the rules reported by an official pertaining to a watercraft or rider, whether or not resulting in disqualification, may be noted in the involved rider's IJSBA membership file.

18.2 EJECTION FROM RACE SITE

18.2.1 Race officials have the right to eject any person(s) from the pit, race course or event grounds.

18.3 DISCIPLINE/RIDER CONDUCT

- 18.3.1 The Race Director may disqualify, exclude or eject the rider, owners, sponsors or pit crew member(s) for any of the following violations:
 - Vulgarity, offensive language or unsportsman-like actions directed towards officials, spectators or other participants.
 - Failure to abide by the race rules of the IJSBA (not including equipment violations).
 - Failure to comply with watercraft requirements.
 - Writing check(s) not backed by sufficient funds.
 - · Pit crew non-compliance with regulations.
 - Use of intoxicating beverages and/or drugs.
 - Unwillingness to accept an official's decision.
 - · Verbal or physical abuse of any official.
 - Participation in an event without holding a valid membership card or involvement in the use of another member's card.
 - Providing inaccurate or false information to officials or on any official IJSBA document.
- 18.3.2 In addition to exclusion or ejection from an event, the IJSBA may determine further penalties including a fine, loss of points, suspension, disqualification or any combination of the above.
- 18.3.3 The decision to discipline a rider for any of these violations is not appealable.

18.4 RIDER/PIT CREW LIABILITY

18.4.1 The rider and his/her pit crew members, in signing the entry/release, elect to use the course of the event at their own risk, acknowledge that there may be both known and unknown risks, and thereby release the sanctioning organization and principals together with their heirs, assigns, officers, representatives, agents, employees, and members, sponsoring organization and owners of properties on which sanctioned events are to be held from all liability from injury to person, property, and/or reputation that may be received by said entrant and from all claims of said injuries to the parties listed above growing out of, or resulting from the event contemplated under the entry form, or caused by any construction or condition of the course over which the event is held.

Rules Infractions

18.5 RIDER RESPONSIBILITY

- 18.5.1 The registered rider is responsible for the condition of his/her watercraft as stated in the IJSBA Official Competition Rule Book. Any rider, whether sponsored by or riding a watercraft owned by someone other than the registered rider, will still be held responsible for complying with all IJSBA rules. If the rider and/or watercraft is found to be in violation of a class rule, the rider will receive the penalty.
- 18.5.2 The rider is responsible for and may be disciplined for his/her personal conduct as well as the conduct of people in his/her party, including but not limited to owners, sponsors, pit crew and family members.

18.6 PENALTIES/TECHNICAL INFRACTIONS

- 18.6.1 Any rider found to be competing on a boat that is determined to be illegal in a particular class, following inspection by the Technical Director, will be disqualified and will not be permitted to compete in any remaining qualifiers or final events for the class and will receive no points. If moto scoring is being used, the rider will be disqualified from the class and will not be allowed to compete in the second moto. The rider may also receive a suspension of up to 30 days from IJSBA or IJSBA-affiliate events, may lose all accumulated series points to that date in that class, and/or may be fined up to \$250 U.S. or the equivalent in local currency.
- 18.6.2 Should there be a second technical infraction, the rider may receive a suspension up to 60 days and a maximum fine up to \$500 U.S. or the equivalent in local currency.
- 18.6.3 Should a third technical infraction occur, it will result in automatic suspension from competition for the remainder of the calendar year and a maximum fine up to \$1,000 U.S. or the equivalent in local currency.
- 18.6.4 All fines must be paid by cashier's check or money order to the IJSBA or IJSBA-affiliate organization before the rider will be allowed to compete in any IJSBA-sanctioned event.

18.7 ENFORCEMENT

18.7.1 Any penalty imposed for violation of the rules and regulations of the IJSBA by any member must be honored by all other members including but not limited to IJSBA and IJSBA-affiliate promoters.

TECHNICAL PROCEDURES

19.1 PRE-RACE TECHNICAL INSPECTION

- 19.1.1 Any entry is subject to inspection upon request by the Race Director or Technical Director. It is the responsibility of the rider to submit his/her equipment to the Technical Director on the proper day for technical inspection.
- 19.1.2 Pre-race technical inspections are mandatory at all races. *Pre-race inspections do not certify that the watercraft is qualified or constituted as legal for class participation. Post-race technical inspections determine machine qualification.* All rider equipment, including helmet and personal flotation device, must be available for technical inspection.
- 19.1.3 The Technical Director may prohibit any watercraft that does not meet IJSBA technical requirements.
- 19.1.4 The Technical Director shall be able to provide accurate watercraft specifications and have the supplies and equipment necessary to verify compliance with IJSBA rules and regulations.
- 19.1.5 All watercraft intended to be raced in an IJSBA- or IJSBA affiliate-sanctioned competition event must be checked for rules compliance. Some, but not necessarily all, items to be inspected are:

Rider protective equipment:

- Approved personal flotation device (PFD);
- Approved full-coverage helmet.

Hull and deck:

- Overall inspection for cracks or damage;
- Inspect the hull for protruding objects that could be hazardous;
- No illegal skegs, fins or rudders on hull bottom, intake grate or pump plate;
- Inspect condition of bumpers;
- · Inspect numbers and background for compliance and legibility;
- Make sure Hull Identification Number (HIN) is displayed;
- Make sure approved sponsor decals are affixed (if requested);
- Make sure flexible bow loop is affixed;
- Tow hooks which extend beyond the plane of the hull are removed.

Handlepole/handlebar:

- · Check condition of handlepole and hinge mechanism;
- · Check steering mechanism for proper adjustment;
- Check that the throttle lever works freely;
- Check that grips are secure;
- Check that the lanyard stop switch is functioning properly and the lanyard is in good condition.

Engine compartment:

- Hose clamps must be secure;
- · Battery must fit into battery box and straps must be secure;
- Gas tank must be secure;
- Fuel pickup and fuel level sender must be secure;
- U.S. Coast Guard, SAE-J1928 or UL-1111 flame arrester securely installed;
- Carburetor/fuel system must not leak and all fuel hoses must be secure.
- 19.1.6 All watercraft may be required to meet respective local boating laws (i.e., current registration displayed on craft, fire extinguisher on board, etc.).
- 19.1.7 **Sponsor Decals:** IJSBA and/or IJSBA affiliate decals and event sponsor decals must be displayed on vehicles and/or rider apparel at each event as determined by the Race Director.
- 19.1.8 *Hull Number:* All watercraft must display the hull identification number (HIN) assigned at the time of manufacture. IJSBA may also assign an IJSBA identification number.

19.2 POST-RACE TECHNICAL INSPECTION

- 19.2.1 Suggested technical inspection procedure is to impound and inspect the first three watercraft in each class. However, the actual number of watercraft to be impounded will be decided by the Race Director or Technical Director.
- 19.2.2 The Technical Director reserves the right to inspect any part of any personal watercraft entered in any class. A rider refusing to cooperate with technical inspection procedures may be penalized by the Race Director.
- 19.2.3 Inspected boats will not be disassembled or reassembled by the inspection group.
- 19.2.4 Rider and/or rider's mechanic will perform teardown to the point required by the Technical Director.
- 19.2.5 Rider and/or rider's mechanic will be the only people allowed with the boat in the inspection area. A rider may have another mechanic take his place.
- 19.2.6 The IJSBA or IJSBA affiliate assumes no responsibility for impounded watercraft.
- 19.2.7 All parts deemed illegal are to remain in the impound area for 30 minutes after notice of disqualification.

19.3 SEALS/INSPECTION DECALS

19.3.1 Riders will allow seals or decals to be affixed on the engine and/or body of their watercraft. To change a seal, mutilate, try to break or re-use it during the event where it is installed without consent of the Race Director, could result in the responsible rider or team being disciplined by the IJSBA or IJSBA affiliate. Accidental breakage or removal of the seal must be reported to the Race Director immediately.

19.4 FUEL TESTS

- 19.4.1 A rider's statements as to the contents of his/her personal watercraft's fuel system will be binding. Gasoline is tested and certified at IJSBA or IJSBAaffiliate events through the application of various chemical analyzes as considered appropriate by Fuel Check personnel. Gasoline may be checked before and/or after use in competition.
- 19.4.2 Aerosol cans of ether will be allowed for starting purposes.
- 19.4.3 Engine fuel must consist of unleaded gasoline only. "Gasoline," for the purpose of this Rule Book, is defined as a mixture of hydrocarbons and oxygen bearing compounds with the following clarifications:
 - 1) Oxygen content must not increase the specific energy of the gasoline.
 - 2) Oxygen content must not exceed 3.7% by weight.
 - Oxygen content must have been blended in by the refiner or the fuel manufacturer.
 - 4) Specific gravity must be between: .715 .770 at 60°F (15°C).
 - The only allowable oxygenates are ethers and alcohols. Epoxides (e.g., propylene oxide) will not be considered ethers. Nitrogen-bearing compounds are not allowed.

NOTE: Most commercially-produced unleaded fuels and oils will meet these criteria. However some may contain additional additives which do not to meet these criteria.

19.5 SOUND TESTING PROCEDURE

- 19.5.1 Announcement may be made by the Race Director at the riders meeting as to sound testing procedure (i.e., how, where and when notice of non-compliance will be given to riders).
- 19.5.2 Boats will be tested during practice sessions. Any boat exceeding the IJSBA sound limit of 86 dB(a) at 22.86m (75 ft.) will be listed on the pit board or the rider will be notified by verbal warning.
- 19.5.3 The Technical Director will post a list of offending boats as soon as possible after the practice session to give riders an opportunity to make the necessary adjustments before the next race. It is a rider's responsibility to ensure that his/her boat meets the IJSBA sound-level requirement at all times.
- 19.5.4 Boats given notice during practice will be re-tested during the next race. If the boat still exceeds the sound level, the rider will be assessed a one-lap penalty. Any other boats (even those that were not given notice after practice) that now exceed the sound level will also be given a one-lap penalty.
- 19.5.5 Boats that have been given a one-lap penalty will be re-tested during the next race. If the boat still exceeds the sound level, the rider may be disqualified. Any other boats that now exceed the sound level (even though no prior notice was given) will be given a one-lap penalty.
- 19.5.6 Exception to 19.5.4 and 19.5.5: A boat that is damaged during a race (such as a broken component) and suddenly emits a sound level exceeding the legal level may not be penalized. However, if the same boat is raced in any subsequent races, it must comply with the sound level requirement.

PROTESTS AND APPEALS

20.1 PROTESTS

- 20.1.1 A race official's decision based upon the exercise of his/her judgment may not be protested under any circumstances.
- 20.1.2 Riders only will have discussion with the Race Director about riding complaints or other infractions unless otherwise requested by Race Director. Riders may approach the Race Director before the day's events, between events, after an event, or at the discretion of the Race Director.

20.2 PROTEST PROCEDURE/EQUIPMENT VIOLATIONS

- 20.2.1 Protests must be filed in writing no later than 30 minutes after the official results have been posted.
- 20.2.2 A separate protest must be filed for each suspected infraction specifying a violation within the following categories:
 - · Drive system
 - Electrical system
 - Engine
 - Exhaust system
 - Fuel/carburetion system
 - Hull
- 20.2.3 When a protest is made against a boat's eligibility, the protester must post with the Race Director a minimum cash bond of \$150 U.S. to cover the costs of any disassembly, inspection and assembly required, regardless if disassembly is required. Bonds may be tailored to reflect the extent of the work involved in disassembly and reassembly for the inspection. Bond Fees above \$150 must be announced at the Riders Meeting or published, in writing, prior to the event. No Bond may exceed \$500 US.
- 20.2.4 If the watercraft is found legal and the protest is disallowed, the cash bond will be awarded to the protested rider.
- 20.2.5 If the watercraft is found in violation of the rules and the protest is allowed, the cash bond will be returned to the protester and the protested party is subject to penalty assessed by the Race Director and/or IJSBA.
- 20.2.6 If an entrant or rider does not allow inspection under these terms, he/she will be disqualified by the Race Director immediately.
- 20.2.7 The Race Director or Technical Director may, at his/her discretion, consult any person to receive information or technical advice. Protested rider may be present during such inquiry but shall have no right to cross-examine or argue with a witness.
- 20.2.8 Only a rider taking part in the competition and entered in the same class may protest another rider in that class.
- 20.2.9 All parts deemed illegal may be held by the IJSBA pending final decision.
- 20.2.10 If a protest is judged to have been filed with malicious or spiteful intent or otherwise in bad faith, the protester may be found guilty of violating protest rules and may be penalized.

20.2.11 Official IJSBA videotape as recognized by the Race Director may be used by officials to make or overrule a decision.

20.3 APPEALS

- 20.3.1 The rider aggrieved by a decision involving an equipment violation may appeal to the IJSBA.
- 20.3.2 An appeal or intent to appeal must be filed in writing within one hour of disqualification and must be accompanied by a fee of \$100 U.S. or the equivalent in local currency.
- 20.3.3 Rulings of the IJSBA will be made within reasonable time from the date the appeal was filed.
- 20.3.4 The IJSBA and/or IJSBA affiliate shall have the right to publish any judgments concerning protests or appeals and to use the names of parties involved. These persons shall have no right to act against the IJSBA and/or IJSBA affiliate, the Race Director or whomever publishes the judgment.
- 20.3.5 Anyone belonging to or under the jurisdiction of the IJSBA who shall take into the courts any controversy arising from the interpretation or application of these rules and regulations shall be liable to disqualification, suspension and/or expulsion.



Glossary of Terms

GLOSSARY OF TERMS

21.1	GLOSSARY OF TERMS
Aftermarket Part	A part replacing or used in addition to the original equipment part. Aftermarket parts are not limited to providing the same function as their original equipment counterparts.
Ambulance	A properly licensed and equipped emergency vehicle normally noted as a rescue vehicle, or ambulance. Said vehicle will be fully equipped to include basic life support equipment and personnel trained in the use of said equipment.
Bond Flange	The bond flange is the overlapping/mating section where the deck (upper) and the hull (lower) portions are joined.
Buoy	A floating object anchored in the water to mark the course.
Competitor	An IJSBA member who has fulfilled all necessary requirements to participate in an event and who is present at the event for the purpose of participating (also <i>Entrant, Participant, Racer, Rider</i>).
Course Marshal	Helps the Race Director control the race and assists stopped riders on the course. Most often is positioned on the course perimeter riding a watercraft.
Deck	The upper structural body of the watercraft located above (and including) the upper bond flange.
DNR	Did Not Race. Official classification of an entered rider who does not start an event or, in closed course competition, does not complete one lap.
Entrant	See Competitor.
Fuel Injection	Any system that does not depend solely on the engine's vacuum to induct fuel into the engine will be considered a fuel-injection system.
Homologation	The process of officially approving or allowing a component or watercraft to compete in IJSBA events.
HIN	Hull Identification Number. A unique serial number generated by the manufacturer and affixed to each watercraft.
Hull	The lower structural body of the watercraft located below (and including) the lower bond flange.
LCQ	Last Chance Qualifier. A closed course event that generally follows a heat race and is used to complete the starting field for a final or semi-final.
Member	A person belonging to the IJSBA holding a valid and proper member card.
Moto Scoring	One of two races where the finishing positions are used to award championship or series points under the Moto Scoring system (see sections 17.8, pg. 65).

Glossary of Terms

Official	A person who supervises a race.
Original Equipment	Parts that were installed on each model of watercraft at the time of manufacture (a.k.a. \textit{OE} or \textit{OEM} .)
Owner	The person named on the title of the watercraft.
Participant	See Competitor.
Participate	To willfully take part in a race (also Compete).
PFD	Personal Flotation Device. A device used to keep riders afloat, required in all forms of IJSBA activity.
Pit Area	Area used by riders and mechanics to make machine repairs, refuel and make rider changes.
Pit Crew	A rider support person or group that prepares and maintains the watercraft.
Promoter	A person or body controlling a facility where events are organized, promoted and staged.
PWC	Personal Watercraft: A vessel which uses an inboard motor powering a water jet pump as its primary source of motive power. Designed to be operated by a person sitting, standing or kneeling on the vessel rather than inside it.
Race	A contest of skill for watercraft and riders.
Race Director	The person responsible for the conduct of the race.
Racer	See Competitor.
Replacement Part	A non-original equipment part used to replace an original equipment part. Replacement parts are limited to providing only the dimensions, performance and function that their OEM counterparts provide.
Replica	A copy or duplicate.
Rider	See Competitor.
Riding Platform	The part of the watercraft where the rider stands or sits.
Sanction	An agreement between the IJSBA or IJSBA affiliate and a promoter that stipulates specific criteria to be met by the promoter in exchange for IJSBA support.
Sponson	A special surface which may be attached to the hull sides or transom for stability.
	<i>Ski Division Only:</i> Sponsons may be attached to the hull sides, transom or inside the bond flange portion of the hull.
Sponsor	A person or group that provides support to a rider, promoter or association usually in exchange for promotion.
Staging Area	The place near the starting line where watercraft and riders wait for their scheduled race.
Starter	The person who officially gives the signal to begin the race.
Starting Line	A straight boundary, either real or imaginary, that denotes the beginning point of the race.

Glossary of Terms

Strake	A well-defined angle (longitudinal step) usually added to deep- ${\sf V}$ hulls for a softer ride at high speeds.
Technical Director	The person who checks all competing watercraft for rules compliance and eligibility.
Trim Tab	An extension of the hull's planing surface. Trim tabs are attached to the transom of the hull and may be angled up or down to alter the running angle of the craft.





EXPLODED VIEW

PORT CHAMFERING



PUMP COVER PLATE EXTENSION





at the widest point.









SLALOM COURSE LAYOUT

SPECIAL PRODUCTION HOMOLOGATION

An OEM Manufacturer in good standing may homologate less than 100 identically produced units that will be eligible only for a controlled Special Production Stock Class* and the Modified/GP classes. Only units approved by the IJSBA are eligible to be homologated in the Special Production or GP classes.

For a Manufacturer to produce less than 100 identically manufactured units of a model and qualify for current-year IJSBA and- IJSBA affiliate sanctioned competition the manufacturer must adhere to the following criteria for all models produced in quantities below 100:

- The manufacturer must produce a minimum of 25 identically manufactured units of a model. Should the manufacturer sell, or dispose of all units before July 1st then the manufacturer must produce and additional 25 units, identical to the initial 25, and have those units available by September 2nd.
- 2) The manufacturer shall declare, in the initial application for homologation, that the model will have production numbers less than 100.
- 3) The manufacturer shall inform and update the IJSBA as to the status, location, and/or purchaser of each unit produced within 15 days of the units being released for distribution and shall update the IJSBA with this information for 180 days or through the end of the calendar year, whichever is greater..
- 4) The manufacturer must allow the IJSBA, upon request, to broker the sale of up to seven of the total model units produced in order to ensure distribution to IJSBA competition members.
- 5) The IJSBA may place restrictions on the model and withhold or withdraw the homologation of any component or watercraft for reasons deemed to be in the best interest of the sport.
- 6) If the unit is not available for sale or not legal for sale in a region then that affiliate may chose not to offer the Special Production Class.
- 7) The manufacturer shall transport an IJSBA official to inspect the assembly line of the unit according to the terms listed in the homologation application.
- 8) Failure to comply with all requirements in this section shall result in the immediate suspension of the unit in sanctioned competition.

The manufacturer must provide the IJSBA with a current service manual, parts catalog, owners manual and additional technical information for each model considered for homologation.

The manufacturer must provide the IJSBA, upon request, a production model watercraft and separate components for examination and testing for each model being considered for homologation. Items will be returned after completion of examination and testing.

- Mid-year production changes to a homologated model must be approved by the IJSBA. Samples of new components, copies of related service bulletins and customer notification letters must be submitted before approval will be granted. Changes and updates on all affected units must be made available at no cost to the customer, parts and labor included.
- * If Lites Classes are offered then the competition organizer may merge the non-Lites Stock Classes with the Special Production Class. However, the name of the class must retain the name Special Production.

Appendix—Spec Classes Addendum

SPEC CLASSES ADDENDUM

The IJSBA is pleased to offer information on Spec Class Racing. Spec Class in Personal Watercraft is a grass roots created category of racing which is intended to create a more equal level of performance on the race course irrespective of whatever brand watercraft a competitor chooses to utilize. Additional goals of this type of racing include cost savings and keeping some outdated models in the forefront of competitive racing. Spec Class Racing can be applied to the Runabout, Ski, and Sport divisions. The IJSBA encourages participation in these classes and requests feedback so that the evolution of these endeavors can continue to meet the stated goals.

Runabout Stock Spec

There has been no Stock Spec racing for Runabout watercraft at the time of this publication. The IJSBA encourages promoters and affiliates to explore opportunities for new ways to extend the life of popular older brand Runabouts without overburdening the event schedules with too many additional classes. A beginning suggestion is to group former classes: Runabout 800 Superstock, Runabout 1300 Limited, and Four Stroke Stock classes together on the same line with the smaller displacements closer to the pole position.

Ski Spec

The following condensed set of Ski Spec Rules comes from the American Power Boat Association (APBA Technical Rule 24) where this category of racing is usually used in place of the Stock Classes. Promoters who offer this class should follow these rules specifically in order to ensure compatibility among competitors who want to freely use their craft between in differing associations. Appeals to the IJSBA of penalties for rule infractions under these Stock Spec rules will first be sent to the APBA for a ruling. A second appeal may be filed to IJSBA, however, the IJSBA will give a great deal of deference to the APBA's rulings.

SPEC SKI RULES (condensed version courtesy of APBA).

For the Stock Spec Ski class all watercraft may conform to the IJSBA Stock Ski class rules with the following exceptions and additions:

ALL MODELS

Reeds: Reed petals may be modified or aftermarket provided the original equipment reed stop and cage assembly are used.

Girdle Kits: Engine girdle systems like one made by Pro-Tec Performance are allowed.

HYDROSPACE ONLY

Boost Pressure: Four-Stroke turbocharged watercraft may race in all Stock Ski Spec classes provided the maximum boost pressure does not exceed 5psi.

Boost Regulator Value: All four-stroke turbocharged watercraft to run an approved boost regulator valve set at 5psi of boost.

Electronic Control Unit (ECU): The original electronic control unit must be OEM. Engine temperature sensors may not be disabled. The ECU may not be programmed to alter the original function of the OEM controls and or switches.

YAMAHA SUPERJET ONLY

A Yamaha SuperJet owner has two options:

Option A – Cylinder and Head – The racer can chose to run an OEM Yamaha 760 Cylinder and 760 Head. If the racer chooses to run an aftermarket cylinder and head all other modifications allowed in the Stock Spec Ski rules for a two-stroke watercraft are allowed. The cylinder bore must not exceed the 850 cc limit. The same allowed modifications would apply if a racer chose to run the Stock OEM 701 cylinder and head.

Option B – Run a Wet Pipe. The pipe must have been manufactured, designed, and sold as a wet pipe and continue to function as a wet pipe. Converting a dry pipe to a wet pipe is not allowed. If the racer chooses to run a Wet Pipe the following Stock Spec Ski modifications are NOT allowed:

- Ignition: The Ignition must remain OEM and can not be modified or altered in any way. RPM limiter function may not bypassed or eliminated. CDI unit must be OEM and can not be modified or aftermarket. Ignition timing may NOT be changed. Modifications to the original equipment ignition pickup mount are not allowed. Original equipment charging system must be used.
- Gaskets: The head and base gaskets must be OEM. Replacement gaskets that are the same thickness as OEM will be allowed.
- Bore: Bore must be stock, however, an overbore allowance of 1mm over stock will be allowed.

2008-2009 Yamaha SuperJet models: Carburetors may be machined to allow access to the circuit adjustment screws. Screws may be replaced or modified with tee handle type or other to provide easier adjustment. All fuel circuits must remain unchanged and may not be machined (i.e.: main circuit booster, low speed transfer, etc.). No other machining to carburetors is allowed.

KAWASAKI SXR ONLY

1) Kawasaki SXR may run a pump cone.

SPORT SPEC CLASS COMPETITION

The Sport Spec Class is intended to promote interest in personal watercraft competition with a limited number of modifications, and to enable individuals to become active competitors with a relatively modest investment. Watercraft that are eligible to compete in this class are: Kawasaki X2 (Pre 05); Kawasaki X2 (05-07); Polaris Hurricane; Sea Doo HX and Yamaha Waveblaster 701. Watercraft competing in this class must conform to the specifications which follow. These rules are specifically outlined for each individual model to promote close competition.

**All Sport Spec Class models are required to run 95 and BELOW octane unleaded fuel. This rule is mandatory to insure the cost of racing this class stays low.

**Kawasaki X2 (old style, pre 2005) are allowed to update to 750 or 800 Kawasaki engines and electronics and are to follow IJSBA Open class rules.

All watercraft must remain strictly stock, except where rules allow or require substitutions or modifications. Changes or modifications not listed here are not *permitted.* Some original equipment components may not comply with IJSBA rules.

Appendix—Spec Classes Addendum

NOTE: When rules permit or require equipment to be installed, replaced, altered or fabricated, it is the sole responsibility of the rider to select components, materials and/or fabricate the same so that the watercraft operates safely in competition.

Original equipment parts may be updated or backdated with original equipment parts of the same model. The part must be a bolt-on requiring no modifications to that part or any other parts except where rules allow substitutions or modifications. (Refer to Model Homologation listing on page 10-11.)

Sound level shall not exceed 86 dB(a) at 22.86m (75 ft.). See Section 19.5 (pg. 73). Engine fuel must consist of gasoline meeting the criteria defined in Section 19.4.3 (pg. 73).

HULL: All watercraft must have a flexible tow loop attached to the bow. The tow loop should be made of a flexible material (e.g., nylon strap, rope, etc.) so as not to create a hazard. Tow hooks which protrude beyond the plane of the hull must be removed. Hull and deck repairs may be made. However, these repairs must not alter the standard configuration by more than 2.00mm (0.08 in.).

Hull, bulkhead and deck may be internally reinforced. Fasteners may be installed through the hull, bulkhead and deck for the purposes of securing components to interior surfaces, provided a hazard is not created. Bulkhead may be cut for exhaust or electrical routing. Fire extinguisher, fuel petcock and choke holes may be filled or capped.

All watercraft may be equipped with a maximum of two sponsons. Original equipment sponsons may be modified, aftermarket, repositioned or removed. Overall length of each sponson shall not exceed 91.45cm (36.00 in.). Sponsons shall not protrude from the side of the hull by more than 100.00mm (3.94 in.) when measured in a level horizontal plane. The vertical channel created by the underside of the sponson shall not exceed 63.5mm (2.50 in.). No part of the sponsons shall extend downward below the point at which the side of the hull intersects the bottom surface of the hull by more than 63.5mm (2.50 in.). Aftermarket or modified sponsons must exceed 6mm (0.24 in.) in thickness. All leading edges must be radiused so as not to create a hazard. Sponsons may not be attached to the planing surfaces of the hull. Fins, rudders, skegs and other appendages that may create a hazard will not be allowed. (See diagrams in Appendix.)

The decision of the Technical Director and/or Race Director regarding modifications will be final. Any question regarding the legality of modifications should be directed to the IJSBA or IJSBA affiliate prior to use in competition. Intake grate may be modified or aftermarket. Intake grate is required and must be the full-length type with at least one bar running parallel to the drive shaft. Grates may not extend more than 12.00mm (0.47 in.) below the flat plane of the pump intake area of the hull. All leading edges must be radiused so as not to create a hazard.

Pump cover plate may be modified or aftermarket. An extension may be added to the rear of the plate but shall not exceed the width of the original equipment plate. Modified and aftermarket plates must not extend more than 100.0mm (3.94 in.) beyond the end of the original equipment plate. The extension must be connected to the radiused portion of the pump plate so as not to create a hazard. (See diagram in Appendix.) Fins, rudders, skegs and other appendages that may create a hazard will not be allowed. Pump shoe may be aftermarket but may not extend more than 12.00mm (0.47 in.) below the flat plane of the pump intake area of the hull.

Aftermarket fixed-position trim tabs may be used. Original equipment trim plates that are detachable from the hull may be removed or replaced when installing aftermarket trim tabs. Trim tabs cannot exceed the width of the planing surface or extend rearward more than 100.00mm (3.94 in.) beyond the end of the original planing surface. Manual or automatic trim tabs attached to the hull or ride plate are not allowed. All hull extensions mounted on the hull's transom will be considered as a trim tab. All edges must be radiused so as not to create a hazard. Fins, skegs, rudders and other appendages that may create a hazard are not allowed.

Replacement bumpers may be used provided a hazard is not created.

A soft, flexible water-spray deflector may be attached to the hull sides or to the bond flange provided a hazard is not created. No part of the deflector may extend beyond the perimeter of the original equipment bumper or side moldings as measured by a plumb line.

Battery box may be relocated.

Handlebar, throttle, throttle cable, and grips may be modified or aftermarket. Handlebar cover may be modified or removed.

Aftermarket switches and switch housings may be used. Steering shaft, steering shaft holder and handlebar holder may be aftermarket. The handlebar must be padded at the mounting bracket or, if it has a crossbar, the crossbar must be padded.

Aftermarket steering cables will be allowed.

Seat height may be changed and/or covered but must utilize OEM stock unmodified base. Padding and/or mat kits may be added and custom painting is allowed. The surface finish of any metal component outside the area above the hull bond flange may be polished, shot peened or painted.

Original bilge pump may be modified or disconnected. Aftermarket bilge draining systems that do not create a hazard are allowed.

Engine compartment foam may be removed, modified or aftermarket. Only floatation foam within the engine compartment may be removed. Only foam that can be removed without modification to any other part or parts, except where rules allow the parts to be modified, is allowed. The hull's inner liner or deck may not be cut or modified to remove foam. Removal of foam between layers of the hull and/or deck is not allowed.

Engine compartment ventilation tubes may be modified, aftermarket, relocated on the original equipment ducting, or removed. Inlet and outlet openings may not be enlarged (i.e., when the tube is removed, the opening may not be larger than stock). Vents may be shielded or plugged. No other modifications to the hood will be allowed.

ENGINE : All spec eligible Engines may be bored a MAX of 1mm. Yamaha Waveblaster may upgrade to 701 62T style cylinders. Pre-1996 Yamaha Waveblaster may update to 1996 and newer engine components. Replacement piston assemblies may be used provided the original port timing, dome profile, skirt length and shape and type of material are not changed. Replacement piston assemblies must weigh within $\pm 5.00\%$ of original equipment. Chamfering of cylinder ports must not exceed 1.00mm (0.04 in.) at a 30 degree maximum angle. (See diagram in Appendix.) Cylinders may be machined to accept girdle system cylinder heads.

Replacement starter motor and bendix may be used. Replacement engine mounts may be used.

Appendix—Spec Classes Addendum

Crankshaft may be rebuilt using replacement counterweights, crank pins, bearings and connecting rods. Counterweights, crank pins and connecting rods made of non-ferrous metals are not allowed. Stroke and rod length may not be changed. Counterweights on non-rebuildable style crankshafts may be machined to accept a press-through crank pin. Replacement bearings must maintain their original type and dimensions. Replacement counterweights must resemble the original part (i.e., holes and/or pockets not existing on the original part may not be on the replacement part). Total weight of the crank- shaft assembly must be within ±5.00% of original equipment. Crankpins may be welded and/or keyed to the counterweights.

Repairs to cracked or punctured crankcases may be made provided only one damaged area affecting one cylinder bank has been repaired. Crankcase drain and cable may be removed and plugged. No other modifications or repairs are allowed. External modifications to the engine finish (e.g., plating, polishing and/or painting) are allowed for cosmetic purposes only.

No internal modifications of any kind, including grinding, surfacing, polishing, machining, shot peening, etc., will be allowed on any engine components.

Kawasaki, Polaris and Yamaha Cylinder heads and gasket may be modified or aftermarket providing they do NOT exceed 190lbs of compression. Kawasaki, Polaris and Yamaha aftermarket or OEM head domes must not go below .040 head squish clearance at any point. Sea Doo HX heads may be modified but may not go below .051 head squish clearance and may not exceed 175lbs of compression. Drop down style domes are not allowed on any model.

Kawasaki, Polaris and Yamaha Exhaust manifold, head pipe, expansion chamber, gaskets and all hoses between expansion chamber and exhaust exit may be modified/ altered or aftermarket. Only exhausts originally manufactured as a wet style systems will be allowed. Exhausts originally intended as dry type systems may NOT be used. No water jacked chambers are allowed. Exhaust exit may be relocated to the rear of the hull. Waterbox may be relocated and aftermarket. Flow control valves may be used. No tuned portion of the exhaust shall protrude outside the hull. Through-hull exhaust outlet flap may be removed. Electronic water injection is NOT allowed on any model. Sea Doo HX must retain unmodified stock HX exhaust system and waterbox. Sea Doo HX may not use stinger sprayers or water injectors.

Replacement of general maintenance parts (e.g., gaskets, seals, spark plugs, spark plug wires, spark plug caps, wiring, water hoses, fuel lines, clamps and fasteners) shall not be restricted to original equipment providing the following:

- 1) Replacement gaskets may be used. Base gasket must remain OEM thickness for each individual model or as outlined in service manual.
- Fasteners (e.g., bolts, nuts and washers) may not be substituted with titanium pieces unless originally equipped. Fasteners may integrate locking mechanisms.
- 3) Sea Doo HX may upgrade to larger bolts or studs for the exhaust system.

AIR/FUEL DELIVERY: Polaris Hurricane and Yamaha Waveblaster Carburetor(s) may be modified or aftermarket provided they do not vent or spill fuel at any attitude with or without the engine running. The number of venturis cannot exceed the number of cylinders. No slide-type carburetors. Kawasaki X2 (05-07) and Sea Doo HX must retain stock carbs from that model; but may be rejetted. Aftermarket primer may be used.

Polaris Hurricane and Yamaha Blaster Intake manifold assembly may be modified or aftermarket. Kawasaki X2 (05-07) and SeaDoo HX must retain OEM intake manifold from factory. Aftermarket crankcase-pressure-operated fuel pumps may be used. Additional carburetor pulse line fittings may be installed on the crankcase.

Modified or aftermarket vapor/air separators must not exceed 2 in. x 6 in., and must have a return line to the fuel tank open at all times. Additional fuel reservoirs may not be used. Aftermarket or modified electric fuel pumps, not exceeding 4 psi, may be used. When the engine is shut off or stops, the fuel pump must automatically stop. No manually operated on/off-type fuel pumps are allowed.

The entire fuel system is a closed system. The watercraft must not vent or spill fuel at any attitude with or without the engine running. Original equipment fuel tank, fuel filler and relief valve must be used and cannot be modified. The fuel pickup, fuel filter and fuel petcock assembly may be removed and/or after-market parts may be used. Additional fuel filters may be used and fuel cell foam may be added to the original equipment fuel tank. Fuel tank filler cap may be modified or aftermarket provided a hazard is not created.

Flame arrester(s) which satisfy United States Coast Guard, SAE-J1928 Marine or UL-1111 Marine backfire flame arrester test standards must be installed. Aftermarket flame arresters satisfying one of these test standards will be allowed. Intake silencer may be removed.

Reed valve assemblies may be modified or aftermarket. Reed spacers may be added. Rotary valve must remain OEM stock from factory.

IGNITION AND ELECTRONICS: RPM limiter function may be modified. Polaris and Yamaha model CDI units may be modified or aftermarket provided ignition timing is not manually adjustable. Original equipment charging system must be used. Timing may not be advanced at the stator plate. Kawasaki X2 may use ignition jumper for heat sensor. Flywheels must be OEM stock and unmodified as provided from the factory. Coils, plug wires and plug caps may be aftermarket. No other ignition system modifications will be allowed.

Replacement batteries are allowed but must fit into the original equipment battery box and be securely fastened.

Engine temperature sensor may be disconnected and/or removed.

DRIVELINE: Stator vane assembly must remain OEM stock from factory. Pump mounting plate and/or pump shoe may be modified or aftermarket. Titanium driveshafts are not allowed. Impeller may be modified or aftermarket. Pump nozzle and directional nozzle may be modified or aftermarket. Overall length of the complete pump and nozzle assembly may be no more than 50.00mm (1.97 in.) longer than original equipment. Aftermarket nozzle-trim systems may be used. Kawasaki, Polaris and Yamaha models may add additional cooling fitting. Visibility spout must be removed or plugged. Silicone adhesive sealant may be used in addition to original equipment seal to seal pump inlet. Couplers, bearing housing and driveshaft may be modified or aftermarket provided they maintain a 1:1 drive ratio between the engine and the pump. SeaDoo HX may backdate to 580 PTO. Kawasaki X2 may use aftermarket pump cones.

International Affiliates

INTERNATIONAL AFFILIATES

23.1 AFFILIATE DIRECTORY

The IJSBA international affiliates, countries they represent and National Codes assigned by the IJSBA are:

<u>Country</u>	<u>Affiliate</u>	Code	Page
Argentina	AJS	. RA	95
Australia	AJSBA	. A	95
Austria	AJSA	. AU	95
Bahamas			95
Belgium	BJSBA	. В	95
Bermuda	PWAB	. BE	95
Brazil	BJSA	. BR	96
Bulgaria			96
Canada	WCWA	. C	96
Cayman Islands			96
China	CJSBA		96
Costa Rica	ACOJETS	. CR	96
Croatia	JSSH	. CA	97
Czech Republic		-	97
Denmark	DJSU	. DK	97
El Salvador	JEMA		
England	JSBA		97
Estonia	F.IMSF	FS	97
Finland	SISY	FI	98
France		F	
Germany	GIRA	. ו ח	
Groop	GJNA	. Dם	
Greece	C ISDA	. D	
Hollond		. G	90
		. INL	98
Hong Kong	HKJSBA		98
Hungary	MJSJ	. H	99
Indonesia	IJBA	. KI	99
Iran			99
Ireland	IJSA	. IR	99
Israel	ILMSA	. IL	99
Italy	FIM	.	99
Jamaica			100
Japan	JJSF	. J	100
Korea	KJSBA	. K	100
Kuwait	KJSF	. KW	100
Malaysia	MNWSC	. ML	100
Mexico	AMMJ	. M	100
Morocco			100
New Zealand	NZJSBA	. NG	100
Nigeria	NJSBA	. NZ	101
Norway	NMF	. N	101
Oman			101
Paraguay	APMS	. PY	101
Peru	APEPA	PF	101
Philippines	ISAP	RP	101
Poland	PISBA	PI	102
Portugal	FPJS	P	102
Oatar		∩∆	102
Sorbio	1999	SM	102
Serbia	N70	. SIVI	102
Slovenia		. 57	102
South Africa	SAJSBA	. ZA	102
spain		. ⊑	103
	IJC	. IH	103
I nalland	IJSBA	. I	103
UAE			103
United States	IJSBA, APBA	. US	103
Uruguay	AUJMA	. U	103
23.2 ARGENTINA

AJS (Association Argentina de Motos de Agua y Jet Ski) Dean Funes 437 Capital Federal, Buenos Aires, 1214 Attn: Miguel Manghesi Phone: 54 1 956 1371

23.3 AUSTRALIA

AJSBA (Australian Jet Sports Boating Association) PO Box 307, Morphett Vale SA 5162 Attn: Tammy Hawkes Phone: 61 4 1960 9337 secretary@<u>ajsba.org.au</u>

23.4 AUSTRIA

Alpen Adria Cup Brodtischgasee 28 2700 Wr. Neustadt Attn: Thomas Reiterer PHONE: +436644119222 Fax: +4326222987122 info@aac-jetskiracing.com

23.5 BAHAMAS

Bahamas Ocean Sports Authority 5th Floor Centerville House 2nd Terrace West-Collins Ave. Nassau Attn: Rich Ryan Phone: 242 422 3250 <u>Roger@eoep.com</u>

23.6 BELGIUM

Belgian Jetsport Boating Federation(BJBF) Chaussee De Bruxelles 72 7020 Dampremy Attn: Peter De Smet Phone: 32 473 560244

23.7 BERMUDA

Personal Watercraft Association of Bermuda (PWAB) Radnor Court #1 CR-01 Attn: Chris Smith Phone: 441 500 1313 www.pwab.org chris@telecom.bm

Brazil - Costa Rica

23.8 BRAZIL

BJSA (Brazilian Jet Sports Association) Av. dos Bandeirantes 3655 Moema Sao Paulo SP 04086-020 Attn: David Haddad Junior Phone: 55 11 5093-2838 www.bjsa.com.br bjsa@bjsa.com.br

23.9 BULGARIA

Bulgarian Jet Ski Federation Simeonovo district 166, Simeonovsko shosse Sofia Attn: Mrs. Silvia Panagonova Phone: +359 2 9611361 bfjski_sport@abv.bg

23.10 CANADA

WCWA (Western Canadian Watercross Association) 212 Berard Cres. Fort McMurray, Alberta T9K-1V9 Attn: Mike & Carla Klippenstein Phone: 780-791-7825 www.klipperracing.com Klipper@klipperracing.com

23.11 CAYMAN ISLANDS

Cayman Islands Watercraft Association (CIWA) PO Box 30165 SMB Grand Cayman Attn: Vincent G. Ramgeet, director Phone: 345-925-4810 Fax: 345-814-0450 Vincent.ramgeet@time4lime.com

23.12 CHINA

Contact IJSBA

23.13 COSTA RICA

ACOJETS (Association Costarricense de Motos Acuaticas San Jose, 5133-1000 Attn: Jurgen Larsson Phone: (506) 221 7748 Fax: (506) 223 0085

23.14 CROATIA

JSSH (Jet Ski Savez Hrvatske) M. Gupca 97 49210 Zabok Attn: Dalibor Turkovic Phone: 385 49 222 501 Fax: 385 49 500 201 jssh@hi.htnet.hr

23.15 CZECH REPUBLIC

CZAVS (Jet Ski Racing Associaton of Czech Republic) Ruska 8 101 00 Prague Attn: Vaclav Zacek Phone: +420 602 82 99 14 www.czavs.cz info@czavs.cz

23.16 DENMARK

DJSU (Danish Jet Sport Union) Jegstrupvej 140 8361 Hasselager Attn: Steen V. Pedersen Phone: 45 70 200 600; Fax: 45 86 292 861

23.17 EL SALVADOR

JEMA International Jet Ski El Salvador Maya Association 67 ave sur Centro Comercial Roma L-20 Colonia Roma San salvador, El Salvador, C.A Phone: 503 22838947 and 503 22750288

23.18 ENGLAND

Brain Lee The JSRA PO Box 8813 Leicester, LE9 0AY Great Britain Tel/Fax: 01455 840751 EMAIL: info@jsra.co.uk Website: www.jsra.co.uk

23.19 ESTONIA

(EJMSF) Estonian Jetski and Snowmobile Sport Federation Kentmanni 19 Tallinn, 10116 Attn: Gerli F. Kaur Phone: 372 660 41 90 Fax: 372 660 41 93 info@ejmsf.ee

Finland – Hong Kong

23.20 FINLAND

SJSL (Suomen JetSport Liitto) Tolkkistentie 993 06750 TOLKKINEN Attn: Sammy Pajalin Phone: 358 40 7727720 Fax: 358 9 8866 6090 www.sjsl.fi sammy.pajalin@contrarian.fi

23.21 FRANCE

Contact IJSBA

23.22 GERMANY

GJRA (German Jetsport and Racing Association) Sportplatzsiedlung 15 91353 Hausen Attn: Klaus Wagner Phone: 49 170 5455880 falccon@gmx.net

23.23 GREECE

Hellenic Motorboating Association 59, Mylleroy Str. Metaxourgeio, 10436 Athens Attn: Diamantis Konstantinos Phone: 210 9918900 Fax: 210 9918900 www.jetskigr.com jetskigr@yahoo.com

23.24 GUAM

GJSRA (Guam Jetsport Racing Association) PMB 538 - 1270 N. Marine Dr., Ste. 101 Tamuning 96913 Attn: Russell Young Phone: (671) 649-2917 Fax: (671) 649-2919 postnet@netpci.com

23.25 HOLLAND

NWSF (Nederlands Water Scooter Federation) Admiraliteitskade 85 Rotterdam, EG 3063 Attn: Herman van Oldenmark Phone: 31 10 2807553 Fax: 31 10 2809076

23.26 HONG KONG

Contact IJSBA

23.27 HUNGARY

MJSJ (Magyar Jet Ski Szovetseg) Dembinszky u. 1 Budapest 1155 Attn: Csaba Gerencser Phone: 36 1 307 6221 Fax: 36 1 307 6763 www.jet-ski.hu secretary@mjssz.hu

23.28 INDONESIA

Indonesia Jetsport & Boating Association (IJBA) Jalan Pantai Indah Mercure Hotel Taman Impian Jaya Ancol, Jakarta 10002 Attn: Mr.Syaiful Ihsan Phone: 6221.64703041 Fax: 6221.64703040 ijba_ina@yahoo.com

23.29 IRAN

Iranian Canoe- Kayak and WaterSki Federation Attn: Mr Ahmad Donyamali Phone: 98 21 88 01 33 91 Fax: 98 21 88 00 67 16 ir_canoe@yahoo.com

23.30 IRELAND

IJSA (Irish Jet Sport Association) 6 Ballyrogan Road Bradshaws Brae Co Down BT23 4ST, N Ireland Attn: Robin Adair Phone: 44 28 91 827151 www.irishjetsportassociation.co.uk robin.adair@btconnect.com

23.31 ISRAEL

IL.M.S.A. (IsraeL.Motor.Sport.Association) P.O.Box 246 Holon 58100 Attn: Barouch Shalit, Pres. Phone: 972 3 5048686 Fax: 972 3 5016454 www.motor-sport.co.il

23.32 ITALY

CONTACT IJSBA

23.33 JAPAN

JJSF (Japan Jet Sports Federation) 8-20-34, Ginza, Chuo-ku Tokyo 104 Attn: Takahiro Yoshimura Phone: 81 3 3543 7321 Fax: 81 3 3543 7328

23.34 KOREA

KJSBA (Korea Jet Sports Boating Association) 88-2 Bang 1-Dong Song Pa-Gu Seoul 138-050 Attn: Kim Jong-Woon Phone: 82 2 533 3366 Fax: 82 2 533 7953

23.35 KUWAIT

Kuwait Jet Ski Federation (KJSF) P.O. BOX 5863 Safat, 13059 Attn: General Fahed Alfahed Phone: 965 5710131 Fax: 965 5743818 www.kssclub.com kssclub2@hotmail.com

23.36 MALAYSIA

Malaysian National Water Sports Council (MNWSC) 347 Batu 2-1/2 Jalan Ipoh Kuala Lumpur, 51200 Attn: Belee Chung Phone: 603 44143088 Fax: 603 4420201

23.37 MEXICO

Contact IJSBA

23.38 MOROCCO

Contact IJSBA

23.39 NEW ZEALAND

New Zealand Jet Sports Boating Association (NZJSBA) PO Box 80154 Green Bay, Auckland Attn: Lisa Dermott, President Phone: 64 3 3557049 www.nzjetsport.org.nz nzjsba@xtra.co.nz2

23.40 NIGERIA

Nautical Jet Sports Boating Association of Nigeria (NJSBA) 16 Imani Housing Estate Maitama Abuja Attn: Bem Ibrahim Garba Phone: 234 803 453 4039 Fax: 234 9 413 7991 bengarba@wave-com.net

23.41 NORWAY

Norges Motorsportforbund (NMF) Nedre Storgate 13 3015 Drammen Attn: Per Mangerud Phone: +47 32016180 Fax: +47 32016186 nmf@nmfsport.no

23.42 OMAN

Oman Water Sports Committee P.O Box:57 101 Oman Attn: Adel Bin Suwaid AL Abri, Secre Phone: 00968-24755170 Fax: 00968-24793767

23.43 PARAGUAY

APMS (Asociacion Paraguaya de Moto Ski) Madame Lynch 413 c/0 Bertoni Asuncion Attn: Roberto Valasquez Phone: 595 21 671 631 Fax: 595 21 671 630

23.44 PERU

ASOCIACION PERUANA DE MOTOS ACUATICAS Av Angamos Oeste 355 Miraflores Attn: Anibal Aliaga Swidin, Pres. Phone: 51 583 10 47 www.jetskiperu.com presidencia@jetskiperu.com

23.45 PHILIPPINES

JSAP (Jet Sports Association of the Philippines) BLK 3, Lot 1, Phase IV-G, Along C-4 Road Dagat-Da 1470 Melabon City Attn: Paul Gerard B. Del Rosario Phone: (632)-288-3401 Fax: (632)-287-2859 irmafishing@hotmail.com

Poland – South Africa

23.46 POLAND

Polish Jet Sports Boating Association (PJSBA) ul. Ptasia 5 80035 Gdansk Attn: Piotr Szczep Phone: +48 601666777 Fax: +48 58 3091388 www.jetski.pl pisba@jetski.pl

23.47 PORTUGAL

FPJS (Federacao Portuguesa de Jet Ski) Rua De S. Marcal 77-79 1200-419 Lisboa Attn: Francisco Pita, Pres. Phone: 351 21 324 0388 Fax: 351 21 346 0207 www.fpjetski.pt geral@fpjetski.pt

23.48 QATAR

QMSF (Qatar Marine Sports Federation) P.O. Box 23311 Doha Attn: Shk. Hassan Bin Jabor Al Thani Phone: 974 4319110 Fax: 974 4357809

23.49 SERBIA

Jet Ski Association of Serbia (JSSS) Nevesinjska 2 Belgrade, 11000 Attn: Dragana Tutorovic, President Phone: 381 11 3065340 Fax: 381 11 655911 www.eurojetsport.com info@eurojetsport.com

23.50 SLOVENIA

Slovene Nautical Association (NZS) Spelina Ulica 2 2000 Maribor Attn: Borut Lukman Phone: +386 2 330 1666 Fax: +386 2 330 1665 borut@ma-tisk.si

23.51 SOUTH AFRICA

SAJSBA (South African Jet Sport Boating Association) PO Box 1398 Bella Bella 0480 Attn: SJ Muller Phone: 27 82 822 7851 Fax: 27 11 394 6029 www.sajsba.co.za info@sajsba.co.za

23.52 SPAIN

Inter-Globe Sport Avda Juan Carlos I Edf Torre-Cristal plta 3 Attn: Membership Dept. Phone: 34 968308200 Fax: 34 968858077 ortiz22@attglobal.net

23.53 TAHITI

TJC (Tahiti Jet Club) Bp: 111167 98709 Mahina Attn: André TRIMAILLE Phone: (689) 483 796 Fax: (689) 483 796 www.tahitijetclub.pf andretahiti@mail.pf

23.54 THAILAND

TJSBA (Jet Sports Boating Association of Thailand) 1099 Prachachuen 35 Bangsue Bangkok, 10800 Attn: Mr. Sittichai Suebsahakarn Phone: 662 585 5700 Fax: 662 587 9909 www.tjsba.com info@tjsba.com

23.55 UAE

UAE Marine Sports Federation P.O.Box 24883 Attn: Mr. Saeed Hareb, Vice Chairman Phone: +9714 3995777 Fax: +9714 3994148 www.dimc-uae.com dimcdxb@emirates.net.ae

23.56 URUGUAY

AUJMA ASOCIACION URUGUAYA DE JETSKI Y MOTOS DE AGUA DALIAS ESQUINA RACINE CIUDAD DE LA COSTA URUGUAY PHONE 00598 2 6826098 bruno_casa@hotmail.com President BRUNO CASA

United States

24.1 UNITED STATES

24.1.1 The following organizations are supported by the IJSBA to sanction events in the United States:

INTERNATIONAL JET SPORTS BOATING ASSOCIATION

330 Purissima Street Ste. C Half Moon Bay, CA 94019

Phone (714) 751-8695 Fax (714) 751-8609 E-mail: info@ijsba.com

AMERICAN POWER BOAT ASSOCIATION (APBA)

American Power Boat Association (APBA) 17640 Nine Mile Road Eastpointe, MI 48021

Attn: Patrick Mell Phone: (586) 773-9700 Fax: (586) 773-6490 www.apbapwr.com patrickmell@aol.com

24.1.2 The following organizations are supported by the IJSBA to promote events in the United States

Great Lakes Watercross

Contact: Scott Hyke 3806 Tulane Avenue Madison, WI 53714 Phone: 608/575-3037 E-mail: scott@greatlakeswatercross.com www.greatlakeswatercross.com

Upstate Watercraft Promotions

Contact: AJ & Jennifer Handler 1937 Fairport 9 Mile Point Road Penfield, NY 14526 Phone: 585/388-0049 Fax: 585/388-7144 E-mail: info@uwpinc.com www.uwpinc.com

Freeride and US Motosurf (West)

On Course Events Attention: CarolAnne Giustina 981 Tulare Ave. South Lake Tahoe, CA 96150 carolannegiustina@mac.com

Nauti Water Racing

705 N. Broadway Wichita, KS 67214 Attn: Terri Hiebert Tel: (316)-312-4049 Fax: (316)-260-8886 Email: <u>mainevents21@msn.com</u>

R5Water-XRacing

Brian Smith or Jennifer Jeter 2814 Lineville Dr #104E Farmers Branch TX, 75234 Main Phone: 214-498-3592 Home: 972-488-6980 E-mail: <u>R5Water-XRacing@hotmail.com</u>

DMP Motorsport

dmpmotorsport.com 18120 Grand ave Lake Elsinore, CA 92530 ph 951-609-3623 fax 951-609-3624 email <u>dmpmotorsports@msn.com</u>

Daytona Freeride

Attn: Nick Foederer www.daytonafreeride.com

Promoters Organized By The American Power Boat Association (APBA)

Desert Steel Motorsports Contact: Jim Russell 1100 Vista Drive Lake Havasu City, AZ 86404 Phone: 928/764-2210 Fax: 928/764-2218 E-mail: info@DSMevents.com www.dsmevents.com

R.P.M. Racing Enterprises

Contact: Ross Wallach 1803 Morgan Lane Redondo Beach, CA 90278 Phone: 310/ 318-4012 Fax: 310/372-7427 E-mail: <u>rossdboss26@yahoo.com</u> www.scscracing.com

PM Sports Marketing

Contact: Patrick Mell 49734 Maurice Drive Chesterfield, MI 48047 Phone: 586/598-2856 Fax: 586/773-6490 E-mail: patrickmell@aol.com www.pwcfun.com

Hammertime Promotions

Contact: Jacque Bryant 5225 East 225th Street Noblesville, IN 46062 Phone: 317/877-0789 E-mail: jbryant@watercross.com www.watercross.com

Surf and Turf Promotions

Contact: Mike Young 1007 76th Street Bradenton, FL 34209 Phone: 850/376-5495 E-mail: mpyoungjr@aol.com www.pwcfun.com

COMPETITION CLASSES

25.1 COMPETITION CLASSES (IJSBA)

- 25.1.1 The following competition classes are typical of what may be offered at IJSBAsanctioned events. Event promoters have the option to decide which classes are offered depending on local interest. Competitors should contact event promoters for information regarding the specific classes that will be offered.
- 25.1.2 Riders intending to compete at national tour or world championship events and/or qualifiers should be aware of the specific rules and classes applicable to those events. For information regarding national and world championship classes, go to www.ijsba.com.
- 25.1.3 For a watercraft to be eligible for competition in Regional and National events in the United States, the manufacturer must produce a minimum of 500 (200 for Ski Division) identically manufactured units of a model and make those units available for sale through the manufacturer's normal means of U.S. distribution (see Homologation).

Beginner Ski Women Ski Veterans Ski Ski Lites Ski Stock Ski Limited Ski Open Ski Modified /GP

Sport Spec Sport Modified Beginner Runabout Women Runabout Veterans Runabout Masters Runabout Runabout Lites Runabout Stock Runabout Stock Runabout Open Runabout Open Runabout Modified /GP (Popular Additional Runabout Distinctions: 800cc, 1300cc, Normally Aspirated, Classic)

Freestyle

Contact IJSBA for additional class suggestions and to obtain a list of current alternative classes (i.e. Vintage Ski, 550 Superstock, X2, etc.)

Classes should be further distributed by skill designation (i.e. Novice, Expert, Pro or combined skills such as Amateur and Pro-Am.

THE IJSBA HIGHLY ADVISES AGAINST NOVICES OPERATING OPEN, MODIFIED, OR GP CLASS PWC!

Note:

In all 800cc Ski Classes, all normally aspirated two-stroke watercraft may increase engine displacement to 850cc maximum displacement.

Competition Classes

CHART 25.1 GIBILITY

25.1.4 FOUR STROKE ELIGIBILITY CHART

2008 Class Eligibility for 0-1600cc Four-stroke Runabout

Vormally aspirated and turbocharged/supercharged four-stroke watercraft may compete in the current 1300 Stock, Limited, and Open classes. Watercraft may compete in higher-level classes (i.e., a Stock-class boat may compete in Limited or Open)



Normally aspirated and turbocharged/supercharged four-stroke watercraft may compete in the current 800 Stock, Limited, and Open classes. Watercraft may compete in higher-level classes (i.e., a Stock-class boat may compete in Limited or Open)



RELEASE AND WAIVER OF LIABILITY

26.1 RELEASE AND WAIVER OF LIABILITY

26.1.1 The following is a condition of participation. Every participant will be required to sign the release and waiver form at each IJSBA-sanctioned event before participating.

RELEASE AND WAIVER OF LIABILITY, ASSUMPTION OF RISK AND INDEMNITY AGREEMENT FOR IJSBA EVENTS

I Assume the risk of serious injury or death. Personal Watercraft racing is a high speed activity where numerous persons are navigating a very tight buoy course in a competitive and aggressive manner. Personal Watercraft do not have brakes, water spray frequently causes limited visibility, and changing water conditions make for an inconsistent atmosphere in all parts of the race course. Collisions are frequent as are mechanical failures, spin outs, loss of control, and mental errors. Endurance and Freeride/Freestyle activities carry equal dangers and risks as closed course. It is a strong possibility that I will be injured, or even killed, while participating in a Personal Watercraft competition and I still chose to participate in this event despite this possibility:_____ (Initials).

IN CONSIDERATION of being permitted to compete, officiate, observe, work for, or participate in any way in the EVENT(S) or being permitted to enter for any purpose any RESTRICTED AREA (defined as any restricted area requiring special authorization, credentials or permission to enter or any area which admission by the general public is restricted or prohibited including but not limited to the competition area), EACH OF THE UNDERSIGNED, for himself, his personal representatives, heirs and next of kin:

- Acknowledges, agrees and represents that he or she has or will immediately upon entering any of such RESTRICTED AREAS, and will continuously thereafter, inspect the RESTRICTED AREAS which he or she enters. He or she further agrees and warrants that if at any time he or she is in or about RESTRICTED AREAS and feels anything to be unsafe, he or she will immediately advise the officials of such and will leave the RESTRICTED AREAS and/or refuse to participate further in the EVENT(S).
- 2. Acknowledge that this event is not produced by the IJSBA. This event is produced by an independent promoter who is responsible for all safety aspects of the event. The skill levels, speeds, track size, experience/inexperience of participants may be drastically different from other sanctioned events and rhere may be a higher frequency of aggressiveness and competitiveness as well as a higher degree of inexperienced competitors who are more prone to errors. There is no warranty or guarantee that competitors actual skill matches the skill designated on their license and/or classification.
- HEREBY RELEASE, WAIVES, DISCHARGES AND COVENANTS NOT TO SUE the International Jet Sports Boating Association, Inc. (IJSBA), the promoters, participants, racing associations, other sanctioning organizations, or any subdivisions thereof, track operators, course owners, officials, riders, pit crews,

Release and Waiver of Liability – continued

rescue personnel, any persons in any RESTRICTED AREA, promoters, sponsors, advertisers, owners or lessees of premises used to conduct the EVENT(S), premises and event inspectors, surveyors, underwriters, consultants and others who give recommendations, directions or instructions or engage in risk evaluation or loss control activities regarding the premises or EVENT(S) and each of them, their directors, officers, agents and employees, all for the purposes herein referred to as "Releasees," FROM ALL LIABILITY TO THE UNDERSIGNED, his personal representatives, assigns, heirs and next of kin FOR ANY AND ALL LOSS OR DAMAGE, AND ANY CLAIM OR DEMANDS THEREFORE ON ACCOUNT OF INJURY TO THE PERSON OR PROPERTY OR RESULTING IN DEATH OF THE UNDERSIGNED ARISING OUT OF OR RELATED TO THE EVENT(S), WHETHER CAUSED BY THE NEGLIGENCE OF THE RELEASEES OR OTHERWISE.

- 4. HEREBY AGREES TO INDEMNIFY AND SAVE AND HOLD HARMLESS the Releasees and each of them FROM ANY LOSS, LIABILITY, DAMAGE OR COST they may incur arising out of or related to the EVENT(S) WHETHER CAUSED BY THE NEGLIGENCE OF THE RELEASEES OR OTHERWISE.
- HEREBY ASSUMES FULL RESPONSIBILITY FOR ANY RISK OF BODILY INJURY, DEATH OR PROPERTY DAMAGE arising out of or related to the EVENT(S) WHETHER CAUSED BY THE NEGLIGENCE OF THE RELEASEES OR OTHERWISE.
- HEREBY ACKNOWLEDGES THAT THE ACTIVITIES OF THE EVENT(S) ARE VERY DANGEROUS and involve the risk of serious injury and/or death and/or property damage. Each of THE UNDERSIGNED also expressly acknowledges that INJURIES RECEIVED MAY BE COMPOUNDED OR INCREASED BY NEGLIGENT RESCUE OPERATIONS OR PROCEDURES OF THE RELEASEES.
- 7. HEREBY agrees that this Release and Waiver of Liability, Assumption of Risk and Indemnity Agreement extends to all acts of negligence by the Releasees, INCLUDING NEGLIGENT RESCUE OPERATIONS and is intended to be as broad and inclusive as is permitted by the laws of the Province or State in which the EVENT(S) is/are conducted and that if any portion thereof is held invalid, it is agreed that the balance shall, notwithstanding, continue in full legal force and effect.
- HEREBY UNDERSTANDS that failure for the undersigned to maintain a valid medical insurance policy will automatically mean that I declare I am self insured for \$25,000 before utilizing IJSBA's supplemental insurance.
- 9. THE UNDERSIGNED grants permission to the International Jet Sports Boating Association, Inc., sponsors, event sponsors, event promoters and their assigns, to use their voice and/or likeness, photographs and photographs of their personal watercraft in advertising and promotion material, feature use including radio, television, motion picture film, video tape, newspapers, magazines, programs and all other media in connection with advertising and purposes of trade, and agrees to display sponsor and IJSBA emblem on the chest of rider's vest or racing uniform, and the sponsor and IJSBA decal on both sides of the personal watercraft while competing in any IJSBA event.

Release and Waiver of Liability – continued

THE UNDERSIGNED IS A MEMBER IN GOOD STANDING OF THE IJSBA AND/OR HAS APPLIED FOR MEMBERSHIP IN THEIJSBA, and agrees to abide by the IJSBA rules as set forth in the IJSBA Official Competition Rule Book, as these rules may be amended or interpreted from time to time.

I HAVE READ THIS RELEASE AND WAIVER OF LIABILITY, ASSUMPTION OF RISK AND INDEMNITY AGREEMENT, FULLY UNDERSTAND ITS TERMS, UNDERSTAND THAT I HAVE GIVEN UP SUBSTANTIAL RIGHTS BY SIGNING IT FREELY AND VOLUNTARILY WITHOUT ANY INDUCEMENT, ASSURANCE, OR GUARANTEE BEING MADE TO ME AND INTEND MY SIGNATURE TO BE A COMPLETE AND UNCONDITIONAL RELEASE OF ALL LIABILITY TO THE GREATEST EXTENT ALLOWED BY LAW.



MODULAR FLOATING DOCK & PWC SYSTEMS

ARE YOU READY TO MAKE SOME WAVES?

The Wave Dock[™] is a modular floating dock platform that revolutionizes the way lake and ocean home owners and marinas customize their floating dock systems; Available in an amazing new Pebble Beach textured finish, bringing a rich new look to the industry. With the proprietary patent pending H-Beam Channel Lock System[™], these dock sections are infinitely modular, assemble quickly, and offer a solid connection platform with just the right mix of rigidity and flexibility. Each floating dock section is 60 inches wide x 120 inches long x 16 inches tall, allowing the system to be easily assembled into the exact configuration needed. With a full line of accessories and custom attachments the Wave Dock[™] has set the new standard for modular floating dock systems. Visit us online at <u>www.wavearmor.net</u>



OFFICIAL SPONSOR OF TH





18720 Crenshaw Boulevard,Torrance,CA90504 U.S.A http://www.quakysense.us E-Mail:info@quakysense.us



We're in favor of closed courses...





And we oppose closed waters.

From the racers in Havasu to recreational riders from coast to coast, the AWA fights the good fight for the Good People.

We defeat two-stroke bans in Montana, keep waters open to PWC use in Texas, and fight against anti-PWC legislation from Florida to Washington state. The locations change, but the attacks on our personal freedoms will continue. The American Watercraft Association

is committed to equal access for all on our nation's waterways. As the only consumer based PWC organization, we need your commitment too.

Become an AWA member, and add your voice to ours.

Sign up for your membership now and we'll include a complimentary subscription to Ride PWC Magazine and its expanded Speed Zone section, featuring pages of extensive race and event coverage!!

Log on to awahq.org for membership details, and ...











